

Maintenance Schedule

Item	DISTANCE COVERED (KMS) / MONTHS WHICHEVER IS EARLIER										
	5000/3 month	10000/ 6month	20000/ 9month	30000/ 12month	40000/ 15month	50000/ 18month	60000/ 21month	70000/ 24month	80000/ 27month	90000/ 30month	100000/ 33month
Engine											
Engine oil	R	I	R	I	R	I	R	I	R	I	R
Engine oil filter	R	-	R	-	R	-	R	-	R	-	R
Auto tensioner and belt	-	-	-	-	-	-	I	-	I	-	R
Coolant	I	I	I	I	I	I	I	I	R	I	I
Air, Fuel and Exhaust											
Air filter element	-	-	-	-	R	-	-	-	R	-	-
Fuel filter cartridge	-	-	R	-	R	-	R	-	R	-	R
Exhaust pipe mountings and damage/leakage	-	I	I	I	I	I	I	I	I	I	I
Water sediments drain - fuel filter (or when indicator illuminates)	I	I	I	I	I	I	I	I	I	I	I
Note: Under extreme operating conditions replace air filter element every 20,000 kms											

Item	DISTANCE COVERED (KMS) / MONTHS WHICHEVER IS EARLIER										
	5000/3 month	10000/ 6month	20000/ 9month	30000/ 12month	40000/ 15month	50000/ 18month	60000/ 21month	70000/ 24month	80000/ 27month	90000/ 30month	100000 /33month
Transaxle											
Transaxle oil	-	-	R	-	-	-	-	-	-	-	R
IRDA and PTU											
IRDA oil	R	-	-	-	-	R	-	-	-	-	R
PTU oil	R	-	-	-	-	R	-	-	-	-	R
Brakes											
Brake and clutch fluid - level check	-	-	I	I	R	I	I	I	R	I	I
Parking brake	I	-	I	-	I	-	I	-	I	-	I
Front and rear brake pads / calliper	-	I	I	I	I	I	I	I	I	I	I

Item	DISTANCE COVERED (KMS) / MONTHS WHICHEVER IS EARLIER										
	5000/3 month	10000/ 6month h	20000/ 9month h	30000/ 12month th	40000/ 15month th	50000/ 18month th	60000/ 21month th	70000/ 24month th	80000/ 27month th	90000/ 30month th	100000 /33month th
Suspension											
Front suspension bolts torque		-		-		-		-		-	
Rear suspension bolts torque		-		-		-		-		-	
Suspension bushes	-	-	-	-		-	-	-		-	-
Suspension arms and links	-	-	-	-		-	-	-		-	-
Steering											
Power steering fluid - level check											
Wheel alignment	Inspect if abnormal condition					-	-	-		-	-
Electrical											
Battery electrolyte level and specific gravity	-										
All Lights, Horns, Wipers and Washers	-										
Head light aiming	-										

Item	DISTANCE COVERED (KMS) / MONTHS WHICHEVER IS EARLIER										
	5000/3 month	10000/ 6month	20000/ 9month	30000/ 12month	40000/ 15month	50000/ 18month	60000/ 21month	70000/ 24month	80000/ 27month	90000/ 30month	100000/ 33month
Heating/Air conditioning											
Particle filter	-	C	C	C	C	C	C	C	C	C	C
Final inspection											
Tyre pressure	I	I	I	I	I	I	I	I	I	I	I
Under body, nuts and bolts for tightness	-	I	I	I	I	I	I	I	I	I	I
Road test	I	I	I	I	I	I	I	I	I	I	I
Tyre rotation	-	I	I	I	I	I	I	I	I	I	I
Service reminder indicator reset	I	I	I	I	I	I	I	I	I	I	I

I - INSPECT and CORRECT, R - REPLACE, C - CLEAN

Recommended lubricants and filling capacities

SYSTEM	LUBRICANT NAME	FILLING QUANTITY, LITRES	SPECIFICATION	REMARKS
Engine	MAHINDRA "MAXMILE CROWN"	6.0 lit	Exceeds APICH-4; SAE 1 ^{5W-40}	For other than Maxim ile brand, oil change interval has to be reduced to 10000 km if the oil meets minimum of API CH-4 SAE 15W-40 specification
Engine oil filter	Mahindra "Maximile Universe"		Recommend to use only the genuine filter for better engine protection and lubricant life.	
Engine cooling	MAHINDRA "MAXIMILE ULTRA COOL" (READY TO USE COOLANT. NO NEED TO MIX WATER)	8.0 lit	Brand specific. Don't use other coolants / water for top up. In case of emergency, coolant meeting JIS K2234 specification should be used (30% concentration diluted with distilled water) and coolant change period to be reduced as 30,000 km	
Transaxle	MAHINDRA "MAXIMILE SYNTEC 75W-90"	3.0 lit	Special Manual Transmission Fluid	As alternate, Castrol Syntrans 75W-90 can be used. Avoid mixing of two different brands. No other brand recommended.

SYSTEM	LUBRICANT NAME	FILLING QUANTITY, LITRES	SPECIFICATION	REMARKS
IRDA (Only for AWD models)	MAHINDRA "MAXIMILE DO 80W-90 EXL"	1.2 lit	SPECIAL AXLE FLUID	For other than Maxim ile brand, oil change interval has to be reduced to 20000 km if the oil meets minimum of API GL5 SAE 80W- 90 specification
PTU (Only for AWD models)	MAHINDRA "MAXIMILE DO 80W-90 EXL"	0.8 lit.	SPECIAL AXLE FLUID	For other than Maxim ile brand, oil change interval has to be reduced to 20000 km if the oil meets minimum of API GL5 SAE 80W- 90 specification
Power steering	SHELL Make "SPIRAX S3ATFMD3"/ CALTEX Make "TEXAMATIC 1 888"	0.7 lit for FWD	DEXRON III	Brand specific and no other brands recommended
		0.9 lit for AWD		
Brake and Clutch	CASTROL "Brake Fluid DOT4"or SHELL MAKE "BRAKE & CLUTCH FLUID DOT 4"	1.0 lit	Brake Fluid meeting SAE J1703 FMVSS No.116 DOT 4 or IS 8654 Type-2 Specification	

Maintenance Schedule



SYSTEM	LUBRICANT NAME	FILLING QUANTITY, LITRES	SPECIFICATION	REMARKS
Recommended Fuel	High Speed Diesel confirming to IS 1460; 2010 specification or equivalent	70 ± 2 lit		