

QINGDAO EVERUN MACHINERY CO., LTD.



WHEEL LOADER ER1220



1200kg
Rated Loading



1920mm
Maximum Dump Height



0.26m³
Standard Bucket Capacity



3600x1200x2170mm
Overall Dimension

- Kubota Euro5/Epa4 Engine
- Italy Brand Hydrostatic Driving System
- Italy Brand 4 Wheels Driving Motors
- Quick Hitch, Adjustable Steering Wheel
- Inching Function, Electric Hand Brake
- Folded Canopy, Electric Tipping Cabin
- Front 2 Wheel Of The Driving Motor With Service Brake



WHEEL LOADER

ER1220



SPECIFICATION:

Performance	Rated loading	1200kg
	Overall weight	1900kg
	Rated bucket capacity	0.26m ³
	Maximum tractive force	12kN
	Maximum breakout force	15kN
	Maximum grade ability	21°
	Maximum dump height	1920mm
	Maximum dump reach	600mm
	Overall dimension (L×W×H)	3600*1200*2170mm
	Minimum turning radius (outside of wheels)	2420mm
	Oscillation angle	8°
Engine	Model	KUBOTA D1105 (Euro5/EPA4)
	Type	Inline water cooled, four stroke
	No. of cylinder-bore/stroke	3—78×78.4mm
	Displacement	1.123L
	Rated power	18.2kW
	Idel speed	850-900r/min
	Rated speed	3000r/min
	Maximum torque N.m @speed	70.4@2200r/min
Transmission System	Type	Closed piston pump
	Gear shift	Electric, Stepless
	Maximum speed	L0-11 H 0-22
Drive Axles	Main reducing mode	Hydrostatic driving
	Wheel base (mm)	
	Wheel tread(mm)	
Hydraulic System	Ground clearance	210mm
	System working pressure	19Mpa
	Boom lifting time	3.2s
	Total time	6.3s
	Fuel tank capacity	40L
	Function of leveling automatically	Yes
	Service brake	Hydrostatic brake
Tyre	Parking brake	Electronic parking
	Type specification	26-12.12
	Front tyre pressure	350kPa
	Rear tyre pressure	350kPa