

A large orange tower crane is shown from a low angle, looking up. The crane's lattice structure is prominent, and the white operator's cab is visible. The crane arm extends across the top of the frame. The background is a solid black rectangle.

ACE

Tower Cranes



**INDIA'S NO. 1
CRANE BRAND**

About ACE



Corporate Office

ACE - Action Construction Equipment Limited is India's largest Mobile Crane and Tower Crane manufacturing company. In addition to Tower Cranes, ACE also offers Mobile Cranes, Loaders, Vibratory Roller, Truck Mounted Cranes, Crawler Cranes, Forklifts, Tractors and other Construction Equipment. ACE has a consolidated presence in all major Infrastructure, Construction, Heavy Engineering and Industrial Projects across the country.

The policy of responding with speed and expertise has been rewarded over the years in the form of repeat business, resulting in constant growth of the company and making us one of the leading companies in the Mobile Cranes, Tower Cranes and Construction Equipment sector in the country.



Corporate Office

Another factor driving our growth has been the versatility of our equipment to satisfy a vast range of possible applications. Our equipment has been successfully used in many sectors like Infrastructure Construction, Power, Ports & Shipyards, Dams, Metro Rail, Roads, Mining, Steel, Engineering, Automobile, Railways, Cement, Petroleum, Defence, Chemicals & Fertilizer, Warehousing, Logistics, Building Construction etc., to name a few.



Tower Crane Plant



**International Brand
Consulting Corp., USA**
India's Most Trusted
Company 2017





Planman Media
Power Brands India
Super Power Edition 2017-18
India's 70 Most Trusted
Power Brands



Equipment India
Best Seller in
Mobile Cranes 2017

TOWER CRANE RANGE

Model	Maximum Capacity (t)	Free Standing Height (m)	Jib Length (m)	Tip Load (t)	Mast Size L x B x H (m)	Mast Types
TOWER CRANES - SELF ERECTING						
MTC-2418	1.6	24	18	0.55	(-)	
MTC-3625	2.5	36	25	0.80	(-)	
TOWER CRANES - FIXED / INNER CLIMBING / RAIL MOUNTED						
TC 5034	5	34.5	50	1.3	1.2 x 1.2 x 3.0	L12.16
TC 5040	5/6	40.0	50	1.3	1.6 x 1.6 x 2.8	B16.10
TC 5540	5/6	40.0	55	1.0	1.6 x 1.6 x 2.8	B16.10
TC 5040T	5	40.0	50	1.3	1.6 x 1.6 x 2.8	B16.10
TC 5540T	5	40.0	55	1.0	1.6 x 1.6 x 2.8	B16.10
TC 6040	5/6	40.0	60	1.0	1.6 x 1.6 x 2.8	B16.12
TC 6040B	5/6	40.0	60	1.0	1.6 x 1.6 x 2.8	B16.12
TC 6552	10	51.3	65	2.0	1.83 x 1.83 x 3.0	B18.14
TC 7052-A	12	52.0	70	3.0	2.15 x 2.15 x 3.0	B20.16A
TC 7054	16	52.0	70	3.5	2.15 x 2.15 x 3.0	B20.16B
TC 7059	20	59.0	70	5.2	2.15 x 2.15 x 3.0	B20.16C
TC 7074	25	73.0	70	5.2	2.50 x 2.50 x 5.95	B25.16



The Economic Times
Economic Times
Infra Focus – 2017



Construction Word
Annual Awards 2017
India's Top Challengers
2016-17 Trophy





Equipment India
Best seller in
Mobile Cranes Category
2016


MTC 2418 Mobile Tower Crane

1.6 t

- MTC-2418 is an **all-terrain, self propelled** mobile tower crane, with a road speed of 25 km/hr. A differential lock enables it to get out of tough spots.
- MTC-2418 is **self erecting/self-folding**. Operations can be easily affected in a few minutes by a single operator through a remote control pod.
- MTC-2418 is **remote controlled**. It facilitates the operator to position himself in such a way that he can see both picking as well as dumping points for precise load positioning.
- A **built-in generator**, driven by the prime mover's engine makes MTC-2418 totally independent of any outside electric source. The crane only uses a part of the power and the generator can be used to supply other electrical equipment like mixers, vibrators and job site lighting systems.
- An articulated chassis and hydraulic steering system enables a very **short turning radius and easy positioning**.
- Stabilizers are of out and down type and can be retracted into the lower chassis to satisfy **road clearance codes**.



ALL DIMENSIONS IN METRES ±5%



Horizontal jib position	Height	15.5 mtrs.
	Length	7.5 mtrs. 18 mtrs.
	Capacity	1600 Kgs. 550 Kgs.
Raised jib position	Height	24 mtrs.
	Length	7.2 mtrs. 15.8 mtrs.
	Capacity	1600 Kgs. 550 Kgs.
Speed	Trolleying	33m/min.
	Hoisting	15m/min. & 30m/min.
	Slewing	1 RPM
Electrical motors	Trolleying	1.5 H.P.
	Hoisting	7.5 H.P.
	Slewing	2.0 H.P.
Electric Power		10.25 KVA
Engine (Prime mover)		Four cylinder, water cooled, diesel engine developing 49 BHP at 2300 RPM. Model A498
Generator Power Developed		20 KVA
Total weight with Ballast		13500 Kgs.
Total weight without Ballast		8700 Kgs.
Transportation Dimensions	Width	2.5 mtrs.
	Length	10 mtrs.
	Height	3.9 mtrs.
Front axle load		5300 Kgs.
Rear axle load		8200 Kgs.
Safety device		• Circuit breakers • Overload limit switch • Moment limit switch • Hoist limit switch • Trolley limit switch
Variant Model		MTC 2418 T Mounted on a towable trailer without prime mover.

MTC 2418




MTC 2418 T - Mounted on a towable trailer



MTC 3625 Mobile Tower Crane

2.5 t

- MTC-3625 is a **self erecting/self folding** mobile tower crane. Operations can be easily affected by a single operator, through a remote control pod.
- The crane is mounted on a **towable type trailer** with compact dimensions for easy transportation.




Prime mover (optional)



- MTC-3625 is **controlled by a remote**. This facilitates the operator to position himself in such a way that he can see both picking as well as dumping points for precise load positioning.


MTC 3625 in folded position




- To minimise dead weight for long distance transportation, the counter weight box is designed with trap doors to enable **general ballast use as counter weight**.

- The chassis design enables a short turning radius and **easy positioning**.

- Stabilizers are out and down type and can be reiterated into the lower chassis to satisfy **road clearance codes**.



- An optional prime mover with a **built-in 25KVA** generator, makes MTC-3625 totally independent of any outside electric source and a separate carrier vehicle. The crane uses only a part of the power and the generator can be used for other site equipment like mixers, vibrators and job site lighting systems.



MTC 3625



ALL DIMENSIONS IN METRES ±5%


Horizontal jib position	Height Reach Capacity	23 mtrs. 7.5 mtrs. 2500 Kgs. 25 mtrs. 800 Kgs.
Raised jib position	Height Reach Capacity	36 mtrs. 7.2 mtrs. 2500 Kgs. 21.6 mtrs. 800 Kgs.
Speed	Trolleying Hoisting Slewing	30m/min. 20m/min. & 40m/min. 1 RPM
Electrical motors	Trolleying Hoisting Slewing	1.5 H.P. 10.0 H.P. 2.0 H.P.
Electric Power		12.5 KVA
Total weight with Ballast		17000 Kgs.
Total weight without Ballast		8000 Kgs.
Transportation Dimensions	Width Length Height	2.5 mtrs. 11.5 mtrs. 3.2 mtrs.
Safety device		• Vfd • Circuit breakers • Overload limit switch • Moment limit switch • Hoist limit switch • Trolley limit switch
Optional		Prime mover fitted with 49 BHP, water cooled diesel engine and a 25 KVA alternator.

TC 5034 Tower Crane

5 t

Load Capacity



Jib Length	Radius (m)		15	17	20	22	25	28	30	32	35	40	45	50
	Hoisting Load (t)		5.00	4.30	3.60	3.20	2.70	2.50	2.40	2.20	2.00	1.70	1.50	1.30
Jib Length 50m	Hoisting Load (t)		2.50						2.50	2.40	2.20	1.85	1.59	
Jib Length 45m	Hoisting Load (t)		5.00	4.60	3.80	3.40	2.90	2.50	2.50	2.40	2.20	1.85	1.59	
Jib Length 40m	Hoisting Load (t)		5.00	4.80	3.90	3.50	3.00	2.50	2.50	2.45	2.20	1.92		
Jib Length 35m	Hoisting Load (t)		5.00	4.80	3.90	3.50	3.00	2.75	2.50	2.45	2.20			
Jib Length 30m	Hoisting Load (t)		5.00	4.80	3.90	3.50	3.00	2.75	2.50					
Jib Length 25m	Hoisting Load (t)		5.00	4.80	3.90	3.50	3.10							



Specifications

Hoisting	No of Falls								
	Speed (m/min)		7	35	70	3.5	17.5	35	
	Hoisting Load (t)		2.6	2.6	1.3	5.0	5.0	2.6	
	Power (kw)		3.5	18.0	18.0	3.5	18.0	18.0	
Slewing			Speed(rpm)		0 ~ 0.8				
			Power(kw)		4				
Trolley			Speed(m/min)		40		20		
			Power(kw)		3.3		2.2		
Climbing			Speed(m/min)		0.55 - 0.7				
			Power(kw)		5.5				
Main Supply			415V / 50Hz						
Electric Power			25.3 kw (31.7 kVA)						

F1	◇ 75t	△ 90t	
F2	◇ 55.5t	△ 72.5t	22t



F Reaction ◇ In Service △ Out of Service ⊠ Dead weight without load and counter weights but with longest jib and free standing height.


P - Vertical load

TC 5040 Tower Crane

5 t

Load Capacity

Jib Length 50m	Radius (m)	2.5~16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50
	Hoisting Load (t)	5.00	4.56	4.04	3.62	3.27	2.97	2.72	2.50	2.31	2.15	2.00	1.87	1.75	1.64	1.54	1.46	1.37	1.30
		2.50																	
Jib Length 44m	Radius (m)	2.5~18	20	22	24	26	28	30	32	34	36	38	40	42	44				
	Hoisting Load (t)	5.00	4.62	4.14	3.74	3.41	3.13	2.88	2.67	2.48	2.31	2.16	2.03	1.91	1.80				
		2.50																	
Jib Length 38m, 32m, 26m	Radius (m)	2.5~18	20	22	24	26	28	30	32	34	36	38							
	Hoisting Load (t)	5.00	4.88	4.38	3.96	3.61	3.31	3.05	2.83	2.63	2.46	2.30							
		2.50																	




Note:-

TC 5040 is also available with 32 Mtrs & 26 Mtrs Jib length optionally

Specifications


Hoisting	No of Falls							
	Speed (m/min)		11.75	40	80	5.87	20	40
	Hoisting Load (t)		2.5	2.5	1.28	5	5	2.56
	Power (kw)		5	18	18	5	18	18
Slewing			Speed(rpm)		0 ~ 0.6			
			Power(kw)		5.5			
Trolley			Speed(m/min)		40		20	
			Power(kw)		3.3		2.2	
Climbing			Speed(m/min)		0.55 - 0.7			
			Power(kw)		5.5			
Main Supply			415V / 50Hz					
Electric Power			26.8kw (33.5kVA)					
Optional		6 Ton Max. Capacity Mechanism at 14.16m						

Outrigger Stationary




F1	◇ 68t	△ 86t
F2	◇ 46t	△ 71t

Chassis Stationary/Rail Mounted



31t



F Reaction ◇ In Service △ Out of Service Dead weight without load and counter weights but with longest jib and free standing height.


P - Vertical load

TC 5540 Tower Crane

5 t

Load Capacity

Jib Length 55m	Radius (m)	2.5~13.64	16	18	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	53	55
	Hoisting Load (t)	5.00	4.70	3.90	3.24	2.93	2.66	2.43	2.24	2.06	1.91	1.78	1.66	1.55	1.46	1.37	1.29	1.21	1.15	1.06	1.00
Jib Length 50m	Radius (m)	2.5~16	18	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50			
	Hoisting Load (t)	5.00	4.56	3.62	3.27	2.97	2.72	2.48	2.31	2.15	2.00	1.87	1.75	1.64	1.54	1.46	1.37	1.30			
Jib Length 44m	Radius (m)	2.5~18	22	24	26	28	30	32	34	36	38	40	42	44							
	Hoisting Load (t)	5.00	4.14	3.74	3.43	3.13	2.88	2.67	2.48	2.31	2.16	2.03	1.91	1.8							
Jib Length 38m	Radius (m)	2.5~18	22	24	26	28	30	32	34	36	38										
	Hoisting Load (t)	5.00	4.38	3.96	3.61	3.31	3.05	2.83	2.63	2.46	2.30										




Specifications


Hoisting	No of Falls								
	Speed (m/min)		11.75	40	80	5.87	20	40	
	Hoisting Load (t)		2.5	2.5	1.28	5	5	2.56	
	Power (kw)		5	18	18	5	18	18	
Slewing			Speed(rpm)		0 ~ 0.6				
			Power(kw)		2 x 2.2				
Trolley			Speed(m/min)		40		20		
			Power(kw)		3.3		2.2		
Climbing			Speed(m/min)		0.55 - 0.7				
			Power(kw)		5.5				
Main Supply			415V / 50Hz						
Electric Power			25.7kw (32.1 kVA)						
Variant Model			6 Ton Max. Capacity Mechanism at 13.64m						

Outrigger Stationary

Chassis Stationary/Rail Mounted



F1	◇ 72t	△ 86t	
F2	◇ 43t	△ 66t	
			32 t



F Reaction ◇ In Service △ Out of Service 32 t Dead weight without load and counter weights but with longest jib and free standing height.


P - Vertical Load

TC 5040-T Flat Top Tower Crane

5 t

Load Capacity


Jib Length 50m	Radius (m)	2.8~15	18	20	22	25	28	30	32	35	38	40	42	45	48	50
	Hoisting Load (t)	5.00	4.51	3.87	3.54	2.98	2.62	2.39	2.21	1.91	1.75	1.66	1.52	1.42	1.30	1.23
Jib Length 45m,40m	Radius (m)	2.8~15	18	20	22	25	28	30	32	35	38	40	42	45		
	Hoisting Load (t)	5.00	4.62	4.12	3.63	3.17	2.70	2.55	2.31	2.11	1.82	1.78	1.60	1.53		
Jib Length 35m	Radius (m)	2.8~18	20	22	25	28	30	32	35							
	Hoisting Load (t)	5.00	4.42	3.91	3.41	3.01	2.75	2.55	2.28							
Jib Length 30m,25m, 20m	Radius (m)	2.8~18	20	22	25	28	30									
	Hoisting Load (t)	5.00	4.70	4.26	3.63	3.21	2.93									




Specifications

Hoisting	No of Falls								
	Speed (m/min)		11.75	40	80	5.87	20	40	
	Hoisting Load (t)		2.5	2.5	1.28	5	5	2.56	
	Power (kw)		5	18	18	5	18	18	
Slewing		Speed(rpm)		0 ~ 0.6					
		Power(kw)		5.5					
Trolley		Speed(m/min)		40		20			
		Power(kw)		3.3		2.2			
Climbing		Speed(m/min)		0.55 - 0.7					
		Power(kw)		5.5					
Main Supply			415V / 50Hz						
Electric Power			26.8kw (33.5 kVA)						
Variant Model			6 Ton Max. Capacity Mechanism at 14.16m						

Outrigger Stationary




Chassis Stationary/Rail Mounted



F1	◇ 59t	△ 75t
F2	◇ 81t	△ 97t

32.0t



F Reaction ◇ In Service △ Out of Service Dead weight without load and counter weights but with longest jib and free standing height.
P - Vertical Load

TC 5540-T Flat Top Tower Crane

5 t

Load Capacity

Jib Length 55m	Radius (m)		2.8~15	18	20	22	25	28	30	32	35	38	40	42	45	48	50	52	55
	Hoisting Load (t)		5.00	4.26	3.67	3.34	2.87	2.46	2.27	2.07	1.85	1.63	1.53	1.41	1.29	1.16	1.09	1.02	0.93
			2.50							2.34	2.14	1.91	1.70	1.60	1.48	1.35	1.23	1.16	1.09
Jib Length 50m	Radius (m)		2.8~15	18	20	22	25	28	30	32	35	38	40	42	45	48	50		
	Hoisting Load (t)		5.00	4.51	3.87	3.54	2.98	2.62	2.39	2.21	1.91	1.75	1.66	1.52	1.42	1.30	1.23		
			2.50							2.28	1.98	1.82	1.73	1.59	1.49	1.37	1.30		
Jib Length 45m,40m	Radius (m)		2.8~15	18	20	22	25	28	30	32	35	38	40	42	45				
	Hoisting Load (t)		5.00	4.62	4.12	3.63	3.17	2.70	2.55	2.31	2.11	1.82	1.78	1.60	1.53				
			2.50							2.38	2.18	1.89	1.85	1.67	1.60				
Jib Length 35m	Radius (m)		2.8~18	20	22	25	28	30	32	35									
	Hoisting Load (t)		5.00	4.42	3.91	3.41	3.01	2.75	2.55	2.28									
			2.50							2.35									
Jib Length 30m,25m, 20m	Radius (m)		2.8~18	20	22	25	28	30											
	Hoisting Load (t)		5.00	4.70	4.26	3.63	3.21	2.93											
			2.50																

40.0m

30m

62.4m

54m

84.8m

78m

107.2m


100m

126.8m

120m

140.0m

132m




Anchorage Diagram


Specifications

Hoisting	No of Falls							
	Speed (m/min)		11.75	40	80	5.87	20	40
	Hoisting Load (t)		2.5	2.5	1.28	5	5	2.56
	Power (kw)		5	18	18	5	18	18
Slewing			Speed(rpm)		0 ~ 0.6			
			Power(kw)		2 x 2.2			
Trolley		Speed(m/min)		40		20		
		Power(kw)		3.3		2.2		
Climbing		Speed(m/min)		0.55 - 0.7				
		Power(kw)		5.5				
Main Supply			415V / 50Hz					
Electric Power			25.7kw (32.1 kVA)					
Variant Model		6 Ton Max. Capacity Mechanism at 13.5m						


Outrigger Stationary



Chassis Stationary/Rail Mounted



F1	◇ 59t	△ 75t	32.9t
F2	◇ 81t	△ 97t	



F Reaction ◇ In Service △ Out of Service 32.9t Dead weight without load and counter weights but with longest jib and free standing height.
P - Vertical Load

TC 6040 Tower Crane

5 t

Load Capacity

Jib Length 60m	Radius (m)		2.5~16		18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	54	56	60
	Hoisting Load (t)		5.00		4.40	3.90	3.48	3.14	2.85	2.61	2.40	2.21	2.05	1.91	1.78	1.66	1.56	1.46	1.38	1.30	1.23	1.10	1.08	0.94
			2.50										2.27	2.11	1.97	1.84	1.72	1.62	1.52	1.44	1.36	1.29	1.16	1.14
Jib Length 54m	Radius (m)		2.5~16		18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	54			
	Hoisting Load (t)		5.00		4.83	4.28	3.83	3.46	3.15	2.88	2.65	2.45	2.27	2.12	1.98	1.85	1.74	1.64	1.54	1.46	1.24			
			2.50										2.33	2.18	2.04	1.91	1.80	1.70	1.60	1.52	1.30			
Jib Length 48m	Radius (m)		2.5~18		20	22	24	26	28	30	32	34	36	38	40	42	48							
	Hoisting Load (t)		5.00		4.48	4.01	3.63	3.30	3.02	2.78	2.57	2.39	2.23	2.08	1.95	1.83	1.54							
			2.50										2.29	2.14	2.01	1.89	1.60							
Jib Length 42m	Radius (m)		2.5~18		20	22	24	26	28	30	32	34	36	42										
	Hoisting Load (t)		5.00		4.48	4.01	3.63	3.30	3.02	2.78	2.57	2.39	2.23	1.83										
			2.50										2.29	1.90										

40.0m

62.4m

82.0m

101.6m


121.2m

30m

51m

72m


93m




Specifications

Hoisting	No of Falls							
	Speed (m/min)		11.75	40	80	5.87	20	40
	Hoisting Load (t)		2.5	2.5	1.28	5	5	2.56
	Power (kw)		5	18	18	5	18	18
Slewing			Speed(rpm)		0 ~ 0.6			
			Power(kw)		2 x 2.2			
Trolley			Speed(m/min)		20		40	
			Power(kw)		2.2		3.3	
Climbing			Speed(m/min)		0.55 - 0.7			
			Power(kw)		7.5			
Main Supply			415V / 50Hz					
Electric Power			25.7 kw (32.1kVA)					
Variant Model			6 Ton Max. Capacity Mechanism at 13.76m					

Outrigger Stationary




Chassis Stationary/Rail Mounted



F1	◇ 80t	△ 95t
F2	◇ 60t	△ 74t

	⊗ 34.5t
--	---------



F Reaction ◇ In Service △ Out of Service ⊗ Dead weight without load and counter weights but with longest jib and free standing height.
P - Vertical Load

TC 6040B Tower Crane

5 t

Load Capacity

Jib Length 60m	Radius (m)		2.5~18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50	54	60
	Hoisting Load (t)		5.00	4.51	4.04	3.65	3.32	3.04	2.80	2.59	2.41	2.24	2.10	1.97	1.85	1.74	1.64	1.55	1.47	1.32	1.14
		2.50										2.30	2.16	2.03	1.91	1.80	1.70	1.61	1.53	1.38	1.20
Jib Length 54m	Radius (m)		2.5~19	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	54		
	Hoisting Load (t)		5.00	4.83	4.33	3.92	3.57	3.27	3.02	2.79	2.60	2.42	2.26	2.12	2.00	1.88	1.78	1.68	1.44		
		2.50										2.32	2.18	2.06	1.94	1.84	1.74	1.50			
Jib Length 48m	Radius (m)		2.5~19	20	22	24	26	28	30	32	34	36	38	40	42	48					
	Hoisting Load (t)		5.00	4.83	4.33	3.92	3.57	3.27	3.02	2.79	2.60	2.42	2.26	2.12	2.00	1.68					
		2.50										2.32	2.18	2.06	1.74						
Jib Length 42m, 36m	Radius (m)		2.5~19	20	22	24	26	28	30	32	34	36	42								
	Hoisting Load (t)		5.00	4.83	4.33	3.92	3.57	3.27	3.02	2.79	2.60	2.42	2.00								
		2.50										2.06									

40.0m

30m

56.8m

54m

79.2m


78m

101.6m

102m

7m


12m




Specifications

Hoisting	No of Falls							
	Speed (m/min)		11.75	40	80	5.87	20	40
	Hoisting Load (t)		2.5	2.5	1.28	5	5	2.56
	Power (kw)		5	18	18	5	18	18
Slewing		Speed(rpm)			0 ~ 0.6			
		Power(kw)			2 x 2.2			
Trolley		Speed(m/min)			20		40	
		Power(kw)			2.2		3.3	
Climbing		Speed(m/min)			0.55 - 0.7			
		Power(kw)			7.5			
Main Supply			415V / 50Hz					
Electric Power			25.7 kw (32.1kVA)					
Variant Model			6 Ton. Max Capacity Mechanism at 15.53 M					

Outrigger Stationary



F1	◇ 81t	△ 96t	🏗️
F2	◇ 61t	△ 75t	34.8t



F Reaction ◇ In Service △ Out of Service 🏗️ Dead weight without load and counter weights but with longest jib and free standing height.
P - Vertical Load

TC 6552 Tower Crane

10 t

Load Capacity

Jib Length 65m	Radius (m)		3.2~15.68	18	20	22	25	28	30	32	35	38	40	42	45	48	50	52	55	58	60	63	65
	Hoisting Load (t)		10.00	8.48	7.47	6.65	5.68	4.92	4.51	4.15	3.68	3.30	3.07	2.87	2.60	2.36	2.22	2.09	1.92	1.76	1.66	1.53	1.45
			5.00									4.70	4.23	3.85	3.62	3.42	3.15	2.91	2.77	2.64	2.47	2.31	2.21
Jib Length 60m	Radius (m)		3.2~17.2	18	20	22	25	28	30	32	35	38	40	42	45	48	50	52	55	58	60		
	Hoisting Load (t)		10.00	9.48	8.36	7.45	6.38	5.55	5.09	4.69	4.18	3.75	3.50	3.28	2.98	2.72	2.57	2.42	2.23	2.05	1.95		
			5.00									4.73	4.30	4.05	3.83	3.53	3.27	3.12	2.97	2.78	2.60	2.50	
Jib Length 55m	Radius (m)		3.2~18.27	20	22	25	28	30	32	35	38	40	42	45	48	50	53	55					
	Hoisting Load (t)		10.00	9.04	8.02	6.70	5.99	5.50	5.07	4.53	4.07	3.81	3.57	3.25	2.97	2.81	2.58	2.45					
			5.00									4.62	4.36	4.12	3.80	3.52	3.36	3.13	3.00				
Jib Length 50m	Radius (m)		3.2~18.88	20	22	25	28	30	32	35	38	40	42	45	48	50							
	Hoisting Load (t)		10.00	9.34	8.35	7.16	6.24	5.74	5.30	4.73	4.26	3.98	3.74	3.41	3.12	2.95							
			5.00									4.81	4.53	4.29	3.96	3.67	3.50						
Jib Length 45m,40m	Radius (m)		3.2~21.1	22	25	28	30	32	35	38	40	42	45										
	Hoisting Load (t)		10.00	9.55	8.22	7.19	6.61	6.11	5.48	4.95	4.64	4.36	3.95										
			5.00										4.65	4.50									


70.5m

51.3m

36m

63m


97.5m




Specifications

Hoisting	No of Falls					
	Speed (m/min)		0 ~ 45	0 ~ 90	0 ~ 22.5	0 ~ 45
	Hoisting Load (t)		5.0	2.5	10.0	5.0
	Power (kw)		45	45	45	45
Slewing			Speed(rpm)	0 ~ 0.6		
			Power(kw)	2 x 5.5		
Trolley			Speed(m/min)	0 ~ 60		
			Power(kw)	5.5		
Climbing			Speed(m/min)	0.6		
			Power(kw)	11		
Main Supply		415V / 50Hz				
Electric Power		61.5kw (76.9kVA)				

Outrigger Stationary




Chassis Stationary/Rail Mounted



F1	◇ 112t	△ 166t
F2	◇ 66t	△ 86t

58t



F Reaction ◇ In Service △ Out of Service 58t Dead weight without load and counter weights but with longest jib and free standing height.
P Vertical Load

TC 7052-A Tower Crane

12 t


Load Capacity

Jib Length 70m	Radius (m)	3.75~23.0										
	Hoisting Load (t)	12.00										
		6.00										
Jib Length 65m	Radius (m)	3.75~25										
	Hoisting Load (t)	12.00										
		6.00										
Jib Length 60m	Radius (m)	3.75~25										
	Hoisting Load (t)	12.00										
		6.00										
Jib Length 55m	Radius (m)	3.75~27										
	Hoisting Load (t)	12.00										
		6.00										
Jib Length 50m	Radius (m)	3.75~27										
	Hoisting Load (t)	12.00										
		6.00										
Jib Length 45m	Radius (m)	3.75~30										
	Hoisting Load (t)	12.00										
		6.00										
Jib Length 40m	Radius (m)	3.75~30										
	Hoisting Load (t)	12.00										
		6.00										


Specifications

Hoisting	No of Falls					
	Speed (m/min)		0 ~ 42.5	0 ~ 85	0 ~ 21.25	0 ~ 42.5
	Hoisting Load (t)		6.0	3.0	12.0	6.0
	Power (kw)		55	55	55	55
Slewing		Speed(rpm)		0 ~ 0.8		
		Power(kw)		2 x 9		
Trolley		Speed(m/min)		0 ~ 58		
		Power(kw)		7.5		
Climbing		Speed(m/min)		0.5		
		Power(kw)		15		
Main Supply		415V / 50Hz				
Electric Power		80.5 kw (100.6kVA)				


Outrigger Stationary



Chassis Stationary/Rail Mounted



F1	◇ 241.8t	△ 237.7t	
F2	◇ 184.7t	△ 183.7t	86t



Anchorage Diagram

F Reaction ◇ In Service △ Out of Service ⊕ Dead weight without load and counter weights but with longest jib and free standing height.
P Vertical Load

TC 7054 Tower Crane

16 t


Load Capacity

Jib Length 70m	Radius (m)		3.75~18.0	23	25	30	35	40	45	50	55	60	65	70
	Hoisting Load (t)		16.00	12.30	11.20	8.90	7.34	6.16	5.26	4.55	3.95	3.48	3.07	2.72
			8.00					7.60	6.04	5.32	4.74	4.26	3.85	3.50
Jib Length 65m	Radius (m)		3.75~19.7	23	25	30	35	40	45	50	55	60	65	
	Hoisting Load (t)		16.00	13.30	12.0	9.67	7.99	6.74	5.77	5.01	4.38	3.86	3.42	
			8.00					7.52	6.55	5.78	5.16	4.64	4.20	
Jib Length 60m	Radius (m)		3.75~20.5	23	25	30	35	40	45	50	55	60		
	Hoisting Load (t)		16.00	14.0	12.7	10.2	8.44	7.14	6.13	5.32	4.67	4.12		
			8.00					7.91	6.90	6.10	5.44	4.90		
Jib Length 55m	Radius (m)		3.75~21.3	23	25	30	35	40	45	50	55			
	Hoisting Load (t)		16.00	14.6	13.3	10.7	8.85	7.49	6.44	5.60	4.92			
			8.00					7.22	6.38	5.70				
Jib Length 50m	Radius (m)		3.75~22.2		25	30	35	40	45	50				
	Hoisting Load (t)		16.00		13.9	11.2	9.41	7.89	6.80	5.92				
			8.00					7.57	6.70					
Jib Length 45m	Radius (m)		3.75~23.7		25	30	35	40	45					
	Hoisting Load (t)		16.00		15.10	12.2	10.10	8.60	7.42					
			8.00											
Jib Length 40m	Radius (m)		3.75~24		25	30	35	40						
	Hoisting Load (t)		16.00		15.3	12.3	10.3	8.72						
			8.00											


Specifications

Hoisting	No of Falls					
	Speed (m/min)		0 ~ 37.5	0 ~ 75	0 ~ 18.75	0 ~ 37.5
	Hoisting Load (t)		8.0	3.0	16.0	6.0
	Power (kw)		60	60	60	60
Slewing		Speed(rpm)		0 ~ 0.8		
		Power(kw)		2 x 9		
Trolley		Speed(m/min)		0 ~ 58		
		Power(kw)		7.5		
Climbing		Speed(m/min)		0.5		
		Power(kw)		15		
Main Supply		415V / 50Hz				
Electric Power		85.5 kw (106.87kVA)				


Outrigger Stationary



Chassis Stationary/Rail Mounted



F1		241.8t		237.7t		
F2		184.7t		183.7t		87t



Anchorage Diagram

F Reaction In Service Out of Service Dead weight without load and counter weights but with longest jib and free standing height.
P Vertical Load


TC 7059 Tower Crane

20 t

Load Capacity

Jib Length 70m	Radius (m)		3.5~21.19	25	30	35	38	40	43	45	48	50	53	55	58	60	63	65	68	70	
	Hoisting Load (t)		20.00	16.42	13.16	10.86	9.78	9.15	8.32	7.83	7.17	6.77	6.24	5.92	5.47	5.20	4.83	4.60	4.29	4.09	
			10.00							9.43	8.94	8.28	7.88	7.35	7.03	6.58	6.31	5.94	5.71	5.40	5.20
Jib Length 65m	Radius (m)		3.5~21.72	25	30	35	38	40	43	45	48	50	53	55	58	60	63	65			
	Hoisting Load (t)		20.00	16.92	13.57	11.21	10.10	9.45	8.60	8.10	7.42	7.02	6.47	6.14	5.68	5.41	5.02	4.79			
			10.00							9.71	9.21	8.53	8.13	7.58	7.25	6.79	6.52	6.13	5.90		
Jib Length 60m	Radius (m)		3.5~22.46	25	30	35	38	40	43	45	48	50	53	55	58	60					
	Hoisting Load (t)		20.00	17.62	14.15	11.70	10.55	9.88	9.00	8.48	7.78	7.36	6.79	6.45	5.98	5.69					
			10.00							9.59		8.89	8.47	7.90	7.56	7.09	6.80				
Jib Length 55m	Radius (m)		3.5~22.80	25	30	35	38	40	43	45	48	50	53	55							
	Hoisting Load (t)		20.00	17.94	14.42	11.93	10.76	10.08	9.18	8.65	7.94	7.52	6.94	6.59							
			10.00							9.76		9.05	8.63	7.70							
Jib Length 50,45, 40m	Radius (m)		3.5~22.96	25	30	35	38	40	43	45	48	50									
	Hoisting Load (t)		20.00	18.09	14.54	12.04	10.86	10.17	9.27	8.74	8.02	7.59									
			10.00							9.85		9.13	8.70								


Outrigger St



Specifications


Hoisting	No of Falls					
	Speed (m/min)		0 ~ 45	0 ~ 96	0 ~ 22	0 ~ 45
	Hoisting Load (t)		10.0	5.0	20.0	10.0
	Power (kw)		90	90	90	90
Slewing			Speed(rpm)		0 ~ 0.72	
			Power(kw)		3 x 5.5	
Trolley			Speed(m/min)		0 ~ 100	
			Power(kw)		11	
Climbing			Speed(m/min)		0.46	
			Power(kw)		11	
Main Supply			415V / 50Hz			
Electric Power			117.5 kw (146.9 kVA)			

Outrigger Stationary



F_1 F_2

F1	◇ 143t	△ 171t	
F2	◇ 240t	△ 256t	



Anchorage Diagram

F Reaction  In Service  Out of Service  Dead weight without load and counter weight but with longest jib and free standing height.


TC 7074 Tower Crane

25 t

Load Capacity

Jib Length 70m	Radius (m)	3.5~17.52	20	25	30	35	38	40	43	45	48	50	53	55	58	60	63	65	68	70
	Hoisting Load (t)	25.00	21.41	16.42	13.16	10.86	9.78	9.15	8.32	7.83	7.17	6.77	6.24	5.92	5.47	5.20	4.83	4.60	4.29	4.09
		12.50				11.97	10.89	10.26	9.43	8.94	8.28	7.88	7.35	7.03	6.58	6.31	5.94	5.71	5.40	5.20
Jib Length 65m	Radius (m)	3.5~17.95	25	30	35	38	40	43	45	48	50	53	55	58	60	63	65			
	Hoisting Load (t)	25.00	16.92	13.57	11.21	10.10	9.45	8.60	8.10	7.42	7.02	6.47	6.14	5.68	5.41	5.02	4.79			
		12.50				11.21	10.56	9.71	9.21	8.53	8.13	7.58	7.25	6.79	6.52	6.13	5.90			
Jib Length 60m	Radius (m)	3.5~18.56	25	30	35	38	40	43	45	48	50	53	55	58	60					
	Hoisting Load (t)	25.00	17.62	14.15	11.70	10.55	9.88	9.00	8.48	7.78	7.36	6.79	6.45	5.98	5.69					
		12.50				11.66	10.99	10.11	9.59	8.89	8.47	7.90	7.56	7.09	6.80					
Jib Length 55m	Radius (m)	3.5~18.85	25	30	35	38	40	43	45	48	50	53	55							
	Hoisting Load (t)	25.00	17.94	14.42	11.93	10.76	10.08	9.18	8.65	7.94	7.52	6.94	6.59							
		12.50				11.87	11.19	10.29	9.76	9.05	8.63	8.05	7.70							
Jib Length 50, 45, 40m	Radius (m)	3.5~18.97	25	30	35	38	40	43	45	48	50									
	Hoisting Load (t)	25.00	18.09	14.54	12.04	10.86	10.17	9.27	8.74	8.02	7.59									
		12.50				11.97	11.28	10.38	9.85	9.13	8.70									

Outrigger Stationary




F1 ↓ ↑ F2

F1	◇ 143t	△ 171t	
F2	◇ 240t	△ 256t	141t

Specifications

Hoisting	No of Falls			
	Speed (m/min)		0 ~ 45	45 ~ 90
	Hoisting Load (t)		12.5	6.3
	Power (kw)		110	110
Slewing	Speed (rpm)		0 ~ 0.72	
	Power (kw)		3 x 5.5	
Trolley	Speed (m/min)		0 ~ 100	
	Power (kw)		11	
Climbing	Speed (m/min)		0.46	
	Power (kw)		11	
Main Supply			415V / 50Hz	
Electric Power			110 kw (137.5kVA)	



Anchorage Diagram


F Reaction ◇ In Service △ Out of Service Dead weight without load and counter weights but with longest jib and free standing height.

LC 85 Luffing Crane

6 t


Load Capacity

Jib Length 40m	Radius (m)	4~18	20	25	28.5	30	32	35	40
	Hoisting Load (t)	6.0	5.2	3.7	2.9	2.6	2.3	1.9	1.4
Jib Length 35m	Radius (m)	4~18	20	25	28.5	30	32	35	
	Hoisting Load (t)	6.0	5.2	3.7	2.9	2.6	2.3	1.9	



Specifications


Hoisting	No of Falls	3			4		
	Speed (m/min)	0 ~ 40	0 ~ 66	0 ~ 80	0 ~ 20	0 ~ 33	0 ~ 40
Hoisting Load (t)	Power (kw)	24	24	24	24	24	24
	Speed (rpm)	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7
Slewing	Power(kw)	6	6	6	6	6	6
	Speed (rpm)	0 ~ 25	0 ~ 25	0 ~ 25	0 ~ 25	0 ~ 25	0 ~ 25
Travelling	Power(kw)	2 x 5.2	2 x 5.2	2 x 5.2	2 x 5.2	2 x 5.2	2 x 5.2
	Speed (m/min)	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0	≤ 3.0
Luffing	Power(kw)	24	24	24	24	24	24
	Speed (rpm)	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7	0 ~ 0.7
Main Supply	415V / 50Hz						
Electric Power	54 kw (67.5 kVA)						



F2	◇ 90t	△ 142t	⬢ 38.5t
F3	◇ 62t	△ 117t	38.5t

F1	◇ 60t	△ 81t
	⬢ 38.5t	

A	7m	11m
R1	23t	15t
R2	20t	13t
P	48t	48t
	⬢ 37t	




F Reaction ◇ In Service △ Out of Service ⬢ Dead weight without load and counter weights but with longest jib and free standing height.
P Vertical Load H Free Standing Height Jib * 40m

LC 120 Luffing Crane

8 t




Load Capacity

Jib Length 45m	Radius (m)	3.5~18.6	20	25	30	32	35	40	45
	Hoisting Load (t)	8.0	7.3	5.5	4.2	4.0	3.3	2.6	2.2
		4.0					3.3	2.6	2.2
Jib Length 40m	Radius (m)	3.5~18.6	20	25	30	32	35	40	
	Hoisting Load (t)	8.0	7.3	5.5	4.3	4.0	3.4	2.6	
		4.0					3.4	2.6	
Jib Length 35m	Radius (m)	3.5~18.6	20	25	30	32	35		
	Hoisting Load (t)	8.0	7.4	5.6	4.4	4.0	3.4		
		4.0					3.4		
Jib Length 30m	Radius (m)	3.5~18.6	20	25	30				
	Hoisting Load (t)	8.0	7.4	5.6	4.4				
		4.0							



Specifications

Hoisting	No of Falls							
	Speed (m/min)		0 ~ 40	0 ~ 66	0 ~ 80	0 ~ 20	0 ~ 33	0 ~ 40
	Hoisting Load (t)		4.0	2.4	2.0	8.0	4.8	4.0
	Power (kw)		30	30	30	30	30	30
Slewing			Speed(rpm)			0 ~ 0.7		
			Power(kw)			2 x 4.5		
Travelling			Speed(rpm)			0 ~ 25		
			Power(kw)			2 x 5.2		
Luffing			Speed(m/min)			≤ 3.5		
			Power(kw)			30		
Main Supply			415V / 50Hz					
Electric Power			69kw (86.3 kVA)					




F Reaction In Service Out of Service Dead weight without load and counter weights but with longest jib and free standing height.
 P Vertical Load H Free Standing Height Jib * 30 - 35m ** 40 - 45 m

LC 160B Luffing Crane

10 t



Load Capacity

Jib Length 55m	Radius (m)	3.3~18.0	20	22	25	27	30	32	35	37	40	42	45	47	50	52	55
	Hoisting Load (t)	10.0	8.6	7.6	6.5	5.8	5.0	4.6	4.1	3.8	3.5	3.2	2.9	2.7	2.5	2.3	2.1
Jib Length 50m	Radius (m)	3.3~20.0	22	25	27	30	32	35	37	40	42	45	47	50			
	Hoisting Load (t)	10.0	8.7	7.5	6.8	6.0	5.5	5.0	4.7	4.2	3.8	3.5	3.2	3.0			
Jib Length 45m	Radius (m)	3.3~20.0	22	25	27	30	32	35	37	40	42	45					
	Hoisting Load (t)	10.0	9.0	7.7	7.0	6.2	5.7	5.1	4.7	4.2	4.0	3.6					
Jib Length 40m	Radius (m)	3.3~20.0	22	25	27	30	32	35	37	40							
	Hoisting Load (t)	10.0	9.1	7.8	7.1	6.2	5.7	5.1	4.8	4.3							
Jib Length 35m	Radius (m)	3.3~20.0	22	25	27	30	32	35									
	Hoisting Load (t)	10.0	9.2	8.0	7.2	6.4	5.9	5.3									



Specifications

Hoisting	No of Falls						
	Speed (m/min)	0 ~ 50	0 ~ 75	0 ~ 100	0 ~ 25	0 ~ 37.5	0 ~ 50
	Hoisting Load (t)	5.0	3.0	2.0	10.0	6.0	4.0
	Power (kw)	55	55	55	55	55	55
Slewing	Speed(rpm)	0 ~ 0.7					
	Power(kw)	2 x 9					
Travelling	Speed(m/min)	0 ~ 25					
	Power(kw)	4 x 3.4					
Luffing	Speed(m/min)	≤ 3.0					
	Power(kw)	37					
Main Supply		415V / 50Hz					
Electric Power		110kw (137.5 kVA)					




F Reaction In Service Out of Service Dead weight without load and counter weights but with longest jib and free standing height.
P Vertical Load H Free Standing Height Jib * 30 - 35m * 40 - 45m *** 50m ***** 55m

LC 228B Luffing Crane

12 t



Load Capacity

Jib Length 55m	Radius (m)	3.8~17.6	20	22	25	30	31.8	35	37	40	42	45	47	50	52	55
	Hoisting Load (t)	12.0	10.4	9.4	8.0	6.3	5.8	4.9	4.4	3.9	3.5	3.1	2.9	2.6	2.4	2.3
		6.0						5.1	4.6	4.1	3.7	3.3	3.1	2.8	2.6	2.5
Jib Length 50m	Radius (m)	3.5~19.6	22	25	27	30	32	34.2	34.8	37	40	42	45	47	50	
	Hoisting Load (t)	12.0	10.0	8.8	8.0	6.8	6.3	6.0	5.8	5.2	4.6	4.2	3.7	3.4	3.05	
		6.0								5.4	4.8	4.4	3.9	3.6	3.25	
Jib Length 45m	Radius (m)	3.5~20.0	22	25	27	30	32	34.4	35	37	40	42	45			
	Hoisting Load (t)	12.0	10.4	9.0	8.1	7.0	6.4	6.0	5.8	5.3	4.8	4.4	3.9			
		6.0								5.5	5.0	4.6	4.1			
Jib Length 40m	Radius (m)	3.5~20.2	22	25	27	30	32	34.8	35.4	37	40					
	Hoisting Load (t)	12.0	10.5	9.2	8.2	7.1	6.5	6.0	5.8	5.3	4.8					
		6.0								5.5	5.0					
Jib Length 35m	Radius (m)	3.5~20.4	22	25	27	30	32	35								
	Hoisting Load (t)	12.0	10.8	9.3	8.3	7.3	6.6	6.1								
		6.0														



Specifications

Hoisting	No of Falls							
	Speed (m/min)		0 ~ 40	0 ~ 65	0 ~ 80	0 ~ 20	0 ~ 30	0 ~ 40
	Hoisting Load (t)		6.0	4.0	3.0	12.0	8.0	6.0
	Power (kw)		55	55	55	55	55	55
Slewing			Speed(rpm)			0 ~ 0.7		
			Power(kw)			2 x 9		
Travelling			Speed(m/min)			0 ~ 25		
			Power(kw)			4x3.4		
Luffing			Speed(m/min)			≤ 3.0		
			Power(kw)			45		
Main Supply			415V / 50Hz					
Electric Power			118kw (147.5 kVA)					




F Reaction In Service Out of Service Dead weight without load and counter weights but with longest jib and free standing height.

P Vertical Load H Free Standing Height Jib * 30 - 35m ** 40 - 45m *** 50m **** 55m

Technical Specifications

ACS Series

S. No.	Description	Units	HGY 13	HGY 17
1	Max Radius of Placing Boom	m	13.00	17.00
2	Max. Height Working Reach	m	15.35	19.90
3	Max.Depth Working Reach	m	5.40	11.78
4	Elevation Angle	deg.	-2 ~ 84.4	-2 ~ 84.4
5	Slewing Range	deg.	360	360
6	Motor Power	kW	4	5.5
7	Hydraulic Pressure	MPa	20	20
8	Slewing	r/min	0.46	0.2-0.3
9	Delivery Pipeline Diameter	mm	125	125
10	Length of End Hose	m	3.00	3.00
11	Footprint of machine	mxm	3.15 x 3.15	4.23 x 4.23
12	Total Weight (without counter weight)	kg	2700	4940
13	Counter weight	kg	2x900	2x1050
14	Length of Boom I	m	3.70	6.67
15	Length of Boom II	m	4.50	5.73
16	Length of Boom III	m	4.80	4.60
17	Overall Dimensions	m	6.82x3.43x3.14	10.22 x4.64x3.50
18	Weight of Heaviest Component	kg	2310	3173



Technical Specifications

ACP Series

	Description	Units	HGY 33C-3R	HGY 36C-4R
Performance	Max Radius of Placing Boom	m	32.7	36
	Free Standing Height	m	22.7	22.7
	Slewing Range	deg.	±400	±400
	Total Weight	kgs.	22000	28000
	Counter Weight	kgs.	no need	no need
	Weight of Heaviest Component	kgs.	5200	5300
	Electric Power		415V/50Hz	
Motor	Power	kW	15	30
Hydraulic System	System Pressure	MPa	30	32
	Oil Tank Capacity	ltrs.	180	180



	Controls			Radio Remote Control
				Manual
	Section of Tubular Column		(mxm)	0.75 x 0.75
	Boom Type			Hydraulically Foldable Arm Sections
	Delivery Pipeline Diameter		mm	125
	Length of End Hose		m	3
	1st Section	Length	m	15.5
		Articulation	deg.	-4.2° ~ 82.5°
	2nd Section	Length	m	9.2
		Articulation	deg.	0° ~ 180°
	3rd Section	Length	m	8.0
		Articulation	deg.	0° ~ 180°
	4th Section	Length	m	—
		Articulation	deg.	—
	Climbing Type			Hydraulic
	Internal Climbing Step Distance		m	0.60
	Floor Frame			Hole Prepared in Floor




BUILT TO PERFORM



**RELIABLE AND
DEPENDABLE
EFFICIENCY**

NETWORK



**Toll Free Help Line
1800 1800 004**

www.ace-cranes.com

MARKETING H.Q.

4th Floor, Pinnacle
Surajkund, NCR-121009
Ph.: +91-129-4550000
Fax: +91-129-4550022
E-mail: marketing@ace-cranes.com

REGISTERED OFFICE

Dudhola Link Road, Dudhola
Palwal-121102, Haryana
Ph.: +91-1275-280111
Fax: +91-1275-280133
CIN: L74899HR1995PLC053860

MUMBAI OFFICE

31, "Kalpataru Court"
Chembur, Mumbai - 400074
Ph.: +91-22-25206846, 25207070
Fax: +91-22-25207071
E-mail: acemumbai@ace-cranes.com

KOLKATA OFFICE

"Forma Towers" 84-A, Second Floor
AJC Bose Road, Kolkata - 700014
Ph.: +91-9038070630
E-mail: acekolkata@ace-cranes.com

CHENNAI OFFICE

1st Floor, "Alsa Regency", 165
Eldams Road, Alwar Pet
Chennai - 600018
Ph.: +91-44-24314253
Fax: +91-44-24314252
E-mail: acechennai@ace-cranes.com

HERE TO SERVE YOU.

SPARE PARTS & SERVICE

ACE has all India Sales and Service network operating out of all the major cities. These outlets are fully equipped to provide genuine spare parts and services by company trained engineers. These outlets are further supported by company officials based at Delhi, Mumbai, Chennai, Kolkatta, Ahmedabad, Surat, Pune, Jaipur, Chandigarh, Ranchi, Raipur, Indore, Bhubneshwar, Lucknow, Jamnagar, Hyderabad, Bangalore, Guwahati, Patna, Vizag & Kochi.



Action Construction Equipment Ltd.

Contact:



ACE reserves the right to alter any specifications without prior notice. Dimensions, weights & capacities mentioned herein are variable by $\pm 5\%$. Accessories if shown are not part of the Standard Equipment.