

Solis

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

26
SHUTTLE^{XL}



INTEGRATED
LOADER
JOYSTICK (OPTIONAL)

MULTI TIRE OPTIONS
(AGRI, INDUSTRIAL
& TURF TYRE)

QUICK ATTACHED
LOADER

SYNCHROMESH
SHUTTLE

9 FORWARD
X 9 REVERSED GEAR



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**



26
SHUTTLEXL

Solis



FEATURES S26 SHUTTLEXL	
ENGINE	
Engine Type	Mitsubishi 3-Cylinder Diesel Motor
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1319
Rated RPM (+/-25mm)	2500
Air Cleaner	Dry
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	9 Forward + 9 Reverse
Front Axle	4WD
Transmission	Constant Mesh with Synchromesh Shuttle Lever
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	21.46 @2760 fly up
Minimum Speed (Km/Hr)	1.14@rated
BRAKES	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent
Trailer load (unbraked)	1050 Kg
Inertia Braked	3000 Kg
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540/540E
PTO (actuation)	Mechanical
STEERING	
Steering	Power steering
ELECTRICAL	
Battery	12V, 65 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1 DA
Hydraulic Lifting Capacity	600 Kg
Lift Rods	Standard
Litre per Minute(LPM)	17.8

FEATURES		S26 SHUTTLEXL	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)		20	
TURNING RADIUS 			
Without brakes (m) as per standard tyres		3.02 (RHS), 3.15 (LHS)	
TYRE 			
Front		6.00-12	
Rear		8.30-20	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		1250	
Wheel Base (mm)		1570	
Total Length (mm)		2895	
Total Width (mm)		1215 (max)-1050 (min)	
Height (mm) Up to ROPS		2325	
Min Ground Clearance (mm)		240	
Front Track (mm)		885	
Rear Track (mm)		960	
OTHERS ... 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Front & Rear Weights with std. Ballast		Front weights-2 x 15	
Trailer Hitch		Towbar, drawbar (optional)	
ROPS		Yes	
OPTIONAL FEATURES 			
Cabin Option		Yes	
Tyres			
			
Radial Agri: Front I Rear	Turf: Front I Rear	Ind: Front I Rear	GALAXY PRO
6.5/80-12 280/70 R18	25x8,50-14 13.60-16	23x8,50-12 33x15,50-16,5	R- 280/70R16
Front loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220 / 522222
Fax: 91- 01882-522222 | Email: exports@sonalika.com | URL: www.solistractors.com/www.solisworld.com