

Link-Belt
EXCAVATORS • FORESTRY
DEMOLITION • MATERIAL HANDLING

linkmanualshop.com/

160X₃

SPECIFICATIONS

SAE Net Horsepower: 124 HP (92 kW)

Operating Weight: 37,919 lbs. (17 200 kg)

Digging Depth: 19 ft. 11 in. (6.06 m)



Cab

The Link-Belt X3 cab is the strongest and roomiest LBX has ever offered. The X3 cab is ROPS and FOPS Level 1 certified and is designed to be strong and safe without sacrificing operator comfort. There is plenty of room to rest work boots on the two foot rests on either side of the travel pedals and still have enough space for the straight line travel pedal (standard on 250X3 and larger).

Roomy

- 5% larger than X2 series cab
- 7% more floor space

Strong

- ROPS and FOPS Level 1 certified

Comfortable

- Fully-adjustable KAB seat, forward/backward, up/down
- Control consoles adjust independently of seat
- Adjustable arm rest angles, lumbar support, suspension

Optimum Visibility

- Sunroof with sunshade rated FOPS level 1
- Additional mirrors
- Standard rearview camera
- Wiper blade stores off front glass

Ergonomic Joysticks

- Low-effort
- Pre-wired for auxiliary hydraulics
- Function buttons for wiper swipe, horn, radio mute and one-touch idle
- Large, easy-to-push triggers

Quiet

- Pressurized cab
- 8% stronger climate control system with 8 vents
- Auxiliary sound jack to enjoy music or podcasts

Organized

- Logically located switches and controls
- Accessible 12V outlet for cell phone charging
- Cup holder
- Handy phone storage areas
- Removable ashtray; empty space can be used as an additional cup holder



High-Definition 7" LED Monitor

The Link-Belt X3's from LBX are equipped with an all new High-Definition LED monitor. The full-color 7-inch monitor is one of the largest in the industry and rivals the resolution and quality found in luxury automobiles.

The X3's user-friendly monitor panel includes an engine-idle shutdown option that safely shuts off the engine after 3 minutes of idling, conserving fuel. Another idle feature accessible from the monitor panel is the auto-idle feature that, when selected, takes the engine speed down to an idle level, conserving fuel while waiting for that next truck to show up.



The X3's use a "passive" regeneration process and the monitor clearly lets the operator know what is going on and if they need to do anything with the machine. The on-screen DPD gauge shows the level of particulate matter that the DPF is capturing and will clean it out every 8 hours by way of an Auto Regeneration. During the Auto Regeneration process, the operator does NOT have to do anything with the machine other than keep working. During a parked, or Manual Regeneration, the monitor will give the operator the appropriate instructions on what to do with the machine, making it as simple as possible.

In-Cab Control

- Select and set up attachments
- Track or monitor up to 13 service interval reminders
- Engine idle shutdown, which, when selected, safely shuts off the engine after 3 minutes of idling to conserve fuel
- Adjust hydraulic flow
- Option to adjust and set auxiliary hydraulic flows and pressures (210, 250, 300, 350 models only)
- 18 languages available

Monitor

- Fuel consumption gauge
- Full color display of standard rear view camera AND optional side-view camera on the same screen
- Monitor engine coolant and hydraulic oil temperatures
- Displays fuel level, travel mode, work mode and attachment mode
- System/Machine warning messages
- Work tool settings



A standard rear-view camera displays a panoramic view of the worksite from the rear of the machine, an optional side-view camera is available.



From the Computer Menu, you can change the monitor language, program service reminders and change auxiliary settings for flow and pressure to name a few.

Engine



Improvements over X2 engines:

- Up to 10% more fuel efficient
- Up to 8% faster
- Up to 7% more lift capacity

The fuel-efficient, powerful, productive, quiet and long-lasting Isuzu engine LBX uses in the Link-Belt X3 series meets the EPA's Interim Tier 4 (Tier 4a) requirements by way of cooled exhaust gas recirculation (EGR) technology and a diesel particulate diffuser system (DPD). The DPD consists of a diesel oxidation catalyst (DOC) and a diesel particulate filter (DPF) for "passive regeneration" of exhaust emissions. This is the cleanest running and most fuel efficient engine used in a Link-Belt excavator to date.

A new variable geometry turbocharger (VGT) helps optimize the combustion process and ensures consistent boost pressure during low engine rpm's. This maintains efficient machine performance and helps eliminate harmful nitrous oxides (NOx) from forming.

The X3 has three engine work modes to give the operator full control of the machine for the job at hand:



- **Speed Priority (SP mode)** is the fastest and most productive mode giving the operator peak machine performance to get the job done quickly.
- **Heavy (H mode)** is a perfect combination of fuel efficiency and productivity. It really is the best of both worlds!
- **Applied Power (A mode)** gives the operator 13 different engine rpm settings to choose from to easily fine tune the machine to the specific job at hand. This mode is perfect for heavy lifting, fine grading or leveling work, and pipeline contractors use it to safely set pipe down into the trench.



Intelligent Design

- Quiet
- Long-lasting
- One-touch idle and auto idle functions conserve fuel
- Idle start protects a cold engine from over-revving
- Auto engine warm up feature gradually increases engine speed until normal operating temperature is achieved

Hydraulics

The Link-Belt X3's from LBX are equipped with two Kawasaki variable-displacement axial-piston pumps and one Kawasaki gear pump installed in-line with the engine. This is the most efficient hydraulic pump layout – keeping engine rpm's low while producing plenty of hydraulic muscle.

The X3 uses an open center hydraulic system which refers to the open passage in the control valve that allows the hydraulic oil to return to tank when the control valve is centered. This design gives the machine a much smoother feeling when operating and also eliminates excess pressure throughout the system, which, in turn, helps to conserve fuel.

Powerful & Productive

- Auto Power Boost gives 9% more hydraulic pressure (power) for 8 seconds
- More speed through larger hydraulic lines
- Improved oil regeneration circuits

Safe

- Boom and arm holding valves
- Standard hydraulic control pattern change valve to move between ISO and SAE
- Standard straight-line travel on 250 class and larger
- Optional "Free Swing" auto-centers the machine over the load and takes out the pendulum effect of large, long loads

Long-lasting

- Continuous filtration of 5000-hour hydraulic oil through a 6 micron, full-flow return filter
- Less wear due to reduced back pressure



Serviceability

Easy to maintain

- Ground level access to:
 - ✓ Batteries
 - ✓ Dual fuel filters with water separators
 - ✓ Engine oil filter
 - ✓ Dual element air filter
 - ✓ Cab fresh air filter
- Green drain plug and hose
- Easy-open engine hood
- Easy-access in-cab fuse box accessible while seated in cab seat
- Side-by-side oil cooler/radiator design is easy to clean
- Quick and easy access to grease all attachment pivot points
- Grease cylinder track adjusters make adjusting track tension a breeze

Maintenance reminders

- In-cab monitor will track 13 different serviceable items:
 - ✓ 5 reminders for engine items
 - ✓ 5 for hydraulic items
 - ✓ 3 other reminders

Simple

- Flexible and heat-resistant color-coded wiring harnesses
- External fuel site gauge can be viewed from ground-level to see fuel levels
- Lube and maintenance charts posted inside toolbox for readability and protection from the elements

Performance

Improvements and Optimizations

- 7% increased lift capacity over X2 series
- 10% better fuel efficiency than X2 series
- 8% faster cycle times
- Time will be saved in switching out the attachment tools via the in-cab monitor



Innovation at Work



Durability

LBX built the Link-Belt X3 series to last, and they come with one of the best standard warranties in the industry. We back our machines with a 1-year / 1,800 hour full machine warranty, a 2-year / 3,000 hour engine warranty, and a 3-year / 10,000 hour XtraStructure warranty that even covers the turntable bearing and tub.



EMS (Extended Maintenance System) chrome pins and grease impregnated brass bushings with graphite inserts reduce wear-and-tear and can be found throughout the attachment. This design makes it possible to extend lube intervals to 6 months or 1,000 hours at all pivot points excluding the bucket which is monthly or 250 hours, whichever comes first.

Strong

- All booms and arms are ultrasound tested at the factory
- X-Pattern carbody made with high tensile strength steel
- Turntable bearing tub extends through the carbody and is welded on top and bottom
- Factory standard belly pan guard
- D-channel sideframes provide excellent impact resistance
- Cab is FOPS level 1 and ROPS certified
- Thicker steel plating on the attachment
- Standard HD linkage on 350 X3 and 470 X3 and on all Link-Belt X3 excavators ordered with factory hydraulic packages




X-Pattern carbody



Turntable bearing tub

Options

- Pre-existing mounting bosses make adding additional guarding easy
- Rubber bumper guarding
- Catwalks



D-channel sideframes



Specifications

Engine

Isuzu AM-4JJ1X Tier 4A turbocharged diesel engine with electronic control (ECM) and high pressure common-rail fuel injection, 4-cylinder, Water-cooled, Cooled Exhaust Gas Recirculation (CEGR), Intercooler, Variable-Geometry Turbocharger (VGT), Diesel Particulate Diffuser (DPD) with Diesel Oxidation Catalyst (DOC) and Diesel Particulate Filter (DPF) for "passive regeneration" of exhaust emissions, Electronic fuel pump and priming, Fuel cooler, Auto-idle start, Auto warm-up, EPF engine protection, Dual-stage fuel filtration, In-cab fuel filter restriction indicator, Remote oil filter, Green plug oil drain, Double element air filter.

SAE net horsepower... 124 hp (92 kW) @ 2,200 rpm
Displacement..... 183 cu in (3.0 L)
Maximum Torque ... 288 lb-ft (391 Nm) @ 1800 rpm
Starter 24V-4.0kW
Alternator..... 50 amp
Battery..... (2) 12-volt 72 amp hours

Cab and Controls

ROPS certified cab with climate control A/C and heat with defroster, Control panel with LED Hi-Definition color monitor, Rearview camera display, Fuel-efficiency gauge, DPF regeneration gauge, Low-effort joysticks pre-wired for auxiliary hydraulics, Control pattern changer, Safety glass windows, Sunroof with sunshade, Shockless cab suspension with four fluid mountings, KAB® reclining suspension seat, Sliding 4-position tilting control consoles, AM/FM sound system with MP3 auxiliary input jack, Digital clock, Dome light, Seat belt, Coat hook, Cup holder, Storage compartments, Floor mat, Footrests, Ashtray, 24-volt cigarette lighter, 12-volt outlet, Travel alarm, Handrails, Mirrors, Side-entry cab filter, Spare parts kit.

Four selectable working modes, Anti-theft password protection system, On-board self-diagnostic system with memory and service interval reminders, Auto-idling system, One-touch decelerator, Auto-idle engine shutdown, Auto-power boost, Neutral safety start, Gate-lock safety shutoff.

A/C Rating 20,080 BTU/h
Heater Rating 21,030 BTU/h
Sound Level - Cab Interior..... 70.0 dB(A)
Sound Level - Exterior..... 100.0 dB(A)

Hydraulic System

Open-center system, Two variable-displacement axial-piston pumps and one gear pump for pilot controls, Main control valve with one 4-spool section and one 5-spool section with auxiliary spool: stackable, Auxiliary Control System, Oil cooler, Auto-power boost, Boom and arm holding valves, 6 micron return filter, Firewall.

Hydraulic Pumps

Pump Output 2 x 37.5 gpm (142 L/min)
Pilot Pump Maximum Flow ... 5.3 gpm (20 L/min)

Relief Valve Settings

Boom/Arm/Bucket..... 4,970 psi (34.3 MPa)
in Power Boost 5,260 psi (36.3 MPa)
Swing Circuit..... 4,050 psi (27.9 MPa)
Travel Circuit 4,970 psi (34.3 MPa)

Hydraulic Cylinders

number of cylinders - bore x rod x stroke
Boom 2 - 4.5" x 3.1" x 46.4"
(115 mm x 80 mm x 1,179 mm)
Arm 1 - 4.9" x 3.5" x 50.4"
(125 mm x 90 mm x 1,280 mm)
Bucket 4.1" x 3.0" x 38.8"
(105 mm x 76 mm x 985 mm)

Swing

Planetary reduction powered by axial-piston motor, Internal ring gear with grease cavity for swing pinion, Swing bearing is single-row, shear type ball bearing, Mechanical disc swing brake, Auto-power swing.

Swing Speed..... 11.5 rpm
Tail Swing 8' 0" (2.45 m)
Swing Torque 33,264 lb-ft (45.1 kNm)

Undercarriage

X Pattern carbody with 13' 1" (3.99 m) LC long undercarriage by 6' 6" (1.99 m) track gauge, Sealed and strutted track chain with track guide, Sealed rollers and idlers, Two-speed independent hydrostatic travel with compact planetary final drive, Disc type brakes, Adjustable track tension, Carbody belly pan.

Carrier Rollers 2 per Side
Track Rollers 7 per Side
Track Link Pitch 7.5" (190 mm)
Shoes 44 per Side
Shoe Width..... 23.6" (600 mm)
Ground Pressure 5.95 psi (0.041 MPa)

Travel System

Two-speed independent hydrostatic travel with compact axial-piston motors, Hydraulic motor powered output shaft coupled to a planetary reduction drive and track sprocket, All hydraulic components mounted within the width of side frame, Automatic downshift for high torque to overcome obstacles, Spring-applied hydraulic release parking brake built into each motor, Travel motors equipped with counterbalance valve to prevent over-speeding down an incline, Single-pedal straight line travel.

Travel Speeds... 1.7 - 3.4 mph (2.8 - 5.4 km/h)
Drawbar Pull 36,194 lbf (161 kN)
Gradeability..... 70% (35°)

Attachment

Boom 16' 11" (5.15 m)

Available Arms

Digging Force

• 8' 7" (2.62 m) 17,760 lbf (79 kN)
with Auto Power Boost ... 18,880 lbf (84 kN)
• 10' 0" (3.05 m) 16,190 lbf (72 kN)
with Auto Power Boost ... 17,310 lbf (77 kN)
Bucket Digging Force..... 25,180 lbf (112 kN)
with Auto Power Boost ... 26,530 lbf (118 kN)


Lubricant and Coolant Capacity

Fuel Tank..... 79.3 Gallons (300.0 Liters)
Hydraulic System .43.6 Gallons (165.0 Liters)
Hydraulic Tank..... 23.8 Gallons (90.0 Liters)
Final Drive (per side)... 1.5 Gallons (6.0 Liters)
Swing Drive 1.3 Gallons (5.0 Liters)
Engine Oil..... 4.5 Gallons (17.0 Liters)
Coolant System..... 4.3 Gallons (16.2 Liters)

Operating Weight


Working weight with 23.6" (600 mm) shoes, 16' 11" (5.15 m) boom, 8' 7" (2.62 m) arm, 7,500 lb (3 400 kg) counterweight 1,070 lb. (484 kg) bucket 37,919 lbs. (17 200 kg)

Working Range



Machine Equipped with 16' 11" (5.15 m) Boom	Arm 8' 7" (2.62 m)	Arm 10' 0" (3.05 m)
A. Maximum reach	29' 8" (9.04 m)	30' 9" (9.38 m)
B. Maximum reach @ ground level	29' 1" (8.87 m)	30' 3" (9.22 m)
C. Maximum dig depth	19' 11" (6.06 m)	21' 4" (6.49 m)
D. Maximum dig height	30' 4" (9.24 m)	30' 6" (9.29 m)
E. Maximum dump height	21' 8" (6.61 m)	21' 11" (6.69 m)
F. Digging depth 8' (2.44 m) level bottom	19' 2" (5.85 m)	20' 8" (6.29 m)
G. Bucket rotation	178°	178°
H. Maximum vertical wall depth	16' 8" (5.08 m)	17' 2" (5.22 m)

Travel Dimensions



Lifting Capacities - ISO Ratings

Radius of Load												
8' 7" (2.62 m) Arm with 16' 11" (5.15 m) Boom and 1,050 lb. (480 kg) Bucket with Power-Boost Applied												
	5 ft 0 in (1,5 m)		10 ft 0 in (3,0 m)		15 ft 0 in (4,5 m)		20 ft 0 in (6,0 m)		25 ft 0 in (7,5 m)		Cap. à portée max.	
	 End	 Side	 End	 Side	 End	 Side	 End	 Side	 End	 Side	 End	 Side
+25 ft 0 in lb (7,5 m) kg							5,150* 2 620*	5,150* 2 620*			3,650* 1 630*	3,650* 1 630*
+20 ft 0 in lb (6,0 m) kg							7,100* 3 260*	7,100* 3 260*			3,300* 1 480*	3,300* 1 480*
+15 ft 0 in lb (4,5 m) kg							9,200* 4 280*	7,000 3 240	6,750* 3 220*	4,650 2 180	3,200* 1 450*	3,200* 1 450*
+10 ft 0 in lb (3,0 m) kg			18,500* 8 580*	18,500* 8 580*	13,350* 6 200*	10,450 4 850	10,400 4 830	6,600 3 060	7,150 3 340	4,500 2 090	3,250* 1 480*	3,250* 1 480*
+5 ft 0 in lb (1,5 m) kg			21,350* 9 910*	17,600 8 150	15,900 7 390	9,600 4 440	9,950 4 630	6,150 2 860	6,950 3 230	4,250 1 990	3,450* 1 560*	3,350 1 520
Niveau du sol lb kg			17,200* 7 530*	16,250 7 520	15,150 7 050	8,950 4 150	9,550 4 450	5,800 2 710	6,750 3 140	4,100 1 910	3,850* 1 740*	3,450 1 570
-5 ft 0 in lb (1,5 m) kg	13,450* 6 060*	13,450* 6 060*	21,950* 9 960*	16,450 7 670*	14,850 6 910	8,700 4 040	9,400 4 360	5,650 2 630	6,700 3 110	4,050 1 880	4,550* 2 060*	3,850 1 750
-10 ft 0 in lb (3,0 m) kg	19,550* 8 820*	19,550* 8 820*	28,000* 12 940*	16,750 7 800	14,950 6 950	8,800 4 090	9,500 4 410	5,800 2 680			6,000* 2 710*	4,750 2 140
-15 ft 0 in lb (4,5 m) kg	28,400* 12 560*	28,400* 12 560*	22,600* 10 560*	17,400 8 080	15,100 7 030	9,350 4 300					10,550* 4,440*	7,000 3,110

Radius of Load												
10' 0" (3.05 m) Arm with 16' 11" (5.15 m) Boom and 950 lb. (440 kg) Bucket with Power-Boost Applied												
	5 ft 0 in (1,52 m)		10 ft 0 in (3,05 m)		15 ft 0 in (4,57 m)		20 ft 0 in (6,10 m)		25 ft 0 in (7,62 m)		Cap. à portée max.	
	 End	 Side	 End	 Side	 End	 Side	 End	 Side	 End	 Side	 End	 Side
+25 ft 0 in lb							4,850*	4,850*			3,400*	3,400*
(7,62 m) kg							2 230*	2 230*			1 520*	1 520*
+20 ft 0 in lb							6,550*	6,550*	4,800*	4,800*	3,100*	3,100*
(6,10 m) kg							3 060*	3 060*	2 390*	2 280	1 410*	1 410*
+15 ft 0 in lb							8,400*	7,150	6,550*	4,750	3,050*	3,050*
(4,57 m) kg							3 910*	3 320	3 060*	2 230	1 390*	1 390*
+10 ft 0 in lb			16,350*	16,350*	12,200*	10,700	10,150*	6,700	7,250	4,550	3,150*	3,150*
(3,05 m) kg			7 560*	7 560*	5 660*	4 960	4 670*	3 120	3 380	2 130	1 430*	1 430*
+5 ft 0 in lb			24,150*	18,150	15,900	9,750	10,050	6,250	7,000	4,300	3,350*	3,150
(1,52 m) kg			11 080*	8 420	7 390*	4 520	4 670	2 900	3 250	2 010	1 530*	1 430
Niveau du sol lb	7,250*	7,250*	19,350*	16,550	15,200	9,000	9,600	5,850	6,750	4,100	3,750*	3,250
kg	3 250*	3 250*	8 450*	7 670	7 090	4 180	4 470	2 720	3 150	1 910	1 700*	1 460
-5 ft 0 in lb	12,700*	12,700*	22,000*	16,250	14,800	8,650	9,350	5,650	6,650	4,000	4,450*	3,550
(1,52 m) kg	5 710*	5 710*	9 680*	7 580	6 880	4 010	4 350	2 610	3 090	1 860	2 010*	1 610
-10 ft 0 in lb	17,950*	17,950*	28,850*	16,500	14,800	8,700	9,400	5,650			5,800*	4,300
(3,05 m) kg	7 950*	7 950*	12 860*	7 670	6 890	4 030	4 360	2 630			2 610*	1 930
-15 ft 0 in lb	28,300*	28,300*	24,650*	17,050	15,100	9,050					9,300*	6,000
(4,57 m) kg	12 610*	12 610*	11 470*	7 920	7 030	4 190					4 090*	2 670

Notes: Excavator lifting capacities

- Lifting capacities shown should not be exceeded. Weight of all lifting accessories must be deducted from the above lifting capacities.
- Lifting capacities are based on machine standing on firm, uniform supporting surface. User must make allowances for job conditions such as soft or uneven ground.
- Lifting capacities shown do not exceed 75% of minimum tipping loads or 87% of hydraulic capacities. Capacities marked with an asterisk (*) are limited by hydraulic capacities.
- Least stable position is over the side.
- Operator should be fully acquainted with the Operator's Manual & Operating Safety Booklet, furnished by LBX before operating the machine.
- Capacities apply only to the machine as originally manufactured and normally equipped by LBX Company, LLC.
- Lift capacity ratings are based on SAE J1097, "Earthmoving Machinery - Hydraulic Excavators - Lift Capacity."

Standard and Optional Equipment

CAB

12V Power Outlet	✓	Seat Recline	✓
24V Lighter	✓	Selectable Monitor Languages	✓
AM/FM Sound System	✓	Side View Camera	●
Anti-Theft Device	✓	Small Storage	✓
Ashtray	✓	Sun Visor	●
Auxiliary Switches on Control Lever	✓	Travel Alarm with Cancel Switch	✓
Cab Exterior Light Harness	✓	Trip Meter - Digital	✓
Cab Filter - External	✓	Vandal Cover (front window)	●
Cab Handrails	✓	Wiper & Washer	✓
Cab Interior Light	✓	Wiper Switch on RH Joystick	✓
Cab Lights	●	ENGINE	
Cab Iso-Mounts	✓	Air Filter - Double Element	✓
Clear Roof Window	✓	Air Filter Restriction Indicator	✓
Climate Control A/C and Heater	✓	Auto Warm-Up System	✓
Console Tilt	✓	Auto-Idle	✓
Cup Holder	✓	Auto-Idle Engine Shutdown	✓
Defroster	✓	CEGR - Cooled Exhaust Gas Recirculation	✓
Digital Clock	✓	Cooling Fan	✓
ECO Gauge	✓	Diesel Oxidation Catalyst (DOC)	✓
Emergency Exit and Hammer	✓	Diesel Particulate Filter (DPF)	✓
Face Vent	✓	Drain for Fuel Tank	✓
Floor Mat	✓	Dual Remote Fuel Filters with	
FOPS Head Guard (Level 2)	●	Water Separation	✓
Front Guard (mesh)	●	EGR Coolers	✓
Front Guard (OPG 1,2)	●	Emergency Engine Stop	✓
Front Window One-Touch Lock	✓	Engine Idle System	✓
Gate Lock Hydraulic Activation	✓	Remote Engine Oil Drain	✓
Horn	✓	Engine Protection Feature	✓
Hot & Cool Box	✓	External Fuel Gauge	✓
Hour Meter - Digital	✓	Fan Housing	✓
KAB 815 Suspension Seat	✓	Fuel Filter Restriction Indicator	✓
KAB 855 Air-Suspension	✓	Fuel Management System	✓
LED Color Monitor	✓	Fuel Shut-Off Valve	✓
Magazine Rack	✓	Fuel Usage Monitor	✓
Maintenance Interval Reminders	✓	Glow Plug Pre-Heat	✓
MP3 Auxiliary Input Jack	✓	Idle-Start	✓
On-Board Diagnostic System	✓	Intercooler	✓
One-Piece Right Window	✓	Neutral Start	✓
Radio Mute Switch	✓	One-Touch Idle	✓
Rain Deflector	●	Passive Emissions-Regeneration	✓
Rear View Camera	✓	Radiator / Oil Cooler Protective Screen	✓
Rear View Mirrors	✓	Regeneration Gauge on Monitor	✓
Roof Sun Shade	✓	Remote Oil Filter	✓
ROPS Certified	✓	VGT Turbocharger	✓

ENGINE

HYDRAULICS

Arm Regeneration	✓
Arm Speed Assistance - 2 Pump Flow	✓
Attachment Cushion Valve	✓
Auto Swing Priority	✓
Auxiliary Flow Control	✓
Auxiliary Tool Settings - Memory	✓
Auxiliary Valve	✓
Boom Regeneration	✓
Boom Speed Assistance - 2 Pump Flow	✓
Bucket Curl Assist	✓
Control Levers Pre-Wired for Auxiliary	✓
Control Pattern Changer (2 way)	✓
Fire Wall	✓
Free Swing	●
Holding Valve - Arm	✓
Holding Valve - Boom	✓
Hose Burst Check Valve	●
Hydraulic Filter Restriction Indicator	✓
Long Life Hydraulic Oil - 5,000 Hour	✓
Neutral Pump De-stroke	✓
Oil Cooler	✓
Power Boost	✓
Pressure Reading on Monitor	✓
Pump Stand-By Pressure	✓
Straight Travel Circuit	✓
AUXILIARY HYDRAULIC OPTIONS	
Single-Acting Aux. w/ Switch Activation	●
Single-Acting Aux. w/ Pedal Activation	●
Thumb Aux. w/ Switch Activation	●
Multi-Function Aux. w/ Switch Activation	●
Secondary Aux. w/ Switch Activation	●
Combination Aux. w/ Switch Activation	●
UNDERCARRIAGE	
600 mm shoes (23.6 in) 3-Bar Steel	●
700 mm shoes (27.5 in) 3-Bar Steel	✓
Steps	✓
Carbody Belly Pan (swivel guard)	✓
Center Track Guide (single)	✓
Center Track Guide (triple)	●
Long Undercarriage	✓
Sealed Link Chain	✓
Strutted Track Chain	✓
X-Pattern Carbody	✓

UPPERSTRUCTURE

Belly Pans	✓
Center Cover (Over Main CV)	✓
Fuel Tank Belly Pan.....	✓
Hand Rail - RH Access	✓
Lifting Eyes for Counterweight	✓
Lockable Fuel Cap and Service Doors ..	✓
Rubber Bumper Guards	●
Tool Box - Lockable.....	✓
Turntable Tub	✓
Work Lights - Boom and Tool Box.....	✓

ATTACHMENT

8' 7" (2.62 m) Arm.....	●
10' 0" (3.05 m) Arm.....	●
Attachment Reinforcement Plate (boom+arm).....	●
Auxiliary Pipe Brackets.....	✓
Boom Work Light.....	✓
Bucket Anti-Clatter Device.....	✓
Chrome pins.....	✓
Easy Maintenance System.....	✓
HD Bucket Link.....	●
Quick Couplers.....	●
Remote Lube Bank.....	✓
Teardrop pin retention keepers.....	✓
Thumbs.....	✓

PARTS KIT

Bucket Anti-Clatter Device	✓
Engine Manual	✓
Engine Oil Filter	✓
Filter Wrench	✓
Fuel Filters	✓
Grease Gun	✓
Green Plug Drain Hose for Engine Oil Drain	✓
Hydraulic Return Filter	✓
Ignition Keys	✓
Pilot Circuit Hydraulic Filter	✓
Rearview Mirrors	✓
Work Light for Boom	✓

Equipment Key

Standard ✓ Optional ●

Bucket Sizes

Bucket Type	SAE Heaped Capacity		Width Outside Lip		Bucket Weight		Number of Teeth	Arm Length	
	(yd ³)	(m ³)	(in)	(mm)	(lbs)	(kg)		8' 7"	10' 0"
								2.62 m	3.05 m
STDP Standard duty plate	0.58	0.44	24	610	913	415	4	H	H
	0.76	0.58	30	762	1016	462	4	H	H
	0.95	0.73	36	914	1139	518	5	M	M
	1.14	0.87	42	1067	1245	566	6	L	L
HDP Heavy duty plate	0.57	0.44	24	610	1203	547	4	H	H
	0.76	0.58	30	762	1336	607	4	H	M
	0.95	0.73	36	914	1468	667	5	M	L
	1.14	0.87	42	1067	1598	726	5	L	L
XDP Extreme duty plate	0.50	0.38	24	610	1085	493	4	H	H
	0.65	0.50	30	762	1202	546	4	H	H
	0.81	0.62	36	914	1347	612	5	H	M
	0.97	0.74	42	1067	1464	665	5	M	L
	1.13	0.86	48	1219	1581	718	5	L	L
POWER	0.50	0.38	24	610	1554	706	4	H	H
	0.65	0.50	30	762	1654	752	4	H	H
	0.81	0.62	36	914	1780	809	5	M	L
	0.97	0.74	42	1067	1875	852	6	L	L
DITCH	0.95	0.73	60	1524	1050	477	-	M	M
	1.06	0.81	66	1676	1124	511	-	M	L

Approval Code For Arm/Bucket Combinations

H.....	Heavy material (up to 3,370 lbs./yd ³)
M.....	Medium material (up to 2,700 lbs./yd ³)
L.....	Light material (up to 2,020 lbs./yd ³)
N/A.....	Not applicable

STDP - Standard duty plate
HDP - Heavy duty plate
XDP - Extreme duty plate
POWER - HDP for use with ESCO
multi-pin grabber only