



HOWO



Specifications for Sinotruk Howo 8x4 Dump Truck	
Chassis Model	ZZ3317N3867W (Right Hand Driving Type)
Production Year	2017, new truck.
Cabin	HW76 cab, with one sleeper and two seats, 2-arm windscreen wiper system with three speeds, damped adjustable driver's seat, with heating and ventilating system, exterior sun visor, safety belts, adjustable steering wheel, air horn, air conditioner, with transverse stabilizer, with 4-point support fully floating suspension + shock absorber.
Engine	Make: SINOTRUK Diesel 4-stroke direct injection diesel engine Engine model: WD615.47, Euro II, 371 HP 6-cylinder in-line with water cooling, turbo-charging and intercooling Displacement: 9.726 L
Transmission	HW19710, 10F & 2R, with PTO Ratio: 14.28, 10.62, 7.87, 5.88, 4.38, 3.27, 2.43, 1.80, 1.34, 1.00, 13.91(R1), 3.18(R2)
Steering	ZF power steering, model ZF8118, hydraulic steering with power assistance
Propeller Shaft	Double universal joint propeller shaft with gear-shaped coupling flange
Front Axle	HF9, 2x9000 KGS Steering with double T-cross section beam
Rear Axle	HC16, 2x16000 KGS Pressed axle housing, central single reduction with hub reduction and with differential locks between wheels and axles. Ratio:5.73
Chassis	Frame: U-profile parallel ladder frame with section of 300x80x8mm, and reinforced subframe all cold riveted cross members Front suspension:10 semi-elliptic leaf spring, hydraulic telescopic double-action shock absorbers and stabilizer Rear suspension:12 leaf semi-elliptic springs, bogie spring and stabilizer
Brake	Service brake: dual circuit compressed air brake Parking brake (emergency brake): spring energy, compressed air operating on front shaft and rear wheels Auxiliary brake: engine exhaust brake
Electrics	Operating voltage: 24 V, negative grounded Starter: 24 V, 5.4 Kw Alternator: 3-phase, 28 V, 1500 W Batteries: 2 x 12 V, 165 Ah Cigar-lighter, horn, headlamps, fog lights, brake lights, indicators and reverse light
Fuel Tank	300L
Tire	315/80R22.5, Tubeless tires. 12+1 pics
Cargo Body	25CBM - 28CBM is Optional U-Shape Dump Box is Optional
Overall Dimension	10400*2550*3500 mm
Color	Optional