

MAX-8



MAX-8

Excellent Performance & Reliability

CPC(Q)D15/18/20/25/30/35T8

T8 series 1.5–3.5t forklift

EP EQUIPMENT CO.,LTD
www.ep-ep.com

T8 series 1.5-1.8t forklift specification

General		CPC(QD15T8				CPC(QD18T8			
1	Manufacturer		CPCD15T8-NE92	CPCD15T8-S4Q	CPCD15T8-F20	CPCD15T8-K21	CPCD18T8-NE92	CPCD18T8-S4Q	CPCD18T8-F20
2	Model								
3	Power type		Diesel	Diesel	Gasoline	Gasoline	Diesel	Diesel	Gasoline
4	Rated capacity		1500	1500	1500	1500	1500	1800	1500
5	Load center		500	500	500	500	500	500	500
6	Lift height		3000	3000	3000	3000	3000	3000	3000
7	Free lift height		120	120	120	120	120	120	120
8	Fork size	L×W×T	920×100×35	920×100×35	920×100×35	920×100×35	920×100×35	920×100×35	920×100×35
9	Mast tilt range	F/R	612	612	612	612	612	612	612
10	Fork overhang(wheel center to fork face)		420	420	420	420	420	420	420
11	Rear overhang		420	420	420	420	420	420	420
12	Overall dimensions	Length to face of fork	2230	2230	2230	2230	2270	2230	2230
13		Overall width	1080	1080	1080	1080	1080	1080	1080
14		Mast lowered height	1995	1995	1995	1995	1995	1995	1995
15		Mast extended height	3960	3960	3960	3960	3960	3960	3960
16		Overhead guard height	2070	2070	2070	2070	2070	2070	2070
17	Turning radius(outside)		1995	1995	1995	1995	2035	1995	1995
18	Min.right angle stacking aisle width (Add load length and clearance)		2400	2400	2400	2400	2440	2400	2440
19	Travel (No load)		14	14	14	14	14	14	14
20	Speed	Lifting (Full load)	460	460	460	460	460	460	460
21		Lowering (Full load)	450	450	450	450	450	450	450
22	Max.Drawbar Pull (Full load)		20500(17500)	20500(17500)	20500(17500)	20500(17500)	20500(17500)	20500(17500)	20500(17500)
23	Max.Gradeability (Full load)		20	20	20	20	20	20	20
24	Tyres	Front	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR
25		Rear	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR	5.00-8-10PR
26	Tread	Front	920	920	920	920	920	920	920
27		Rear	920	920	920	920	920	920	920
28	Wheelbase		1430	1430	1430	1430	1430	1430	1430
29	Ground clearance	Lowest	110	110	110	110	110	110	110
30		Wheelbase center	145	145	145	145	145	145	145
31	Self weight		2700	2700	2700	2700	2900	2700	2900
32	Weight	Full load	3570	3570	3570	3570	3895	3570	3895
33		Rear	630	630	630	630	705	630	705
34	Distribution	Front	1215	1215	1215	1215	1305	1215	1305
35		Rear	1485	1485	1485	1485	1595	1485	1595
36	Battery	Voltage/Capacity(20HR)	12/60	12/60	12/60	12/60	12/60	12/60	12/60
37		Modal	4TNE92	S4Q2	FE(2.0L)	K21	4TNE92	S4Q2	FE(2.0L)
38	Manufacture		YANMAR	Mitsubishi	Mazda	Nissan	YANMAR	Mitsubishi	Mazda
39	Rated output/r.p.m		33/2450	32.9/2500	37.2/2700	31.2/2250	33/2450	32.9/2500	37.2/2700
40	Engine	Rated torque/r.p.m	136/1600	136/2000	142/1800	143.7/1600	136/1600	135/2000	142/1800
41		No.of cylinder	4	4	4	4	4	4	4
42		Bore×Stroke	92×100	88×103	86×94	89×83	92×100	88×103	86×94
43		Displacement	2659	2505	2184	2065	2659	2505	2184
44		Fuel tank capacity	50	50	50	50	50	50	50
45	Manufacture		CHINA	CHINA	CHINA	CHINA	CHINA	CHINA	CHINA
46	Transmissions	Type							
47		Stage	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)
48	Operating pressure	For attachments	17.5	17.5	17.5	17.5	17.5	17.5	17.5

1. Special lifting height available (2-stage mast : 2.5m, 2.7m, 3.0m,3.3m, 3.5m,3.6m, 3.7m,4m,4.3m, 4.5m,5m. Full Free Duplex Mast 3.0m,3.3m,3.5m,3.6m, 3-stage mast : 4.3m, 4.5m, 4.8m, 5m, 5.5m, 6m)

3. The parameters in the table are of the standard model. For more information, please contact us. 4. Specification are subject to change without notice.

2. Attachment available.

T8 series 2.0-2.5t forklift specification

General	1		Manufacture		CPC/QD20T8																		CPC/QD25T8																																			
	2	3	Model	Power type	Rated capacity	Load center	Lift height	Free lift height	Fork size	L×W×T	Mast lift range	F/R	CPD20T8-S4S	CPD20T8-	CPD20T8-K21	CPQD20T8-F20	CPQD20T8-491	CPD25T8-S4S	CPD25T8-	CPD25T8-K21	CPQD25T8-F20	CPQD25T8-491																																				
Characteristics & Dimensions	4	5			Kg	mm	mm	mm	mm	mm	mm	deg	Diesel	2000	2000	2000	2000	2000	Diesel	2500	2500	2500	2500																																			
	6	7			mm	mm	mm	mm	mm	mm	mm	mm	500	500	500	500	500	500	500	500	500	500	500																																			
	8	9			mm	mm	mm	mm	mm	mm	mm	mm	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000																																			
	10	11			mm	mm	mm	mm	mm	mm	mm	mm	120	120	120	120	120	120	120	120	120	120	120																																			
	12	13	Overall dimensions	Fork size	L×W×T	F/R	Mast lift range	Fork overhang(wheel center to fork face)	Rear overhang	Length to face of fork	Overall width	Mast lowered height	Mast extended height	Overhead guard height	Turning radius(outside)	Min.right angle stacking aisle width (Add load length and clearance)	Travel (No load)	Lifting (Full load)	Lowering (Full load)	Max.Drawbar Pull (Full load)	Max.Gradeability (Full load)	7.00-12-12PR	6.00-9-10PR	7.00-12-12PR	6.00-9-10PR																																	
	14	15																								16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46		
	12	13																								14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46
	12	13																								14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46
	Performance	20	21			mm/sec	mm/sec	mm/sec	mm/sec	mm/sec	mm/sec	mm/sec	mm/sec	17500	17500	17500	17500	17500	17500	17500	17500	17500	17500	17500																																		
		22	23			N	%	%	%	%	%	%	%	20	20	20	20	20	20	20	20	20	20																																			
24		25			mm	mm	mm	mm	mm	mm	mm	mm	7.00-12-12PR	6.00-9-10PR	7.00-12-12PR	6.00-9-10PR	7.00-12-12PR	6.00-9-10PR	7.00-12-12PR	6.00-9-10PR	7.00-12-12PR	6.00-9-10PR																																				
26		27			mm	mm	mm	mm	mm	mm	mm	mm	970	970	970	970	970	970	970	970	970	970																																				
28		29			mm	mm	mm	mm	mm	mm	mm	mm	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600																																				
30		31			mm	mm	mm	mm	mm	mm	mm	mm	120	120	120	120	120	120	120	120	120	120																																				
32		33			Kg	Kg	Kg	Kg	Kg	Kg	Kg	Kg	3580	3580	3580	3580	3580	3580	3580	3580	3580	3580																																				
34		35			mm	mm	mm	mm	mm	mm	mm	mm	4856	4856	4856	4856	4856	4856	4856	4856	4856	4856																																				
36		37			mm	mm	mm	mm	mm	mm	mm	mm	724	724	724	724	724	724	724	724	724	724																																				
Power & transmission		38	39			mm	mm	mm	mm	mm	mm	mm	mm	1428	1428	1428	1428	1428	1428	1428	1428	1428	1428																																			
	40	41			V/AH	V/AH	V/AH	V/AH	V/AH	V/AH	V/AH	V/AH	2152	2142	2142	2142	2142	2142	2142	2142	2142	2142																																				
	42	43			Modal	Modal	Modal	Modal	Modal	Modal	Modal	Modal	S4S-DPC	C490BPG-25	A498BT1-39	FE(2.0L)	491	S4S-DPC	C490BPG-25	A498BT1-39	FE(2.0L)	491																																				
	44	45			Manufacture	Manufacture	Manufacture	Manufacture	Manufacture	Manufacture	Manufacture	Manufacture	Mitsubishi	CHINA	Nissan	CHINA	CHINA	Mitsubishi	CHINA	Nissan	CHINA	CHINA																																				
	46	47			Rated output/r.p.m	Rated output/r.p.m	Rated output/r.p.m	Rated output/r.p.m	Rated output/r.p.m	Rated output/r.p.m	Rated output/r.p.m	Rated output/r.p.m	34.4/2250	36.8/2400	31.2/2250	37.2/2700	46/2600	34.4/2250	36.8/2400	31.2/2250	37.2/2700	46/2600																																				
	48	49			Rated torque/r.p.m	Rated torque/r.p.m	Rated torque/r.p.m	Rated torque/r.p.m	Rated torque/r.p.m	Rated torque/r.p.m	Rated torque/r.p.m	Rated torque/r.p.m	165/1700	156/1500	143.7/1600	142/1800	165/1600	165/1700	156/1500	143.7/1600	142/1800	165/1600																																				
	50	51			No.of cylinder	No.of cylinder	No.of cylinder	No.of cylinder	No.of cylinder	No.of cylinder	No.of cylinder	No.of cylinder	4	4	4	4	4	4	4	4	4	4																																				
	52	53			Bore×Stroke	Bore×Stroke	Bore×Stroke	Bore×Stroke	Bore×Stroke	Bore×Stroke	Bore×Stroke	Bore×Stroke	94×120	90×105	89×83	86×94	91×86	94×120	90×105	89×83	86×94	91×86																																				
	54	55			Displacement	Displacement	Displacement	Displacement	Displacement	Displacement	Displacement	Displacement	3331	2670	3168	2184	2237	3331	2670	3168	2065	2184	2237																																			
	56	57			Fuel tank capacity	Fuel tank capacity	Fuel tank capacity	Fuel tank capacity	Fuel tank capacity	Fuel tank capacity	Fuel tank capacity	Fuel tank capacity	60	60	60	60	60	60	60	60	60	60	60																																			

1. Special lifting height available (2-stage mast : 2.5m, 2.7m, 3.0m,3.3m, 3.5m,3.6m, 3.7m,4m,4.3m, 4.5m,5m. Full Free Duplex Mast 3.0m,3.3m,3.5m,3.6m, 3-stage mast : 4.3m, 4.5m, 4.8m, 5m, 5.5m, 6m)
3. The parameters in the table are of the standard model. For more information, please contact us.
4. Specification are subject to change without notice.

T8 series 3.0-3.5t forklift specification

1	Manufacture		CPC(QD)30T8				CPC(QD)35T8			
	Model		CPCD30T8-S4S	CPCD30T8-	CPCD30T8-8-K25	CPCQ30T8-F20	CPCQ30T8-491	CPCD35T8-S4S	CPCD35T8-	CPCQD35T8-K25
2	Power type		Diesel	Diesel	Gasoline	Gasoline	Gasoline	Diesel	Diesel	Gasoline
3	Rated capacity		3000	3000	3000	3000	3000	3500	3500	3500
4	Load center		500	500	500	500	500	500	500	500
5	Lift height		3000	3000	3000	3000	3000	3000	3000	3000
6	Free lift height		120	120	120	120	120	120	120	120
7	Fork size	L×W×T	1070×125×45	1070×125×45	1070×125×45	1070×125×45	1070×125×45	1070×125×50	1070×125×50	1070×125×50
8	Mast tilt range	F/R	61/2	61/2	61/2	61/2	61/2	61/2	61/2	61/2
9	Fork overhang(wheel center to fork face)		481	481	481	481	481	486	486	486
10	Rear overhang		590	590	590	590	590	590	590	590
11	Length to face of fork		2762	2762	2762	2762	2762	2822	2822	2822
12	Overall width		1200	1200	1200	1200	1200	1200	1200	1200
13	Mast lowered height		2005	2005	2005	2005	2005	2005	2005	2005
14	Mast extended height		4210	4210	4210	4210	4210	4210	4210	4210
15	Overhead guard height		2180	2180	2180	2180	2180	2180	2180	2180
16	Turning radius(outside)		2950	2950	2950	2950	2950	3010	3010	3010
17	Min right angle stacking aisle width (Add load length and clearance)		20	20	20	20	20	20	20	20
18	Travel (No load)		20	20	20	20	20	20	20	20
19	Lifting (Full load)		400	400	400	400	400	400	400	400
20	Lowering (Full load)		400	400	400	400	400	400	400	400
21	Max Drawbar Pull (Full load)		21000	21000	21000	21000	21000	21500	21500	21500
22	Max Gradeability (Full load)		20	20	20	20	20	20	20	20
23	Tyres	Front	28×9-15-12PR	28×9-15-12PR	28×9-15-12PR	28×9-15-12PR	28×9-15-12PR	28×9-15-12PR	28×9-15-12PR	28×9-15-12PR
24	Tread	Rear	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR	6.50-10-10PR
25	Wheelbase		1700	1700	1700	1700	1700	1760	1760	1760
26	Lowest		140	140	140	140	140	140	140	140
27	Wheelbase center		175	175	175	175	175	175	175	175
28	Self weight		4450	4450	4450	4450	4450	4700	4700	4700
29	Full load		6488	6488	6488	6488	6488	7134	7134	7134
30	Rear		962	962	962	962	962	1066	1066	1066
31	No load		1810	1810	1810	1810	1810	1927	1927	1927
32	Voltage/Capacity(20HR)		12/60	12/60	12/60	12/60	12/60	12/60	12/60	12/60
33	Modal		S4S-DPC	C490BPG-25	A498BT1-39	FE(2.0L)	491	S4S-DPC	A498BT1-39	K25
34	Manufacture		Mitsubishi	CHINA	CHINA	CHINA	CHINA	Mitsubishi	CHINA	CHINA
35	Rated output/r.p.m		36.8/2650	36.8/2650	36.8/2650	37.4/2300	46/2600	34.4/2250	36.8/2400	37.4/2300
36	Rated torque/r.p.m		165/1700	155/1500	168/1700	176.5/1600	165/1600	165/1700	186/1700	176.5/1600
37	No of cylinder		4	4	4	4	4	4	4	4
38	Bore×Stroke		94×105	98×105	98×105	86×94	91×86	94×120	98×105	89×100
39	Displacement		2670	2670	2670	2184	2237	3331	3168	2488
40	Fuel tank capacity		70	70	70	70	70	75	75	75
41	Manufacture		CHINA	CHINA	CHINA	CHINA	CHINA	CHINA	CHINA	CHINA
42	Type		Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift	Powershift
43	Stage		1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)	1/1(2/2)
44	Operating pressure		17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
45	For attachments									
46	Special lifting height available (2-stage mast : 2.5m, 2.7m, 3.0m,3.3m, 3.5m,3.6m, 3.7m,4m,4.3m, 4.5m,5m. Full Free Duplex Mast 3.0m,3.3m,3.5m,3.6m, 3-stage mast : 4.3m, 4.5m, 4.8m, 5m, 5.5m, 6m)									
47	Parameters in the table are of the standard model. For more information, please contact us.									
48	Specification are subject to change without notice.									

1. Special lifting height available (2-stage mast : 2.5m, 2.7m, 3.0m,3.3m, 3.5m,3.6m, 3.7m,4m,4.3m, 4.5m,5m. Full Free Duplex Mast 3.0m,3.3m,3.5m,3.6m, 3-stage mast : 4.3m, 4.5m, 4.8m, 5m, 5.5m, 6m)
3. The parameters in the table are of the standard model. For more information, please contact us.
4. Specification are subject to change without notice.

1.5-1.8t T8 series mast: (pneumatic)

Type	Model	Max.fork height	Overall height				Free lift		Front Overhang		Tilt range		Capacity			
			Lowered	Extended		Without backrest	With backrest	1.5t	1.8t	FWD	BWD	Load capacity at 500 mm				
				Without backrest	With backrest							Single tire		Double tire		
												mm	mm	kg	kg	kg
Wide view mast	2W200	2000	1495	2585	2955	120	120	420	420	6	12	1500	1800	1500	1800	
	2W250	2500	1745	3085	3455	120	120	420	420	6	12	1500	1800	1500	1800	
	2W270	2700	1845	3285	3655	120	120	420	420	6	12	1500	1800	1500	1800	
	2W300	3000	1995	3585	3955	120	120	420	420	6	12	1500	1800	1500	1800	
	2W330	3300	2145	3885	4255	120	120	420	420	6	12	1500	1800	1500	1800	
	2W350	3500	2245	4085	4455	120	120	420	420	6	12	1500	1800	1500	1800	
	2W360	3600	2295	4185	4555	120	120	420	420	6	12	1500	1800	1500	1800	
	2W400	4000	2545	4585	4955	120	120	420	420	6	12	1400	1700	1500	1800	
	2W430	4300	2695	4885	5255	120	120	420	420	6	6	1300	1600	1400	1700	
	2W450	4500	2795	5085	5455	120	120	420	420	6	6	1250	1500	1350	1600	
wide view full 2-stage mast	2F250	2500	1790	3105	3455	1045	765	420	420	6	12	1500	1800	1500	1800	
	2F270	2700	1890	3305	3655	1145	865	420	420	6	12	1500	1800	1500	1800	
	2F300	3000	2040	3605	3955	1345	1105	420	420	6	12	1500	1800	1500	1800	
	2F330	3300	2190	3905	4255	1495	1165	420	420	6	12	1500	1800	1500	1800	
	2F360	3600	2340	4205	4555	1645	1315	420	420	6	12	1500	1800	1500	1800	
	2F400	4000	2540	4605	4955	1815	1565	420	420	6	12	1400	1700	1500	1800	
	3F430	4300	1965	5070	5255	1425	1080	440	440	6	6	1250	1500	1350	1600	
wide view full 3-stage mast	3F450	4500	2045	5130	5465	1485	1140	440	440	6	6	1200	1400	1300	1500	
	3F480	4800	2160	5445	5755	1575	1230	440	440	6	6	1100	1300	1200	1400	
	3F500	5000	2210	5605	5955	1665	1320	440	440	6	6	1050	1200	1150	1300	
	3F550	5500	2375	6120	6455	1825	1480	440	440	3	6	/	/	950	1100	
	3F600	6000	2600	6695	6955	1975	1630	440	440	3	6	/	/	750	900	

Note:1. With sideshifter minus 150Kg, with integral sideshifter minus 100Kg.

2.0-2.5t T8 series mast: (pneumatic)

Tpye	Model	Max.fork height	Overall height				Free lift		Front Overhang		Tilt range		Capacity					
			Lowered	Extended		Without backrest	With backrest	Without backrest					With backrest	Load capacity at 500 mm				
				Without backrest	With backrest				Single tire					Double tire				
									mm	mm	2.0t	2.5t		2.0t	2.5t	2.0t	2.5t	
		mm	mm	mm	mm	mm	mm	mm	mm	Deg	Deg	kg	kg	kg	kg			
Wide view mast	2W200	2000	1585	2740	3420	120	120	476	476	6	12	2000	2500	2000	2500			
	2W250	2500	1725	3040	3720	120	120	476	476	6	12	2000	2500	2000	2500			
	2W270	2700	1825	3240	3920	120	120	476	476	6	12	2000	2500	2000	2500			
	2W300	3000	1995	3540	4220	120	120	476	476	6	12	2000	2500	2000	2500			
	2W330	3300	2145	3690	4370	120	120	476	476	6	12	2000	2500	2000	2500			
	2W350	3500	2245	3890	4570	120	120	476	476	6	12	2000	2500	2000	2500			
	2W360	3600	2295	3990	4670	120	120	476	476	6	12	2000	2500	2000	2500			
	2W400	4000	2495	4040	4720	120	120	476	476	6	12	1900	2300	2000	2500			
	2W430	4300	2645	4340	5020	120	120	476	476	6	6	1800	2100	1950	2450			
	2W450	4500	2745	4290	4970	120	120	476	476	6	6	1700	2000	1900	2400			
wide view full 2-stage mast	2F250	2500	1800	2090	2770	1210	560	476	476	6	12	2000	2500	2000	2500			
	2F270	2700	1900	2290	2970	1310	660	476	476	6	12	2000	2500	2000	2500			
	2F300	3000	2050	2590	3270	1460	810	476	476	6	12	2000	2500	2000	2500			
	2F330	3300	2200	2840	3520	1610	960	476	476	6	12	2000	2500	2000	2500			
	2F360	3600	2350	3140	3820	1760	1110	476	476	6	12	2000	2500	2000	2500			
	2F400	4000	2550	3440	4120	1910	1260	476	476	6	12	1900	2300	2000	2500			
wide view full 3-stage mast	3F430	4300	1970	4240	4880	1360	730	490	490	6	6	1700	2000	1900	2400			
	3F450	4500	2050	4320	5040	1460	810	490	490	6	6	1600	1900	1800	2300			
	3F480	4800	2095	4400	5345	1565	915	490	490	6	6	1500	1700	1700	2100			
	3F500	5000	2240	4620	5540	1610	960	490	490	6	6	1400	1600	1600	2000			
	3F550	5500	2320	4800	6120	1770	1120	490	490	3	6	1050	1200	1500	1800			
	3F600	6000	2740	5220	6540	2020	1370	490	490	3	6	700	800	1400	1600			

Note:1. With sideshifter minus 150Kg, with integral sideshifter minus 100Kg.

3.0-3.5t T8 series mast: (pneumatic)

Tpye	Model	Max.fork height	Overall height				Free lift		Front Overhang		Tilt range		Capacity			
			Lowered	Extended		Without backrest	With backrest	FWD			BWD	Load capacity at 500 mm				
				Without backrest	With backrest				Single tire	Double tire		Single tire	Double tire			
				mm	mm				mm	mm		mm	mm	Deg	Deg	3.0t
Wide view mast	2W200	2000	1520	2570	3250	120	120	481	486	6	12	3000	3000	3500	3500	
	2W250	2500	1770	3070	3750	120	120	481	486	6	12	3000	3000	3500	3500	
	2W270	2700	1875	3270	3950	120	120	481	486	6	12	3000	3000	3500	3500	
	2W300	3000	2025	3570	4250	120	120	481	486	6	12	3000	3000	3500	3500	
	2W330	3300	2145	3690	4370	120	120	481	486	6	12	3000	3000	3500	3500	
	2W350	3500	2245	3890	4570	120	120	481	486	6	12	3000	3000	3500	3500	
	2W360	3600	2295	3990	4670	120	120	481	486	6	12	3000	3000	3500	3500	
	2W400	4000	2495	4040	4720	120	120	481	486	6	12	2850	3000	3250	3500	
	2W430	4300	2645	4340	5020	120	120	481	486	6	6	2700	2900	3000	3400	
	2W450	4500	2745	4290	4970	120	120	481	486	6	6	2550	2850	2850	3350	
wide view full 2-stage mast	2F250	2500	1830	2220	2900	1210	560	481	486	6	12	3000	3000	3500	3500	
	2F270	2700	1930	2320	3000	1310	660	481	486	6	12	3000	3000	3500	3500	
	2F300	3000	2080	2620	3300	1460	810	481	486	6	12	3000	3000	3500	3500	
	2F330	3300	2230	3870	4550	1610	960	481	486	6	12	3000	3000	3500	3500	
	2F360	3600	2380	4020	4700	1760	1110	481	486	6	12	3000	3000	3500	3500	
	2F400	4000	2580	4420	5100	2060	1410	481	486	6	12	2850	3000	3250	3500	
wide view full 3-stage mast	3F430	4300	2000	5570	4910	1360	730	495	500	6	6	2550	2850	2850	3350	
	3F450	4500	2080	5750	5070	1460	810	495	500	6	6	2400	2700	2700	3200	
	3F480	4800	2125	6050	5375	1565	915	495	500	6	6	2250	2550	2450	2950	
	3F500	5000	2270	6250	5570	1610	960	495	500	6	6	1650	2250	2300	2800	
	3F550	5500	2350	6830	6150	1770	1120	495	500	3	6	1800	2250	1800	2550	
	3F600	6000	2770	7250	6570	2020	1370	495	500	3	6	1200	2100	1300	2300	

RATED CAPACITIES AND LOAD CENTERS GRAPH



