

LIGHT COMMERCIAL VEHICLE

GAZelle NEXT. BUS



- ❑ Low cost of ownership and short payback period
- ❑ 19 passenger seats
- ❑ European comfort and safety
- ❑ Large windows
- ❑ Zinc-coated body
- ❑ Spacious compartment of 1900 mm height
- ❑ Modern components from the world's top manufacturer

GAZ-A63R42/A64R42: SPECIFICATION

Parameter	A63R42	A64R42
Passenger capacity, ppl	18	19
Including seats, pcs.	18	18
Gross Weigh, kg	4292	4252
Curb weight, kg	3014	2960
Axle load of the fully loaded vehicle, kg:		
Front	1465	1489
Rear	2827	2763
Clearance (under the rear axle housing of a fully loaded vehicle), mm	170	170
Min turning radius of the outer front wheel tread, m	6.6	6.6
Reference fuel consumption at a constant speed, L/100 km:		
60 km/h	8.5	8.5
80 km/h	11.5	11.5
Max speed, km/h	110	110
Angle of approach, degrees (under load)	22	22
Angle of departure, degrees (under load)	14	14
Max driving gradient of a fully loaded vehicle, %	25	25
Engine	Cummins ISF2.8s4R129	
Type of engine	Turbocharged diesel engine with intercooler	
Cylinder arrangement and number	4, in-line	
Cylinder diameter and piston stroke, mm	94x100	
Cylinder capacity, L	2.8	
Compression rate	16.9	
Max capacity, kW (hp)	88.7 (120.6)	
at crank shaft rpm	3200	
Max torque, net, Nm (kgfm)	295 (30.0)	
at crank shaft rpm	1600-2700	



GAZ Group

603950, Nizhny Novgorod
88 Lenin Avenue
Customer Service phone
number: 8-800-700-0-747
www.azgaz.ru
www.gazgroup.ru

After this publication imprimatur date, configuration, specification, available colors, standard equipment and options, appearance and functions of GAZ vehicles may be amended. The illustrations may show accessories and items of optional configuration that are not included in the standard scope of delivery. Variations in color reproduction due to printing technique are possible. For any further information on this product, please contact the manufacturer or official dealer of GAZ.