

https://truckmanualshub.com/							
DIMENSI / DIMENSION (mm)	NPS 75	NKR 55 LWB 4 Ban Mini Bus	NHR 55 4 Ban	NKR 55 L	NKR 55	NKR 71 125 PS	NKR 71 HD 125 PS
Jarak Sumbu / Wheel Base (WB)	3,365	3,405	2,490	3,360	2,490	3,360	3,360
Panjang / Overall Length (OAL)	5,985	5,505	4,590	5,830	4,590	5,905	5,905
Lebar / Overall Width (OW)	2,040	1,695	1,695	1,860	1,695	1,920	1,920
Tinggi / Oerall Height (OH)	2,455	2,095	2,095	2,120	2,095	2,120	2,120
Tinggi Min dari Tanah / Min.Cleareance (HH)	120	190	190	200	190	210	210
Jarak Pijak Depan / Front Tread (AW)	1,680	1,395	1,395	1,400	1,395	1,408	1,408
Jarak Pijak Belakang / Rear Tread (CW)	1,650	1,385	1,375	1,425	1,375	1,425	1,425
PERFORMANCE							
Kecepatan Maksimum / Max. Speed	110	102	132	125	132	115	110
Daya Tanjakan / Max. Gradeability (%)	30	40	36	25	40	38	45
Radius Putar / Min.Turning Radius (m)	7.2	7.7	5.4	7	5.4	7.5	7.5
RODA / TYRE							
Depan / Front	Single, 7.50 - 16 - 10L	Single, 225/70 R15C	Single, 7.50 - 15 - 10PR	Single, 7.50 - 16 - 14PR	Single, 7.50 - 16 - 12PR	Single, 7.50 - 16 - 14PR	Single, 7.50 - 16 - 14PR
Belakang / Rear	Double, 7.50 - 16 - 10L	Single, 225/70 R15C	Single, 7.50 - 15 - 10PR	Double, 7.50 - 16 - 14PR	Single, 7.50 - 16 - 12PR	Double, Single, 7.50 - 16 - 14PR	Double, Single, 7.50 - 16 - 14PR
Velg / Disc Wheel Size	16 x 6GS - 127	7 JJ x 15	5.5K x 15	6.00 GS x 16	5.5K x 15	6.00 GS x 16	6.00 GS x 16
MESIN/ ENGINE							
Model	4HK1-TCN	4JB1-TC	4JB1-TC	4JB1-TC	4JB1-TC	4HG1-T	4HG1-T
Diameter x Langkah / Bore x Stroke (mm)	115 x 125	93 x 102	93 x 102	93 x 102	93 x 102	115 x 110	115 x 110
Isi Silinder / Piston Dispalcement (cc)	5,193	2,771	2,771	2,771	2,771	4570	4570
Tenaga / Maximum Power (PS/rpm)	150 / 2,600	101 / 3,400	101 / 3,400	101 / 3,400	101 / 3,400	125 / 2,900	125 / 2,900
Torsi / Maximum Torque (Kgm/rpm)	41 / 1,500 - 2,600	22,5 / 2,000 - 3,200	22,5 / 2,000 - 3,200	22,5 / 2,000 - 3,200	22,5 / 2,000 - 3,200	35 / 1,200 - 2,200	35 / 1,200 - 2,200
TRANSMISI / TRANSMISSION							
Model	MYT-5T	MSB5M	MSB5M	MSB5M	MSB5M	MYT5T	MYT5T
Perbandinagan Gigi / Gear Ratio							
1st	5,315	5,594	5.016	5.594	5.594	5.315	5,315
2nd	3,053	2,814	2.672	2.814	2.814	3.053	3,053
3rd	1,655	1,660	1.585	1.660	1.660	1.655	1,655
4th	1,000	1,000	1.000	1.000	1.000	1.000	1,000
5th	0.721	0,794	0.770	0.794	0.794	0.721	0,721
Rev.	5.068	5,334	4.783	5.334	5.334	5.068	5,068
Perbandingan Gigi Akhir / Final Gear Ratio	5.125	5,857	4.875	5.857	5.857	5.857	6,500
SUSPENSI / SUSPENSION							
Depan / Front	Semi Eliptical Leafspring	Semi Eliptical, Laminated Leaf Spring Dengan Shock Absorber Berdaya Ganda	Semi Eliptical, Laminated Leaf Spring Dengan Shock Absorber Berdaya Ganda	Semi Eliptical, Laminated Leaf Spring Dengan Shock Absorber Berdaya Ganda	Semi Eliptical, Laminated Leaf Spring Dengan Shock Absorber Berdaya Ganda	Semi Eliptical, Laminated Leaf Spring Dengan Shock Absorber Berdaya Ganda	Semi Eliptical, Laminated Leaf Spring Dengan Shock Absorber Berdaya Ganda
Belakang / Rear							
REM / BRAKE							
Rem Utama / Service Brake	Hydraulic, Dual Circuit	Hydraulic, Saluran Ganda Dengan Vacuum Booster	Hydraulic, Saluran Ganda Dengan Vacuum Booster	Hydraulic, Saluran Ganda Dengan Vacuum Booster	Hydraulic, Saluran Ganda Dengan Vacuum Booster	Hydraulic, Saluran Ganda Dengan Vacuum Booster	Hydraulic, Saluran Ganda Dengan Vacuum Booster
Rem Tangan / Parking Brake	Mekanisme Mounted	Mekanisme Expanding Di Transmisi Belakang	Mekanisme Expanding Di Transmisi Belakang	Mekanisme Expanding Di Transmisi Belakang	Mekanisme Expanding Di Transmisi Belakang	Mekanisme Expanding Di Transmisi Belakang	Mekanisme Expanding Di Transmisi Belakang
Sistem Pengereman Gas Buang / Exhaust Brake	Ada	Ada	Tidak Ada	Ada	Ada	Ada	Ada
ELECTRICAL							
Aki / Accu (V - AH)	12 - 65 x 2	12 - 75	12 - 75	12 - 75	12 - 75	12 - 65 x 2	12 - 65 x 2
Alternator (V - A)	24 - 50	12 - 60	12 - 60	12 - 60	12 - 60	24 - 35	24 - 35
LAIN-LAIN / OTHERS							
Kap. Tangki / Feul Tank Capacity (Ltr)	100	75	75	100	75	100	100

DIMENSI / DIMENSION		FVM 34 W	FVM 34 Q	FRR 90 Q	FVZ 285 PS	https://truckmanuals.club/	FVR 34 P	FVR 34 S	FTR 90 L	FTR 90 P	FTR 90 S
Wheel Base	(WB)	7,120	5,500	5,320	5,300	4,250	5,050	6,050	4,250	5,050	6,050
Over all Length	(OAL)	11,480	8,810	8,625	8,365	7,685	8,895	10,495	7,435	8,505	10,005
Over all Width	(OW)	2,450	2,450	2,400	2,400	2,450	2,450	2,450	2,400	2,400	2,400
Over all Height	(OH)	2,860	2,860	2,540	2,860	2,860	2,860	2,860	2,720	2,720	2,720
Min. Clearance	(HH)	235	235	190	235	235	235	235	245	245	245
Tread Front	(AW)	1,970	1,970	1,790	1,970	1,970	1,970	1,970	1,990	1,990	1,990
Tread Rear	(CW)	1,845	1,845	1,660	1,845	1,845	1,845	1,845	1,790	1,790	1,790
Front Over Hang	(FOH)	1,440	1,440	1,170	1,440	1,440	1,440	1,440	1,440	1,440	1,440
Rear Over Hang	(ROH)	2,920	1,870	2,135	1,625	1,995	2,405	3,005	1,745	2,015	2,515
Cabin to end	(CE)	9,415	6,745	6,900	6,295	5,619	6,829	8,430	5,369	6,439	7,940
WEIGHT											
Total Vehicle Mass		6,693	6,409								
Depan / Front	(kg)			3,600	3,600	6,300	6,300	6,300	6,300	6,300	6,300
Belakang / Rear	(kg)			7,700	7,700	13,000	13,000	13,000	9,200	9,200	9,200
Gross Vehicle Mass	(GVW)	26,000	26,000								
PERFORMANCE											
Max. Speed	(Km/h)	98	98	103	83	95	95	95	107	107	107
Max. Gradeability	(%)	22	22	40	47	37	37	37	37	37	37
Min. Turning Radius	(m)	10,4	8,0	8	7,7	7,1	8,3	9,7	7,5	7,5	7,5
TIRE											
Front & Rear Tyre		10.00-20-16PR (Miller)	10.00-20-16PR (Miller)	8,25 - 16-14PR (Miller)	10,00 - 20-16PR (Lug)	10.00 - 20-16PR (Miller)	10.00 - 20-16PR (Miller)	10.00 - 20-16PR (Miller)	9.00 - 20-14PR (Miller)	9.00 - 20-14PR (Miller)	9.00 - 20-14PR (Miller)
ENGINE											
Engine Model		6HK1-TCN	6HK1-TCN	4HK1-TCC	6HK1-TCS	6HK1 - TCN	6HK1 - TCN	6HK1 - TCN	4HK1-TCS	4HK1-TCS	4HK1-TCS
Type		Inline Six Cylinder, OHC, Direct Injection Diesel	Inline Six Cylinder, OHC, Direct Injection Diesel	Inline Four Cylinder, OHC, Direct Injection Diesel	Inline Six Cylinder, OHC, Direct Injection Diesel	Inline Four Cylinder, OHC, Direct Injection Diesel	Inline Four Cylinder, OHC, Direct Injection Diesel	Inline Four Cylinder, OHC, Direct Injection Diesel	Inline Four Cylinder, OHC, Direct Injection Diesel	Inline Four Cylinder, OHC, Direct Injection Diesel	Inline Four Cylinder, OHC, Direct Injection Diesel
Bore and Stroke		115x125	115x125	115 x 125	115 x 125	115 x 125	115 x 125	115 x 125	115 x 125	115 x 125	115 x 125
Piston Displacement		7,790	7,790	5,193	7,790	7,790	7,790	7,790	5,193	5,193	5,193
Max. Output	(PS/rpm)	240/2,400	240/2,400	190 / 2,600	285 / 2,400	240 / 2,400	240 / 2,400	240 / 2,400	210 / 2,600	210 / 2,600	210 / 2,600
Max. Torque	(Kgm/rpm)	72/1,450-2,400	72/1,450-2,400	52 / 1,600 - 2,600	90 / 1,450	72 / 1,450 - 2,400	72 / 1,450 - 2,400	72 / 1,450 - 2,400	65 / 1,000 - 2,600	65 / 1,000 - 2,600	65 / 1,000 - 2,600
TRANSMISSION											
Transmission Model		MZW6P	MZW6P	MZZ6W	ZF 9S1112TD	MZW6P	MZW6P	MZW6P	MZW6P	MZW6P	MZW6P
Perbandinagan Gigi / Gear Ratio											
1st		6.615	6.615	6.369	12.728	6.615	6.615	6.615	6.615	6.615	6.615
2nd		4.095	4.095	3.767	8.829	4.095	4.095	4.095	4.095	4.095	4.095
3rd		2.358	2.358	2.385	6.281	2.358	2.358	2.358	2.358	2.358	2.358
4th		1.531	1.531	1.442	4.644	1.531	1.531	1.531	1.531	1.531	1.531
5th		1.000	1.000	1.000	3.478	1.000	1.000	1.000	1.000	1.000	1.000
6th		0.722	0.722	0.720	2.538	0.722	0.722	0.722	0.722	0.722	0.722
7th					1.806						
8th					1.335						
9th					1.000						
Rev.		6.615	6.615	6.369	12.040	6.615	6.615	6.615	6.615	6.615	6.615
Final Gear Ratio		7.167	7.167	5.571	6.143	7.167	7.167	7.167	6.500	6.500	6.500
SUSPENSION											
Suspension Front		Multileaf	Multileaf	Multileaf	Multileaf	Multileaf	Multileaf	Multileaf	Multileaf	Multileaf	Multileaf
Suspension Rear		Multileaf (Trunnion Suspension)	Multileaf (Trunnion Suspension)	Multileaf	Multileaf (Turnnion Suspension)	Multileaf	Multileaf	Multileaf	Multileaf	Multileaf	Multileaf
BRAKE											
Brake Control		Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic	Air Over Hydraulic
ELECTRICAL											
Alternator	(V-A)	24-50	24-50	24 - 50	24 - 50	24 - 50	24 - 50	24 - 50	24 - 50	24 - 50	24 - 50
FUEL											
Fuel Tank Capacity	(Liter)	200	200	200	200	200	200	200	200	8,7	10,3
FRAME											
Frame Dimension		850x258x10	850x258x10	840 x 225 x 6	850 x 258 x 10 + 4.5 + 12	850 x 254 x 8	850 x 254 x 8	850 x 258 x 10	850 x 253 x 7,5	850 x 253 x 7,5	850 x 254 x 8