

<https://truckmanualshub.com> 1

COMPACT WHEEL LOADER PIVOT STEER TELELOADER



PRODUCT RANGE 2014/II



Schaeffer

Compact Wheel Loader	2020	4
	2024	5
	2024 SLT	6
	2028	7
	2028 SLT	8
	2428	9
	2428 SLT	10
	2030	11
	2030 SLT	12
	2030 S	13
	2034	14
	2336/2345	15
	2336 SLT/2345 SLT	16
	2436	17
	2445	18
	3046	19
	3550	20
	3560	21
	4250/4260	22
Pivot Steer	4350Z/4360Z	23
	5058Z/5058ZS	24
	5370Z	25
	8600Z	26
Teleloader	3550T/3560T	27
	3550T SLT/3560T SLT	28
	4560T/4580T	29
	6370T	30
	8610T	31
	9610T	32
	9630T	33
	9660T	34
	9380T	35
Attachements		36-46
Importers		47-49
Notice		50-51

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 14,7 kW = 20 hp
Tyres:	7.00-12 AS
Width:	790 mm-1.150 mm
Height with protection roof:	2.070 mm
Lifting height:	2.470 mm
Length incl. bucket:	3.330 mm
Turning radius:	530 mm
Operating weight:	1.400 kg
Lifting capacity:	1.200 kg
Tipping load, straight:	750 kg
Tipping load, articulated:	350 kg
Speed:	0-12 km/h



As standard:

Hydraulic four wheel drive via double gear pump, foot pedal control, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	2.090 mm
Lifting height:	2.800 mm/3.060 mm*
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.700 kg
Lifting capacity:	1.400 kg
Tipping load, straight:	850 kg
Tipping load, articulated:	480 kg
Speed:	0-12 km/h

* high lift version



As standard:

Hydraulic four wheel drive via double gear pump, hydraulic quickhitch, foot pedal control, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 1.890 mm
Lifting height:	2.800 mm
Length incl. bucket:	3.630 mm
Turning radius:	760 mm
Operating weight:	1.750 kg
Lifting capacity:	1.400 kg
Tipping load, straight:	870 kg
Tipping load, articulated:	500 kg
Speed:	0-12 km/h



As standard:

Hydraulic four wheel drive via double gear pump, hydraulic quickhitch, foot pedal control, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	2.090 mm
Lifting height:	2.800 mm/3.060 mm*
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.760 kg
Lifting capacity:	1.500 kg
Tipping load, straight:	920 kg
Tipping load, articulated:	550 kg
Speed:	0-15 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 1.890 mm
Lifting height:	2.800 mm
Length incl. bucket:	3.630 mm
Turning radius:	760 mm
Operating weight:	1.800 kg
Lifting capacity:	1.500 kg
Tipping load, straight:	920 kg
Tipping load, articulated:	550 kg
Speed:	0-15 km/h



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	27 x 8.5-15
Width:	940 mm-1.240 mm
Height with protection roof:	2.090 mm
Lifting height:	2.300 mm
Length incl. bucket:	3.750 mm
Turning radius:	760 mm
Operating weight:	1.820 kg
Lifting capacity:	1.700 kg
Tipping load, straight:	1.050 kg
Tipping load, articulated:	850 kg
Speed:	0-15 km/h



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, case weight, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 19 kW = 26 hp
Tyres:	27 x 8.5-15
Width:	940 mm-1.240 mm
Height with protection roof:	from 1.890 mm
Lifting height:	2.300 mm
Length incl. bucket:	3.950 mm
Turning radius:	850 mm
Operating weight:	1.860 kg
Lifting capacity:	1.700 kg
Tipping load, straight:	1.185 kg
Tipping load, articulated:	865 kg
Speed:	0-15 km/h



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, case weight, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 22 kW = 30 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	2.090 mm
Lifting height:	2.800 mm/3.060 mm*
Length incl. bucket:	3.530 mm
Turning radius:	660 mm
Operating weight:	1.800 kg
Lifting capacity:	1.500 kg
Tipping load, straight:	920 kg
Tipping load, articulated:	550 kg
Speed:	0-15 km/h
* high lift version	



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 22 kW = 30 hp
Tyres:	7.00-12 AS
Width:	890 mm-1.240 mm
Height with protection roof:	from 1.890 mm
Lifting height:	2.800 mm
Length incl. bucket:	3.630 mm
Turning radius:	760 mm
Operating weight:	1.850 kg
Lifting capacity:	1.500 kg
Tipping load, straight:	920 kg
Tipping load, articulated:	550 kg
Speed:	0-15 km/h



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature warning light, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 24 kW = 33 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm-1.290 mm
Height with protection roof:	2.135 mm
Height with cab:	2.100 mm
Lifting height:	2.880 mm/3.110 mm*
Length incl. bucket:	3.610 mm
Turning radius:	580 mm
Operating weight:	1.980 kg/cab 2.180 kg
Lifting capacity:	1.600 kg
Tipping load, straight:	1.000 kg
Tipping load, articulated:	720 kg
Speed:	0-15 km/h
* high lift version	



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, protective roof.

Technical Specifications:

Engine:	3-cyl.-watercooled Kubota diesel engine 24 kW = 33 hp
Option:	26 kW = 36 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm-1.290 mm
Height with protection roof:	2.200 mm
Height with cab:	2.150 mm
Lifting height:	2.880 mm/3.110 mm*
Length incl. bucket:	3.610 mm
Turning radius:	580 mm
Operating weight:	2.100 kg/cab 2.300 kg
Lifting capacity:	1.600 kg
Tipping load, straight:	1.000 kg
Tipping load, articulated:	720 kg
Speed:	0-15 km/h
Option:	0-20 km/h

* high lift version



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, protective roof.

Technical Specifications:

Engine:	2336	4-cyl.-watercooled Kubota diesel engine 26 kW = 36 hp
	2345	4-cyl.-watercooled Kubota turbo diesel engine 33 kW = 45 hp
Tyres:		10.075-15.3 AS
Width:		1.020 mm-1.390 mm
Height with protection roof:		2.215 mm
Height with cab:		2.110 mm
Lifting height:		2.880 mm/3.110 mm*
Length incl. bucket:		3.880 mm
Turning radius:		800 mm
Operating weight:	2336	2.300 kg/cab 2.500 kg
	2345	2.350 kg/cab 2.550 kg
Lifting capacity:		1.700 kg
Tipping load, straight:		1.200 kg/1.300 kg
Tipping load, articulated:		900 kg/930 kg
Speed:		0-20 km/h
Option:		0-28 km/h
* high lift version		



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, rear weight plate, protective roof.

Technical Specifications:

Engine:	2336 SLT	4-cyl.-watercooled Kubota diesel engine 26 kW = 36 hp
	2345 SLT	4-cyl.-watercooled Kubota turbo diesel engine 33 kW = 45 hp
Tyres:		10.075-15.3 AS
Width:		970 mm-1.390 mm
Height with protection roof:		from 1.950 mm**
Lifting height:		2.880 mm/3.110 mm*
Length incl. bucket:		4.025 mm
Turning radius:		870 mm
Operating weight:	2336 SLT	2.350 kg
	2345 SLT	2.380 kg
Lifting capacity:		1.700 kg
Tipping load, straight:		1.250 kg/1.350 kg
Tipping load, articulated:		930 kg/980 kg
Speed:		0-15 km/h
Option:		0-20 km/h

* high lift version

** with tyres 27x10.5-15 SKD

**As standard:**

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, rear weight plate, protective roof.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 26 kW = 36 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm-1.390 mm
Height with protection roof:	2.215 mm
Height with cab:	2.110 mm
Lifting height:	2.500 mm
Length incl. bucket:	4.045 mm
Turning radius:	1.000 mm
Operating weight:	2.400 kg/cab 2.600 kg
Lifting capacity:	1.900 kg
Tipping load, straight:	1.600 kg
Tipping load, articulated:	1.200 kg
Speed:	0-20 km/h
Option:	0-28 km/h
SLT-Version with overall height from 1,95 m on request.	



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, case weight, low boom pivot, stronger gearpump, rear weight plate, protective roof.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo-diesel engine 33 kW = 45 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm-1.390 mm
Height with protection roof:	2.215 mm
Height with cab:	2.110 mm
Lifting height:	2.500 mm
Length incl. bucket:	4.045 mm
Turning radius:	1.000 mm
Operating weight:	2.450 kg/cab 2.650 kg
Lifting capacity:	1.900 kg
Tipping load, straight:	1.600 kg
Tipping load, articulated:	1.200 kg
Speed:	0-20 km/h
Option:	0-28 km/h
SLT-Version with overall height from 1,95 m on request.	



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, low boom pivot, 20 km/h gear switchable under load, hydraulic quick-hitch, stronger gearpump, rear weight plate, protective roof.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo diesel engine 33 kW = 45 hp
Tyres:	10.075-15.3 AS
Width:	1.200 mm-1.540 mm
Height with protection roof:	2.160 mm
Lifting height:	2.900 mm/3.100 mm*
Length incl. bucket:	4.170 mm
Turning radius:	1.140 mm
Operating weight:	2.570 kg
Lifting capacity:	1.700 kg
Tipping load, straight:	1.500 kg
Tipping load, articulated:	1.050 kg
Speed:	0-20 km/h
* high lift version	



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, rear weight plate, protective roof.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm-1.540 mm
Height with protection roof:	2.270 mm
Height with cab:	2.230 mm
Lifting height:	2.950 mm/3.200 mm*
Length incl. bucket:	4.185 mm
Turning radius:	1.100 mm
Operating weight:	2.800 kg/cab 3.000 kg
Lifting capacity:	2.000 kg
Tipping load, straight:	1.800 kg
Tipping load, articulated:	1.400 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* high lift version

SLT-Version with overall height from 2,04 m on request.



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, HTF (High Traction Force), 20 km/h gear switchable under load, rear weight plate, protective roof.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:	10.075-15.3 AS
Width:	1.020 mm-1.540 mm
Height with protection roof:	2.270 mm
Height with cab:	2.230 mm
Lifting height:	2.950 mm/3.200 mm*
Length incl. bucket:	4.185 mm
Turning radius:	1.100 mm
Operating weight:	2.800 kg/cab 3.000 kg
Lifting capacity:	2.000 kg
Tipping load, straight:	1.800 kg
Tipping load, articulated:	1.400 kg
Speed:	0-20 km/h
Option:	0-28 km/h

* high lift version

SLT-Version with overall height from 2,04 m on request.



As standard:

Hydrostatic four wheel drive, hydraulic quickhitch, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, HTF (High Traction Force), 20 km/h gear switchable under load, rear weight plate, protective roof.

Technical Specifications:

Engine:	4250	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
	4260	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:		11.5/80-15.3 AS
Width:		1.220 mm-1.540 mm
Height with protection roof:		2.270 mm
Height with cab:		2.220 mm
Lifting height:		3.250 mm
Length incl. bucket:		4.500 mm
Turning radius:		1.310 mm
Operating weight:	4250	3.100 kg/cab 3.300 kg
	4260	3.150 kg/cab 3.350 kg
Lifting capacity:		2.300 kg
Tipping load, straight:		2.000 kg
Tipping load, articulated:		1.500 kg
Speed:		0-20 km/h
Option:		0-28 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, HTF (High Traction Force), 20 km/h gear switchable under load, rear weight plate, protective roof.

Technical Specifications:

Engine:	4350Z	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
	4360Z	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:		11.5/80-15.3 AS
Width:		1.230 mm-1.600 mm
Height with protection roof:		2.270 mm
Height with cab:		2.220 mm
Lifting height:		3.260 mm
Length incl. bucket:		4.730 mm
Turning radius:		1.450 mm
Operating weight:		3.400 kg/cab 3.520 kg
Lifting capacity:		2.400 kg
Tipping load, straight:		2.200 kg
Tipping load, articulated:		1.700 kg
Speed:		0-20 km/h
Option:		0-30 km/h



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, armrest, rear weight plate, protective roof, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	5058Z	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
	5058ZS	4-cyl.-watercooled Kubota diesel engine 51 kW = 70 hp
Tyres:		15.0/55-17 AS
Width:		1.420 mm-1.800 mm
Height with canopy/cab:		2.320 mm
Lifting height:		3.400 mm
Length incl. bucket:		4.870 mm
Turning radius:		1.670 mm
Operating weight:		3.920 kg/cab 4.070 kg
Lifting capacity:		2.800 kg
Tipping load, straight:		2.400 kg
Tipping load, articulated:		2.100 kg
Speed:		0-20 km/h



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, case weight, rear weight plate, canopy or cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 51 kW = 70 hp
Tyres:	15.0/55-17 AS
Width:	1.420 mm-1.800 mm
Height with canopy/cab:	2.320 mm
Lifting height:	3.400 mm
Length incl. bucket:	5.250 mm
Turning radius:	1.560 mm
Operating weight:	4.150 kg/cab 4.300 kg
Lifting capacity:	2.800 kg
Tipping load, straight:	2.600 kg
Tipping load, articulated:	2.250 kg
Speed:	0-20 km/h
Option:	0-30 km/h



As standard:

Hydrostatic four wheel drive, HTF (High Traction Force), hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, rear weight plate, canopy or SCV-cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 75 kW = 102 hp
Tyres:	405/70-20 AS
Width:	1.850 mm-2.080 mm
Height with SCV-cab:	2.500 mm
Option:	2.600 mm
Lifting height:	3.400 mm/3.800 mm*
Length incl. bucket:	5.560 mm
Turning radius:	1.890 mm
Operating weight:	5.550 kg/5.950 kg*
Lifting capacity:	4.200 kg
Tipping load, straight:	3.800 kg
Tipping load, articulated:	3.200 kg
Speed:	0-20 km/h
Option:	0-35 km/h
* high lift version	

**As standard:**

Hydrostatic four wheel drive, HTF (High Traction Force), hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	3550T	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
	3560T	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:		15.0/55-17 AS
Width:		1.390 mm-1.800 mm
Height with protection roof:		2.270 mm
Height with cab:		2.230 mm
Lifting height:		3.850 mm
Length incl. bucket:		4.835 mm
Turning radius:		1.230 mm
Operating weight:		3.700 kg/cab 3.900 kg
Lifting capacity:		1.950 kg
Tipping load:		800 kg-1.700 kg
Speed:		0-20 km/h
Option:		0-28 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, HTF (High Traction Force), multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, case weight, protective roof or cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	3550T SLT	4-cyl.-watercooled Kubota diesel engine 37 kW = 50 hp
	3560T SLT	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
Tyres:		15.0/55-17 AS
Width:		1.390 mm-1.800 mm
Height with protection roof:		from 2.040 mm
Lifting height:		3.850 mm
Length incl. bucket:		4.835 mm
Turning radius:		1.230 mm
Operating weight:		3.700 kg
Lifting capacity:		1.950 kg
Tipping load:		800 kg-1.700 kg
Speed:		0-20 km/h
Option:		0-28 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, HTF (High Traction Force), multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, case weight, protective roof or cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4560T	4-cyl.-watercooled Kubota turbo diesel engine 44 kW = 60 hp
	4580T	4-cyl.-watercooled Kubota turbo diesel engine 55 kW = 75 hp
Tyres:		15.0/55-17 AS
Width:		1.370 mm-1.800 mm
Height with protection roof/cab:		2.300 mm
Lifting height:		4.250 mm
Length incl. bucket:		5.105 mm
Turning radius:		1.410 mm
Operating weight:	4560T	3.950 kg/cab 4.150 kg
	4580T	4.050 kg/cab 4.250 kg
Lifting capacity:		1.950 kg
Tipping load:	4560T	900 kg/1.800 kg
	4580T	1.000 kg/1.900 kg
Speed:		0-20 km/h
Option:		0-30 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, protective roof or cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4-cyl.-watercooled Kubota diesel engine 51 kW = 70 hp
Tyres:	15.0/55-17 AS
Width:	1.570 mm-1.800 mm
Height with canopy/cab:	2.320 mm
Lifting height:	4.660 mm/5.100 mm*
Length incl. bucket:	5.580 mm
Turning radius:	1.750 mm
Operating weight:	4.670 kg/cab 4.820 kg
Lifting capacity:	2.800 kg
Tipping load:	1.300 kg-2.500 kg
Speed:	0-20 km/h
Option:	0-30 km/h
* high lift version	



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, canopy or SCV cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 75 kW = 102 hp
Tyres:	405/70-20 AS
Width:	1.850 mm-2.080 mm
Height with SCV-cab:	2.500 mm
Option:	2.600 mm
Lifting height:	5.100 mm
Length incl. bucket:	6.040 mm
Turning radius:	2.240 mm
Operating weight with SCV-cab:	6.200 kg
Lifting capacity:	3.800 kg
Tipping load:	2.000 kg-3.000 kg
Speed:	0-20 km/h
Option:	0-35 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, HTF (High Traction Force), multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 75 kW = 102 hp
Tyres:	405/70-20 AS
Width:	1.850 mm-1.950 mm
Height with SCV-cab:	2.590 mm
Option:	2.690 mm
Lifting height:	5.100 mm
Length incl. bucket:	6.030 mm
Turning radius:	2.240 mm
Operating weight with SCV-cab:	7.200 kg
Lifting capacity:	4.200 kg
Tipping load:	2.300 kg-3.800 kg
Speed:	0-20 km/h
Option:	0-35 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, HTF (High Traction Force), multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 90 kW = 123 hp
Tyres:	405/70-20
Width:	2.050 mm-2.175 mm
Height with SCV-cab:	2.690 mm
Option:	2.590 mm
Lifting height:	5.300 mm
Length incl. bucket:	6.130 mm
Turning radius:	2.240 mm
Operating weight with SCV-cab:	7.700 kg
Lifting capacity:	4.200 kg
Tipping load:	2.500 kg-4.000 kg
Speed:	0-20 km/h
Option:	0-35 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, HTF (High Traction Force), multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 20 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	4-cyl.-watercooled Deutz intercooler turbo diesel engine 115 kW = 157 hp
Tyres:	500/70-24 AS
Width:	2.290 mm-2.490 mm
Height with SCV-cab:	2.970 mm
Lifting height:	6.100 mm
Length incl. bucket:	6.750 mm
Turning radius:	2.400 mm
Operating weight:	11.000 kg
Lifting capacity:	5.000 kg
Tipping load:	2.500 kg-4.700 kg
Speed:	0-30 km/h
Option:	0-40 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, HTF (High Traction Force), multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, 30 km/h gear switchable under load, hydraulic quickhitch, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, pressure free return, decompression function of hydraulic hoses, Ferro Form sliding elements, tilt ram well protected inside boom, tyre at rear axle filled with water and antifreeze, rear weight plate, SCV-cab, Z-bar linkage with parallel lift.

Technical Specifications:

Engine:	6-cyl.-watercooled Deutz intercooler turbo diesel engine 129 kW = 175 hp
Tyres:	650/55-26.5 MPT
Width:	2.400 mm
Height with SCV-cab:	3.040 mm
Option:	2.850 mm
Lifting height:	6.900 mm
Length incl. bucket:	7.380 mm
Turning radius:	2.570 mm
Operating weight with SCV-cab:	14.000 kg
Lifting capacity:	6.000 kg
Tipping load:	2.500 kg-5.500 kg
Speed:	0-40 km/h



As standard:

Hydrostatic four wheel drive, hour meter, fuel gauge, temperature gauge, rev counter, multiple disc brake, work lamp, single lever control, adjustable steering column, oil-cooler, reversing fan, 40 km/h gear switchable under load, Schäffer STS gearbox, 3 speed ranges, load sensing working hydraulics, hydraulic quickhitch, type Vplus, planetary axles with automatic limited slip brakes, oscillating rear axle, armrest, pre air filter, Ferro Form sliding elements, tyre at rear axle filled with water and antifreeze, rear weight plate, SCV-cab, air conditioner, boom suspension, Z-bar linkage with parallel lift.

4 IN 1 BUCKET



Width	Capacity	Weight
1,20 m	310 l	295 kg
1,30 m	330 l	310 kg
1,40 m	350 l	325 kg
1,60 m	550 l	420 kg
1,80 m	620 l	450 kg
2,10 m	750 l	500 kg
2,30 m	850 l	550 kg
2,50 m	950 l	600 kg

SOIL BUCKET WITH ANGULAR BODY



Width	Capacity
0,78 m	240 l
0,90 m	270 l
1,00 m	300 l
1,10 m	330 l
1,20 m	360 l
1,30 m	390 l
1,40 m	420 l
1,50 m	450 l

Width	Capacity
1,60 m	480 l
1,70 m	610 l
1,80 m	650 l
2,00 m	720 l
2,20 m	790 l
2,40 m	870 l
2,50 m	900 l

SOIL BUCKET WITH ROUND BUCKET



Width	Capacity
0,78 m	242 l
0,90 m	279 l
1,00 m	310 l
1,10 m	341 l
1,20 m	372 l

Width	Capacity
1,30 m	403 l
1,40 m	434 l
1,50 m	465 l
1,60 m	496 l

LIGHT MATERIAL BUCKET



Width	Capacity
0,78 m	330 l
0,90 m	380 l
1,00 m	420 l
1,20 m	500 l
1,30 m	550 l
1,40 m	590 l
1,50 m	630 l
1,60 m	670 l
1,80 m	760 l

Width	Capacity
2,00 m	840 l
2,20 m	1100 l
2,40 m	1200 l
2,50 m	1300 l
2,20 m high volume	1600 l
2,40 m high volume	2000 l
2,50 m high volume	2500 l

HIGH TIP BUCKET



Width	Capacity	Weight
1,20 m	700 l	335 kg
1,40 m	820 l	360 kg
1,60 m	940 l	385 kg
1,80 m	1040 l	500 kg
2,00 m	1160 l	535 kg
2,20 m	1280 l	570 kg

BUCKET WITH GRAB



Width	Capacity	Cylinder
0,78 m	330 l	1
0,90 m	380 l	1
1,00 m	420 l	1
1,20 m	500 l	1
1,40 m	590 l	2
1,60 m	670 l	2

MULTISHOVEL



Width	Capacity	Weight
1,30 m	750 l	393 kg
1,40 m	830 l	420 kg
1,60 m	900 l	478 kg
1,80 m	1000 l	512 kg
2,00 m	1100 l	550 kg
2,20 m	1200 l	590 kg
2,40 m	1300 l	640 kg

MULTISHOVEL XL HEAVY DUTY



Width	Capacity	Weight
2,20 m	1800 l	1170 kg
2,40 m	2000 l	1360 kg

MANURE FORK WITH GRAB



Width	Cylinder	Tines
0,78 m	1	5
0,90 m	1	5
1,00 m	1	6
1,20 m	1	7
1,20 m	2	7
1,40 m	2	8

MANURE FORK WITH GRAB HEAVY DUTY



Width	Tines
1,20 m	7
1,40 m	8
1,60 m	9
1,80 m	10
2,00 m	11
2,40 m	13

MANURE FORK



Width	Tines	Tine length
0,78 m	5	800 mm
0,90 m	5	800 mm
1,00 m	6	800 mm
1,20 m	7	800 mm
1,40 m	8	800 mm
1,60 m	9	800 mm
1,70 m	10	1100 mm
1,90 m	11	1100 mm
2,10 m	12	1100 mm

SHEAR GRAB



Width	Capacity	Cut	Cyl.	Weight
0,95 m	600 l	94x80x75 cm	2	450 kg
1,20 m	730 l	115x80x75 cm	2	495 kg
1,40 m	870 l	136x80x75 cm	2	540 kg
1,60 m	1000 l	157x80x75 cm	2	705 kg
1,80 m	1160 l	178x80x75 cm	2	910 kg

DOZER BLADE



Width	Weight
1,50 m	150 kg
1,80 m	165 kg
2,00 m	335 kg
2,40 m	635 kg

SNOW BLADE



Width	Height	Working width 30° turned	Weight	Hydraulic turn
1,35 m	600 mm	1200 mm	265 kg	optional
1,50 m	600 mm	1340 mm	295 kg	optional
1,80 m	600 mm	1600 mm	310 kg	optional
1,80 m	800 mm	1600 mm	352 kg	optional
2,10 m	800 mm	1870 mm	377 kg	standard
2,40 m	800 mm	2140 mm	402 kg	standard
2,70 m	800 mm	2410 mm	427 kg	standard

SNOW BLOWER



SPREADER



Model	L/W/H	Weight	Volume	Capacity salt
Polaro 70 E	570/485/870 mm	29 kg	70 l	ca. 90 kg
Polaro 100 E	570/485/1050 mm	38 kg	105 l	ca. 130 kg

MUCK BLADE



Width	Weight
1,50 m	110 kg
1,80 m	120 kg
2,10 m	130 kg
2,50 m	145 kg

FODDER BLADE



Design	Width
Onesided	0,75 m
Double-sided	1,50 m

HYDRAULIC RUBBER BLADE




Width	Width at 40°	Width folded	Weight
2,20 m	1,70 m	0,95 m	110 kg

BALE GRIPPER



Width	Bale size	Weight
1,00 m	0,90 m - 1,80 m	180 kg
1,80 m	1,00 m - 1,80 m	350 kg

UNWINDER FOR ROUND BALES




Weight	Tines	Tine length
120 kg	4	1,00 m

BIG BALE FORK



Width	Height	Tines	Weight
1,20 m	1,55 m	3	200 kg

PALETT FORK



Width	Tine length	Weight	Capacity
1,00 m	1,00 m	165 kg	2,5 t
1,00 m	1,20 m	185 kg	2,5 t
1,20 m	1,00 m	198 kg	3,5 t
1,20 m	1,20 m	215 kg	3,5 t

STRAW SPREADER



Width	Capacity	Width bucket edge	Weight
1,35 m	850 l	1,00 m	260 kg
1,55 m	1020 l	1,20 m	275 kg
1,75 m	1200 l	1,40 m	290 kg

BUCKET WITH MILLING HEAD



Width	Capacity
1,00 m	484 l
1,20 m	598 l
1,50 m	743 l

BUCKET FOR CONCENTRATES



Width	Capacity	Weight
1,20 m	475 l	210 kg
1,40 m	575 l	240 kg
1,60 m	675 l	300 kg

FEED BUCKET WITH CHAIN CONVEYOR

<https://truckmanualshub.com/> 43



Model	Height	Width bucket edge	Overall width	Capacity	Weight
FD 100 KB	1200 mm	990 mm	1060 mm	780 l	260 kg
FD 120 KB	1200 mm	1190 mm	1240 mm	940 l	275 kg
FD 150 KB	1200 mm	1490 mm	1520 mm	1190 l	320 kg
FD 180 KB	1200 mm	1790 mm	1820 mm	1430 l	365 kg

Optional: Milling head and hydraulic control

AUGER BUCKET



Mo- del	Width, mm	Width cutting edge	Volume, m³	Weight, kg
OM 130	1500	1300	0,90	624
OM 150	1700	1500	1,00	678
OM 170	1900	1700	1,17	715

SWEeper



Width	Sweep roller	Dirt tank	Weight
1,50 m	520 mm	no	260 kg
1,50 m	520 mm	yes	360 kg
1,80 m	520 mm	no	290 kg
1,80 m	520 mm	yes	390 kg
2,10 m	520 mm	no	310 kg
2,10 m	520 mm	yes	410 kg
2,30 m	520 mm	no	330 kg
2,30 m	520 mm	yes	430 kg

MOUNTED EXCAVATOR

<https://truckmanualshub.com/> 44



Model	Weight	Width bucket	Max. reach	Max. height	Useable height	Working depth
For loader 2030 - 2033: NA 1200						
NA 1200	240 kg	200 mm	1750 mm	1700 mm	1300 mm	1200 mm
For loader 2336 - 4360Z: NA 1700						
NA 1700	390 kg	300 mm	2800 mm	2500 mm	1700 mm	2000 mm
For loader 5058Z - 5390Z - 6370T: NA 2300						
NA 2300	550 kg	400 mm	2750 mm	2400 mm	1600 mm	2000 mm

POST HOLE DRILLER



Diameter	Oil needed	Weight
10 cm	20 l	125 kg
20 cm	20 l	140 kg
30 cm	20 l	152 kg
35 cm	20 l	164 kg
40 cm	20 l	176 kg

WORKING PLATFORM



Weight	Width	Depth	Height
225 kg	1,30 m	0,86 m	1,00 m

FLAIL MOWER



Model	Working width	Overall width	Oil-flow	Weight	Knives
MU-F Hydro 120	1,20 m	1,45 m	32 l/min	220 kg	20
MU-F Hydro 140	1,40 m	1,65 m	40 l/min	240 kg	24
MU-F Hydro 160	1,60 m	1,85 m	50 l/min	260 kg	28

FINISHING MOWER



Width	Weight
1,20 m	220 kg
1,50 m	280 kg
1,80 m	330 kg

SICKLE BAR MOWER



Width	Oil needed	Weight
1,50 m	20 l	195 kg
1,90 m	20 l	215 kg

ARENA LEVELER



Width	Weight
1,50 m	220 kg

More widths and features on request.

IMPORTERS

<https://truckmanualshub.com/4/>

Australia

Agtech International
Cameron Moir
22 Park Road
6050 MT. Lawley-Perth
phone +61 892712270
fax +61 892711280
www.schaffer-loaders.com.au
cmoir@agtech-international.com

Austria/Hungary

EZ AGRAR e.Gen.
Salzburger Str. 38
4020 Linz
phone +43 732 3472660
fax +43 732 34726640
www.ezagrار.at
office@ezagrار.at

Belarus

„Biocom Technology“ Ltd.
231741 Grodno region
Grodno district
Raista village, 15
phone +375 152937937
fax +375 152937937
www.biocomtechnology.by
info@biocomtechnology.by

Belgium

N. V. Heusdens Renting
Lichtenberglaan 1001
3800 St. Truiden
phone +32 11 683899
fax +32 11 683165
www.schaffer.be
info@schaffer.be

Bulgaria

Bulagro Mashini AD
Bulagro Center
Zheleznik District
6000 Stara Zagora
phone +359 42600171-4
fax +359 42600175
www.bulagro.com
dimitar.dimitrov@bulagro.com

Canada

Schäffer Loaders Ltd.
653 Main Street North
Box 682, Morris
Manitoba R0G 1K0
phone +1 204 7462108
fax +1 204 7466806
bpi@mts.net

Czechia/Slovakia

Multos s. r. o.
K Silu 2263
39301 Pelhřimov
phone +420 565323284
fax +420 565327880
www.multos.cz
multos@iol.cz

Denmark/Sweden/Norway

Helmstmt Centret A/S
Tavlundvej 4-6, Lind
7400 Herning
phone +45 99282930
fax +45 99282938
www.helmstmt.com
mail@helmstmt.com

Finnland

Konefarmi Oy
Ruopankatu 8
20360 Turku
phone +358 424 90011
fax +358 243 11570
www.konefarmi.fi
konefarmi@konefarmi.fi

France

Ernest Roth Sàrl
16, Rue du Doubs
90101 Fêche-L'Eglise
phone +33 384549563
fax +33 384549564
www.ernestroth.com
loader@rothsa.com

Greece

EMIKO S. A.
111 Orfeos Str.
11855 Athen
phone +302 103485000
fax +302 103461653
smits@emiko.gr

Iran

Shaver Car Loader Co.
110 Dr. Beheshti Ave.
3rd floor Apt 8
Teheran, Iran
phone +98 21 884226345
fax +98 21 88412522
www.schafferloader.ir
info@schafferloader.ir

Ireland/UK

Cyril Johnston & Co. Ltd.
Ballynahinch Road
Carryduff, BT 8 8 DJ
N.-Ireland
phone +44 2890813121
fax +44 2890814220
www.cyriljohnston.co.uk
c.gilbert@cyriljohnston.org

Island

Jötunn-Vélar hf
Austurvegur 69
800 Selfoss
phone +354 4800400
fax +354 4824108
www.jotunn.is
jotunn@jotunn.is

Israel

M. Michael Engineering Ltd.
Kibutz Nahshonim
73190 Israel
phone +97 239037777
fax +97 239014642
www.m-michael.com
amirk@m-michael.com

Italy

F. Staudacher
Fuggerstr. 18, Via Fugger
39049 Sterzing-Vipiteno
phone +39 0472 766010
fax +39 0472 766585
www.staudacher.it
info@staudacher.it

Lebanon/Syria/Jordan/Egypt/

Iraq/Nigeria

Jerico Contracting & Trading Co.
Assad Badoui Bldg.
001 Main Street
Amioun, El Koura
Libanon
phone +961 3 231959
+961 3 233414
fax +961 6 951818
www.jericolb.com
jericolb@hotmail.com

Lithuania

DOTNUVOS PROJEKTAI
Parko g. 6, Akademija
58351 Kédainiai
phone +370 347 37030
fax +370 347 37040
www.dotnuvosprojektai.lt
juozas.peciulis@dotnuvosprojektai.lt

Luxembourg

Agri-Center S. A.
15, Op der Haart
9999 Wemperhardt
phone +352 23637501
fax +352 23637599
www.agri-center.lu
info@wowey.eu

Netherlands

Cees Berkhof
Barneveldsestraat 20
3927 CC Renswoude
phone +31 318572345
fax +31 318572325
www.ceesberkhof.nl
info@ceesberkhof.nl

Poland

Schaffer Ladowarki Pasek Sp. z. o. o.
ul. Lniana 1A
87-148 Lysomice
phone +48 566400057
fax +48 566400067
biuro@ladowarkipasek.pl

Portugal

SM Canaviais
Rui Batista
Quintada da Bela Vista, Pav. 31
Canaviais—7000-213 Evora
phone/fax +351 266761711
www.smcanaviais.pt
rui.batista@smcanaviais.pt

Romania

SC Farm Tech SRL
Calea Bucuresti, Nr. 115B
Sat Saftica, Comuna Balotesti
Judet Ilfov, Cod 077017
phone/fax +40 213529308
www.farmtech.ro
evabelle@xnet.ro
office@farmtech.ro

Russia

MTZ-Service Co Ltd
Elizarova pr. 38
Saint-Petersburg
phone +7 812 3272911
fax +7 812 5602282
www.mtz-service.ru
svetlana@mtz.spb.ru

SMART LLC

Pos. 4, str. 2, Furazhnyi proezd
Mytishchi city
Moscow region, 141011
phone +7 495 6444902
fax +7 495 6444903
www.smart-m.ru
rogachev-smart@mail.ru
inanov-smart@mail.ru

PSSSPOK "AGRO+"

Oblast Nischnij Nowgorod
Bogorodski Rayon
d. Uschakowo
ul. Jubileinaja d. 6 of. 1
phone +7 831 7045032
fax +7 831 7045032
sasha-serednev@yandex.ru
kolganov_sergey@mail.ru

OOO TD „Evropeiskie Agrotechnologi Sibir“

Prozed Ujnyj 37A
656067 Barnaul
phone +7 3852722211
fax +7 3852722277
www.ea-sibir.ru
eat-sibir@yandex.ru

Spain

FONDRIGO MAQUINARIA
Avenida de Galicia, 109
33770 Vegadeo, Asturias
phone/fax +34 985634238
info@fondrigomaquinaria.com

Switzerland

Ernest Roth S A
5, fbg St-Germain
2900 Porrentruy
phone +41 32 4657070
fax +41 32 4657071
www.rothsa.com
info@rothsa.com

<https://truckmanualshub.com/> 49

Ukraine

PROFIAGRO LTD
Elektrykiv Str. 26
04176 Kiev
phone +380445220530
fax +380445999209
www.profiagro.com.ua
office@profiagro.com.ua

United Arab Emirates/Oman/**Saudi Arabia/Qatar/Jemen**

Alzar F. Z. E.
LOB-21, G-01
P. B. No.17311,
J. A. F. Z.,Dubai,
United Arab Emirates
phone +97 14-8814928
fax +97 14-8814929
www.alzarfze.com
alzar@emirates.net.ae
info@alzarfze.com

NOTICE

<https://truckmanualshub.com/> 51

[illegible]



made by SCHÄFFER