https://truckmanualshub.com/

GT55 HP

Truck Mounted Forklift

PALFINGER

PALFINGER GT55 HP the most powerful machine on the market

With a 66 h.p. turbo diesel engine and conical chassis design, the all new GT55 HP sets new standards for power and structural strength in the industry. The anti-stall hydraulic drive system allows a new operator to drive like a veteran and make full use of all the power and strength, right from the start. Like all machines in the new GT-series, the GT55 HP offers a center-seated operator's position with a certified R.O.P.S. guard to provide the operator with an optimal view of the load and the job site.

Center-Seated Operator
58" Overhang
66 h.p. Turbo Diesel
Anti-Stall Drive

https://truckmanualshub.com/

PALFINGER Inc.
7942 Dorchester Rd.
Niagara Falls, ON L2E 6V6
Canada
Tel. 905-374-3363
Fax 905-374-1203
Toll Free 800-567-1554
www.palfinger-northamerica.com

GT55 *HP*
09.12

GT55 HP Truck Mounted Forklift

Operator's Compartment

15" of Ground Clearance

The innovative staggered frame design provides a lower center of gravity, improved stability and excellent ground clearance. The P.L.U.S. feature (PALFINGER Load/Unload System) helps to ensure the machine is riding properly on the transport vehicle and provides a quicker, simpler dismount of the machine.

Simple Operation

Technical Specifications

Capacity at 24" Load Center	5,500 lbs	2,500 kg
Lift Height	120" / 144"	3048 mm / 3658 mm
Dead weight	6,225 lbs / 6,350 lbs	2,824 kg / 2,880 kg
Overhang from vehicle	58"	1,473 mm
Overall height	100" / 116"	2,540 mm / 2,946 mm
Overall width	100"	2,540 mm
Turning circle diameter	80"	2,032 mm
Tire size	31" x 15.5 " - 15"	787mm x 394 mm - 392 mm
Fuel capacity	10 US gal	38 liter
Rate engine speed	2,600 rpm	
Max ground speed	8.5 mph	13.7 km/h
Working pressure	3,190 psi	220 bar
Steering	Hydrostatic	
Lighting system for transport	12 V	75 Ah
Theoretical gradability	30%	

66 h.p. Turbo Diesel Engine

Applications shown in the leaflet do not always correspond to the standard specifications.
Design and specification are subject to change without prior notice.