

NEW 575 COMPACT

COMPACT IN DIMENSIONS, GIANT IN PERFORMANCE

The NEW 575 Compact retains all the attributes that have enshrined it to the farmers, such as economy, versatility and robustness, besides bringing improvements that make it more modern and superior in performance.



AGRALE

www.agrale.com.br

@ f y agraleSA

- New 4-cylinder Perkins engine
- Fully flat work platform
- 15x15 transmission with inverter and reducer as standard
- Compact dimensions, ideal for densified cultures



NEW 575 COMPACT

<https://truckmanualshub.com/>

Generated on 17/07/2022 12:01:02

ENGINE	
Brand / model	PERKINS 1104D
No. of Cylinders	04 Vertical in line / 4.400 cm
Aspiration	Natural
Power	75 cv
Maximum Torque	26,6 kgf.m (261 N.m) @ 1.700 RPM
DRIVING TRANSMISSION	
Type	Synchronized mechanical
No. of Gears	Reverser and creeper 15 forward and 15 reverse
Differential lock	Mechanical foot pedal and automatic disengaging
Front axle	Center differential (4WD)
CLUTCH	
Type	Double dry disc
Drive	Mechanical
POWER TAKEOFF	
Drive	Mechanical
Type / drive	Independent
Nominal Speed	540 @ 2000 engine rpm
HYDRAULIC SYSTEM	
Pressure	180 kgf/cm
Maximum Flow	50 L/min
Remote control	2 way single command Standard with fast coupling and two pressure lines
Hitch	3 Points Category II
Lift capacity	2000 kg

BRAKES	
Service Brake	Wet disc oil bath
Parking Brake	Manual lever
STEERING WHEEL	
Type	Hydraulic, hydrostatic
WHEELSETS	
Standard Front Tires	7.00 18R1
Standard Rear Tires	14.9 24R1
Optional Weelsets	8.00 18R1 / 14.9 28R1 250/80 18R1 / 14.9 24R1 8.00 18R1 / 14.9 24R2 7.00 18R1 / 12.4 28R1 7.5L 15R1 / 12.4 24R1
ELECTRIC SYSTEM	
Battery	12 V 70 A
Alternator	12 V 85 A
CAPACITIES	
Fuel Tank	70 L
DIMENSIONS	
Width	1430 mm
WEIGHTS	
Shipping weight	2.310 Kg (without cabin) 2.590 Kg (with cabin)
Operating weight (curb weight)	3.060 Kg (without cabin) 3.315 Kg (with cabin)
OPTIONAL ITEMS	
Folding rear arch; Two rear weights;	

INVERSOR E SUPER REDUTOR 15X15
(MOTOR A 2400RPM - PNEUS STANDARD)

