

New Holland Boomer™ 4000 & T2400 Series Utility Tractor Specifications



Boomer 4055 Boomer 4060 T2410 T2420

MODEL	BOOMER 4055/T2410	BOOMER 4060/T2420
ENGINE		
Gross engine hp (kW)	55 (41.0)	60 (44.7)
PTO hp (kW), SSS transmission	47 (35.1)	51 (38.0)
EHSS transmission	46 (34.3)	50 (37.3)
Rated speed, rpm	2,700	2,800
Cylinders	4	
Aspiration	Turbocharged	Turbocharged
Displacement, cu. in. (L)	135.2 (2.2)	
Fuel capacity, gal. (L)	13.5 (51.1)	
TRANSMISSIONS		
12x12 Synchro Shuttle Shift (SSS)		
Min/Max forward speed with R4 tires, mph (k/hr)	1.1 to 17.5 (1.8 to 28.2)	1.1 to 18.1 (1.8 to 29.20)
12x12 Electro-Hydraulic Shuttle Shift (EHSS)		
Min/Max forward speed with R4 tires, mph (k/hr)	1.2 to 18.6 (1.9 to 30)	1.2 to 19.2 (1.9 to 31)
BRAKES		
		Wet disc
POWER TAKE OFF (PTO)		
		Independent 540 rpm
HYDRAULICS		
Pump type		Gear
Pump capacity, gpm (Lpm)*	11.6 (43.9)	12.0 (45.4)
Power steering pump, gpm (Lpm)*	5.5 (20.8)	
3-point hitch lift capacity, 24 in. behind the lift balls,		
lb. (kg)	3,465 (1571)	
* @ rated speed		
DIMENSIONS (with R4 TIRES)		
Overall length, 3-pt. raised, in. (mm)	137.3 (3487)	
Overall width (minimum), in. (mm)	71.6 (1819)	
Wheelbase, in. (mm)	74.8 (1900)	
Height to top of ROPS, in. (mm)	91.4 (2322)	
Height to top of cab, in. (mm)	88.25 (2242)	88.25 (2242)
Approx. shipping weight (ROPS models), lbs. (kg)	4,260 (1932)	
Approx. shipping weight (cab models), lbs. (kg)	5,220 (2368)	5,220 (2368)
TIRE OPTIONS		
Ag Tires		
Front	8 x 16 R1	9.5 x 16 R1
Rear	14.9-24 R1 OR	14.9-28 R1
Turf Tires		
Front	27 x 10.5-15 R3	
Rear	44 x 18-20 R3	
Industrial Tires		
Front	12 x 16.5 R4	
Rear	18.4 x 24 R4	
Galaxy® Tires*		
Front	27/12LL x 15 R3	
Rear	22.5LL x 16.1 R3	

*Front end loader installation not compatible with tractors equipped with Galaxy® "Turf Special" golf and turf tires.

Galaxy is a registered trademark of Galaxy Tire & Wheel Co.

New Holland Boomer™ 4000 & T2400 Series Utility Tractor Specifications

Boomer 4055 Boomer 4060 T2410 T2420



OPTIONAL EQUIPMENT

- Soft cab
- Front-end weights
- Rear-wheel weight
- Rear counter-weight bracket
- Linkage drawbar
- Front-end weight carrier
- FOPS canopy
- Drawbar clevis
- Sunshade canopy
- Front bumper/grill guard
- Rear work lamp
- Engine coolant heater
- Remote hydraulic valves kit
- Rear remote valve kits (maximum 3, choice of simple or detented valves)
- 2-function mid-mount remote hyd. with Joystick control
- Armrest assembly
- Deluxe radio
- Right-hand step

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.