

SONALIKA

90 / 105

**HEAVY DUTY
TRACTOR RANGE**
«FOR YOUR FIELD»



**SWITCH TO
NEW-AGE
PALM FARMING**

www.international.sonalika.com

ACCOLADES AND CREDENTIALS



AMONG
TOP 6 TRACTOR
MANUFACTURERS
GLOBALLY*



AMONG
TOP 3 TRACTOR
COMPANIES
IN INDIA




EMINENT
PRESENCE IN
130+ COUNTRIES



WORKFORCE OF
5,500+ DEDICATED
EMPLOYEES WITH
400+ ENGINEERS
IN R&D



JOINT VENTURE
WITH **YANMAR**
(JAPAN)



PRODUCTION
CAPACITY OF
300,000 TRACTORS
PER YEAR

SONALIKA

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area,
Vasant Kunj, New Delhi-110070 (India) | Phone: +91 11 66 45 5200

Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221 | Fax: +91- 01882-522222

Email: exports@sonalika.com | URL: www.solistractors.com/www.solisworld.com

Follow us on:

<https://www.facebook.com/SonalikaInternational> <https://twitter.com/SonalikaTractor>

<https://www.linkedin.com/company/sonalika-tractors-international/> https://www.instagram.com/sonalika_tractor_international/?hl=en

**POWERFUL
AND VERSATILE**

Agri-Professional

90 / 105

- POWERFUL ENGINE
- TOUGHER & MODERN TRANSMISSION
- HIGH LIFTING POWER
- EPICYCLIC REDUCTION
- INDEPENDENT CLUTCH FOR PTO
- DUAL PTO SPEED
- HYDRAULIC ASSISTED BRAKES

SONALIKA



www.international.sonalika.com

PROVEN PERFORMANCE


90 / 105

4 Cylinder high output engine with Turbo Charged

Formerly, heavy duty works like transport, tillage or ploughing slow down your engine.

Now, **Sonalika tractor comes with engine gaining high trust globally with it's unique power curve, more torque under load & especially designed with Individual Cylinder Heads**

- Giving you the extra power you need for toughest applications.
- Individual Cylinder Heads reduce the repair cost & provide Ease of maintenance.



**POWERFUL
4 CYLINDER
ENGINE**



**HIGH BACKUP
TORQUE**



**LOW
VIBRATION**



**CYLINDERS
WITH
WET LINER**



TOUGHER & MODERN TRANSMISSION

<https://truckmanualshub.com/>

SONALIKA

UNMATCHED PERFORMANCE


90 / 105

Synchromesh Transmission W/Shuttle

Forward/Reverse Synchro Shuttle : **Frequent Direction Change Provision**

With latest synchromesh technology : **Smooth and soundless operation**

Proven for toughest conditions : **Long components life and lesser service cost**



SYNCHROMESH
TRANSMISSION



RELIABLE
DRIVE LINE



CREEPER
SPEED OPTION



DOUBLE
CLUTCH



www.international.sonalika.com

POWERFUL AND PRECISE LIFT

90 / 105

Heavy Duty Lift Capacity

Solis 90 – 2500kg and Solis 105 – 3500 kg) : **Capable to work with all implements**

Fine Tune drop rate : **Less wear and tear of implements and Long components life**



MITA
HYDRAULICS



AUTO LIFT



HEAVY LIFTING
CAPACITY



2DA AUXILIARY
HYDRAULIC CIRCUIT



SONALIKA

EPICYCLIC REDUCTION

MORE STRENGTHENED

Multiple Kinematic Combinations

Minimal impact on crown wheel pinion – Long components life & Less maintenance

Capable to carry heavy loads – Suitable for various applications and high productivity



INDEPENDENT CLUTCH FOR PTO

INCREASE PRODUCTIVITY & OPERATOR COMFORT



Independent lever for PTO operation

PTO shaft is controlled with a separate lever - Ease of operation

Improve productivity and saves time - Financial benefit to operator

Less Wear and tear of components - Low service cost

DUAL PTO SPEED

EFFICIENT

Ground Speed PTO

Suitable for PTO driven trailers which provides more power during haulage in muddy condition.

Option for Economical PTO

540E PTO RPM at lower Engine RPMs – Lesser fuel consumption and high torque with various applications i.e. fertilizer spreader & sprayer etc.



HYDRAULIC ASSISTED BRAKES

EFFICIENT BRAKING

- Hydraulic Assisted Brakes provide more comfort and efficient braking during tough conditions i.e. heavy haulage at terrains



FULL OPEN & METAL HOOD

- **Full Opening hood**
- **Easy Servicing** to engine, pump, pipes, electrical giving easy access for servicing
- **Strong and durable** metallic hood prevents from dings and dent



AERODYNAMIC GLOBAL STYLING



- **Sloping hood design**
- **Better visibility** at front so that you can **see obstacles more easily and work worry-free**

AUXILIARY OUTPUTS



- No of Coupler: **4 at Rear**
- **Quick attach couplers** for easy attach & detach
- Suitable for **hydraulic operated implements and fitment of loader/dozer**

HYDROSTATIC STEERING

- **Hydraulic power steering** provides fatigue free operating
- **Better sensitivity** & control
- **Feel good steering** position optimally designed & located to provide comfort to customers



SAFETY FEATURES

GLOBAL STANDARD DRIVER SEAT

Provides more comfort and safety to operator



ROLL OVER PROTECTION SYSTEM

Protects the operator while overturned

DIVERSE APPLICATIONS FOR VARIOUS TASKS



**SONALIKA 90 PERFORMING IN
PADDY FIELDS
WHICH ELEVATES
THE PRODUCTIVITY WITH
ITS PERFORMANCE**



**SONALIKA 90 SHOWING ITS
STRENGTH WITH
BACK PUSHER**



**SONALIKA 90
PERFORMING AT
PALM
ESTATES,
FOR HAULING**



FEATURES	90
Model Description	SONALIKA 90
ENGINE	
Engine Type	4 Cylinder Turbo Charged Engine
HP Category	90
No. of Cylinders	4
Aspiration	Turbo Charged
Cubic Capacity (cc)	4087
Bore/Stroke (mm)	105/118
Rated RPM	2200
Air cleaner	Dry Air Cleaner with Clogging Sensor Precleaner
Max Torque (Nm)	339(+/-5%)Nm @1400(+/-100) RPM
Exhaust	Underhood Updraft
TRANSMISSION	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Transmission	Synchronmesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	33.73@2200 ERPM
Minimum Speed (Km/Hr)	1.64@2200 ERPM
Driver Seat	Adjustable
BRAKES	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Di erential lock	Yes, Foot Operated
PTO	
PTO (rpm)	540/540E
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 110AH
Alternator	12V, 36Amps
Seven pin trailer socket	Yes
HYDRAULICS	
Position Control	Yes
Automatic Draft & Depth Control	Yes
3 point linkage	CAT-II
Stay Bars	Adjustable

FEATURES	90
Hydraulic lifting capacity	2500 kg
Auxiliary hydraulic circuit	2DA/2SA
SAFETY SWITCH	
Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes
CAPACITY (LTRS)(+/-2%)	
Fuel tank (Ltr)	64
TYRE	
Front	12.4-24
Rear	18.4-30
DIMENSION & WEIGHT(+/-5%)	
Weight(kg)	3043 (Ballasted)
Wheel Base (mm)	2350
Total Length (mm)	4330
Total Width (mm)	1975
Height (mm) up to ROPS	2762
Min. Ground Clearance (mm)	405
Front Track (mm)	1628 (with Std. Width)
Rear Track (mm)	1508 (with Std. Width)
OTHERS	
Fuel Indicator gauge	Yes
Registration Plate with light	Yes
Front Tow Hook	Yes, inbuilt in front weight
Front & Rear Weights	Front- 4*30kg + 4*25kg Rear- 1X34 kg (Each Side)
Drawbar	Swinging Drawbar
ROPS	Yes
OPTIONAL FEATURES	
Cabin	HVAC
Front Mudguard	Yes
Trailer Brake	HTB/ATB

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

* T&C apply.

FEATURES	105
ENGINE	
Engine Type	4105IVLT
HP Category	105
No. of Cylinders	4
Aspiration	Turbo Charged & Intercooler
Bore/ Stroke(mm)	105/118
Cubic Capacity (cc)	4087
Rated RPM	2200
Air Cleaner	Two Stage dry filter with pre cleaner & scavenging
Max Torque (Nm)	420(±5%) Nm@ 1400(+/-100) RPM
Exhaust	Underhood Updraft
TRANSMISSION	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Transmission	Synchromesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	35 @ 2200 ERPM
Minimum Speed (Km/Hr)	1.6@ 2200 ERPM
Driver Seat	Adjustable
BRAKES	
Brakes	Oil Immersed Brake
Type of Actuation	Hydraulically assisted
Parking Brake	Independent
DIFFERENTIAL LOCK	
Di erential Lock	Yes
PTO	
PTO (RPM)	540/540E
PTO (Actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12V, 110AH
Alternator	12V, 90Amp
Seven pin trailer socket	Yes
HYDRAULICS	
Position Control	Yes
Automatic Draft & Depth Control	Yes
3 Point Linkage	CAT-II
Hydraulic Lifting Capacity	3500Kg.
Auxiliary Hydraulic Circuit	2DA/2SA

FEATURES	105
SAFETY SWITCHES	
Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes
CAPACITY (LTRS) (+/-5%)	
Fuel Tank (Ltr)	117
TYRES	
Front	380/85R24
Rear	460/85R34
DIMENSIONS & WEIGHT (+/-5%)	
Weight (kg)	4085
Wheel Base (mm)	2376
Total Length (mm)	4310
Total Width (mm)	2225
Height (mm) up to Canopy	2816
Min Ground Clearance (mm)	455
Front Track (mm) (Standard)	1762
Rear Track (mm) (Standard)	1724
OTHERS	
Fuel Indicator Gauge	Yes
Registration Plate with Light	Yes
Front Toe Hook	Yes, inbuilt in front weight
Front & Rear Weights	Front-72+8X31 Kg, Rear- 1X40 Kg on each wheel
Drawbar	Swinging Drawbar
ROPS	Yes
Cabin	HVAC (Optional)

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

* T&C apply.

SONALIKA

TECHNICAL SPECIFICATION

105