

Challenger

MT200B SERIES

With four rugged models and a wide range of horse-power and transmission options available, there's a Challenger® MT200B Series tractor to fit any job and budget.



MODEL	MT225B	MT255B	MT265B	MT275B	MT285B	MT295B	MT297B
GROSS ENGINE HP (KW)	22.5 (16.8)	28.4 (21.2)	33.0 (24.6)	40.1 (29.9)	47.5 (35.4)	52.1 (38.9)	59.1
PTO HP (KW)	17.6 (14.2)	22.3 (18.0)	24.5 (18.3)	31.0 (22.0)	38.0 (27.2)	41.0 (30.6)	46.4
TRANSMISSION Standard # of Gears # of Ranges	Hydrostatic N/A 2	Constant Mesh 9F/3R 3	Synchro Shuttle 8F/8R 3	Synchro Shuttle 8F/8R 2	Synchro Shuttle 8F/8R 2	Synchro Shuttle 8F/8R 2	PowerShuttle 12F/12R 3
PTO Type Output Locations Rear Mid	Independent 540 Std. @ 2000 rpm	Independent 540 Std. @ 2000 rpm	Independent 540 Opt. @ 2000 rpm	Independent 540 Opt. @ 2000 rpm	Independent 540 Opt. @ 2000 rpm	Independent 540 Opt. @ 2000 rpm	Independent 540 N/A
3-POINT HITCH Lift Capacity @ Hitch Point Lift Capacity @ 24": lbs (kg)	1,190 (540) 882 (400)	2,425 (1,100) 1,610 (730)	2,800 (1,270) 2,535 (1,150)	2,800 (1,270) 2,535 (1,150)	3,483 (1,580) 3,086 (1,400)	3,483 (1,580) 3,086 (1,400)	3,748 (1,700) 3,307
HYDRAULICS Total Pump Flow: gpm (lpm)	8.1 (3.1)	10.0 (37.8)	12.7 (48.1)	12.7 (48.1)	14.9 (56.6)	16.2 (61.5)	17.5
FOUR WHEEL DRIVE FRONT AXLE	Standard	Standard	Standard	Standard	Standard	Standard	Standard
WEIGHT Lbs (kg) All Ag Tires	1,604 (730)	2,423 (1,100)	3,169 (1,437)	3,169 (1,437)	3,660 (1,660)	3,726 (1,690)	N/A

MODEL	MT265 Hydro	MT285 Hydro
GROSS ENGINE HP (KW)	33.0 (24.6)	40.1 (30)
PTO HP (KW)	25.0 (18.7)	31.7 (23.6)
TRANSMISSION Standard # of Ranges	Hydrostatic 3	Hydrostatic 3
PTO Type Output Locations Rear Mid	Independent Standard Optional	Independent Standard Optional
3-POINT HITCH Lift Capacity @ Hitch Point Lift Capacity @ 24": lbs (kg)	2,866 (1,300) 1,940 (880)	2,866 (1,300) 1,940 (880)
HYDRAULICS Total Pump Flow: gpm (lpm)	9.6 (36.2)	9.6 (36.2)
FOUR WHEEL DRIVE FRONT AXLE	Standard	Standard
DRY WEIGHT Lbs (kg)	2,981 (1,353)	3,114 (1,413)

Challenger

MT300B SERIES

An ideal complement for the popular MT400B, the new MT300B weighs in as a middleweight champ with a great combination of power and maneuverability.

This 4-tractor ranges from 45 to 75 PTO HP is designed to meet the needs of the progressive fleet owner and the operator looking for an all-purpose tractor.

Ideal for loader work and yard work, this tractor is equally at home in the field. The Challenger® MT300B Series provides one of the most complete tractor packages in this important utility tractor sector.



Model	MT315B	MT325B	MT335B	MT345B
Gross Engine HP (KW)	58 (43.2)	68 (50.7)	78 (58)	91 (67.8)
PTO HP (KW)	45 (33.5)	55 (41)	65 (48.5)	75 (56)
TRANSMISSION				
Base (Synchro Shuttle)	12 x 12 (0.3-18.6 mph)	12 x 12 (0.3-18.6 mph)	12 x 12 (0.3-18.6 mph)	12 x 12 (0.3-18.6 mph)
Optional (Power Shuttle)	12 x 12 (0.3-18.6 mph)	12 x 12 (0.3-18.6 mph)	12 x 12 (0.3-18.6 mph)	12 x 12 (0.3-18.6 mph)
PTO				
Engagement	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic
Standard	540 Ind	540 Ind	540 Ind	540 Ind
Optional	540/540E Ind	540/540E Ind	540/540E Ind	540/540E Ind
FRONT AXLE ENGAGEMENT				
Type	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic	Electro Hydraulic
HYDRAULICS				
Rated Pump Capacity GPM	15.8	15.8	15.8	15.8
Maximum Hyd Pressure psi (bar)	2755	2755	2755	2755
BRAKES				
Type	Hydraulic Oil Cooled Disc	Hydraulic Oil Cooled Disc	Hydraulic Oil Cooled Disc	Hydraulic Oil Cooled Disc
Weight (lbs) 2wd/4wd	5291/5732	5291/5732	5291/5732	5291/5732
Wheel Base 2wd/4wd (in)	82.7	82.7	82.7	82.7



DIESEL "GRADE" TRACTOR

Model:	MT325B
PTO:	55 PTO h/p/ 68 gross h/p
Engine:	3 cylinder turbo charged Diesel
Transmission:	12x12 power shuttle
Tires:	16.9x24 R-4 rear — F12.5/80-18 Front R4
Dual rear remotes, Beacon, Grill Guard, Power links "Top & Tilt" and 78" II/D Box Blade	
Factory Warranty:	24m/2000 hrs
Sale Price:	\$35,600.00*

Includes all options listed

*Price and availability are subject to change.

Challenger®

MT400B SERIES

Have it your way with the Challenger® MT400B Series. Choose from a variety of configurations to fit a variety of tasks. These tough tractors deliver all the strength, power and reliability you expect from a Challenger tractor. Best of all, these tractors are a pleasure to drive and operate, thanks to plenty of comfort and visibility.



Model	MT425B	MT445B	MT455B	MT465B
ENGINE	Caterpillar® 3054	Caterpillar® 3054	Caterpillar® 3054	Caterpillar® 3054
PTO HP	60	70	80	90
Displacement (CID/L)	268/4.4	268/4.4	268/4.4	268/4.4
FUEL TANK CAPACITY				
Standard (US Gal / L)	40/151	40/151	40/151	40/151
TRANSMISSION				
Standard Speeds	16F X 16R	16F X 16R	16F X 16R	16F X 16R
BRAKES				
Type	Hydraulic	Hydraulic	Hydraulic	Hydraulic
	Wet Disc	Wet Disc	Wet Disc	Wet Disc
POWER TAKE-OFF (PTO)				
Speeds RPM	Independent	Independent	Independent	Independent
	540/1000/economy	540/1000/economy	540/1000/economy	540/1000/economy
HYDRAULIC SYSTEM				
Type	Open Center	Open Center	Open Center	Open Center
# remotes cab std./opt.	2/4	2/4	2/4	2/4
# remotes platform std./opt.	2/4	2/4	2/4	2/4
Max. Pressure (PSI/Bar)	2900 / 200	2900 / 200	2900 / 200	2900 / 200
3-POINT HITCH				
3-Point Hitch Control	Electronic	Electronic	Electronic	Electronic
Category:	II	II	II	II
3-Point Hitch Stabilizers	Telescoping	Telescoping	Telescoping	Telescoping
Lift Capacity @ 24" (lb / kg)	6,600/2,993	6,600/2,993	6,600/2,993	6,600/2,993
Lower Draft Arm Link Ends	Telescopic	Telescopic	Telescopic	Telescopic
DIMENSIONS				
Wheel base (in / mm)	97/2463	97/2463	97/2463	100.5/2553
Minimum Tread (in / mm)	60/1518	60/1518	60/1518	60/1518
Height Top of Cab (in / mm)	106.5/2706	106.5/2706	106.5/2706	106.5/2706
Overall Length (in / mm)	169.4/4302	169.4/4302	169.4/4302	169.4/4302

Challenger



MT500B SERIES

Looking for the most technologically advanced 100 to 160 PTO horsepower tractor on the market? Look no further that the Challenger® MT500B Series. Five models feature more power, control and productivity than ever before. Equipped with the raw power to handle your toughest jobs, the MT500B also boasts a wide range of standard and optional high-tech features, including electronic 3-point hitch and automatic transmission shifting.

Model	MT525B	MT535B	MT545B	MT555B	MT565B	MT575B
ENGINE	Caterpillar® C6.6 Acert	Caterpillar® C6.6 Acert	Caterpillar® C6.6 Acert	Caterpillar® C6.6 Acert	Caterpillar® C6.6 Acert	Caterpillar® C6.6 Acert
PTO HP	100	110	120	130	145	160
# of Cylinders	6	6	6	6	6	6
Displacement (CID / L)	366/6.0	366/6.0	366/6.0	366/6.0	366/6.0	403/6.6
CAPACITIES						
Fuel Tank (gal/L)	71/270	71/270	71/270	100/380	100/380	100/380
Cooling System (gal/L)	6.73/25.5	6.73/25.5	6.73/25.5	6.73/25.5	6.73/25.5	6.73/25.5
Hydraulic System (gal/L)	18.5/70	18.5/70	18.5/70	18.5/70	18.5/70	18.5/70
TRANSMISSION						
Type	AutoPower VI	AutoPower VI	AutoPower VI	AutoPower VI	AutoPower VI	AutoPower VI
4:1 Creeper	Optional	Optional	Optional	Optional	Optional	Optional
Type	TechStar CVT	TechStar CVT	TechStar CVT	TechStar CVT	TechStar CVT	TechStar CVT
AXLES						
Front 2WD Autopower VI & IV only	Box in Box/2WD	Box in Box/2WD	Box in Box/2WD	Box in Box/2WD	Box in Box/2WD	Box in Box/2WD
Hydraulic Suspension	Optional	Optional	Optional	Optional	Optional	Optional
Tread with -18.4 tires (in/mm)	60 to 88/ 1,524 to 2,235	60 to 88/ 1,524 to 2,235	60 to 88/ 1,524 to 2,235	60 to 88/ 1,524 to 2,235	60 to 88/ 1,524 to 2,235	60 to 88/ 1,524 to 2,235
BRAKES						
Rear	Hydraulic wet multi-disc	Hydraulic wet multi-disc	Hydraulic wet multi-disc	Hydraulic wet multi-disc	Hydraulic wet multi-disc	Hydraulic wet multi-disc
Front Brakes AutoPower	4WD Pack	4WD Pack	4WD Pack	4WD Pack	4WD Pack	4WD Pack
Front Brakes TechStar CVT	Wet brakes om cardan shaft	Wet brakes om cardan shaft	Wet brakes om cardan shaft	Wet brakes om cardan shaft	Wet brakes om cardan shaft	Wet brakes om cardan shaft
HYDRAULIC SYSTEM						
Type	Pressure flow/ compensated	Pressure flow/ compensated	Pressure flow/ compensated	Pressure flow/ compensated	Pressure flow/ compensated	Pressure flow/ compensated
# of remotes std./ opt.	2/3 up to 4	2/3 up to 4	2/3 up to 4	4	4	4
Max. Pressure (PSI/Bar)	2,900/200	2,900/200	2,900/200	2,900/200	2,900/200	2,900/200
Max. Flow (gpm/lpm)	29/110	29/110	29/110	29/110	29/110	29/110
3-POINT HITCH						
Lift Capacity@24" (lb/kg)	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
TechStar	10,915 (4,950)	10,915 (4,950)	10,915 (4,950)	14,283 (6,479)	14,283 (6,479)	14,283 (6,479)
DIMENSIONS						
Wheel base (in/mm)	112.1/2848	112.1/2848	112.1/2848	112.1/2848	112.1/2848	112.1/2848
Minimum Width (in/mm)	81.1/2060	81.1/2060	81.1/2060	81.1/2060	81.1/2060	81.1/2060
Height Top of Cab (in/mm)	112.8/2865	112.8/2865	112.8/2865	112.8/2865	112.8/2865	112.8/2865
Overall Length (in/mm)	168.5/4279	168.5/4279	168.5/4279	168.5/4279	168.5/4279	168.5/4279
Shipping Weight 2WD (lb/kg)	11,052/5013	11,052/5013	11,052/5013	14,028/6590	14,028/6590	14,028/6590
Shipping Weight AWD (lb/kg)	11,546/5237	11,949/5420	11,949/5420	14,528/6590	14,528/6590	14,528/6590

Challenger

MT600B SERIES

Unmatched comfort, combined with brute strength, comes in four sizes in the MT600B Series wheeled tractors. Covering the range from 180 to 240 PTO horsepower, the MT600B Series boasts a myriad of standard features, including all-wheel drive, a deluxe operator's seat and four-wheel braking.



Model	MT635B	MT645B	MT655B	MT665B
ENGINE				
PTO HP	Endurance 74CTA 180 (134 kW)	Endurance 74CTA 200 (149 kW)	Endurance 84CTA 220 (164 kW)	Endurance 84CTA 240 (180 kW)
# of cylinders/Valves	6/24	6/24	6/24	6/24
Displacement (CID/L)	451/7.4	451/7.4	512/8.4	512/8.4
CAPACITIES				
Fuel Tank (gal/L)	159/600	159/600	159/600	159/600
Cooling system (gal/L)	8.9/34	8.9/34	8.9/34	8.9/34
Hydraulic System (gal/L)	26.4/100	26.4/100	26.4/100	26.4/100
TRANSMISSION				
Type	TechStar CVT	TechStar CVT	TechStar CVT	TechStar CVT
Speed Range	0.01 to 25 mph	0.01 to 25 mph	0.01 to 25 mph	0.01 to 25 mph
AXLES				
Front (standard)	AG210 High Pivot MFD	AG210 High Pivot MFD	AG280 High Pivot MFD	AG280 High Pivot MFD
Rear Bar Axle (in/mm)	118/3,000 - 4.33/110 dia.	118/3,000 - 4.33/110 dia.	118/3,000 - 4.33/110 dia.	118/3,000 - 4.33/110 dia.
Tread Width - 18.4 tires (in/mm)	60 to 88/1,524 to 2,235	60 to 88/1,524 to 2,235	60 to 88/1,524 to 2,235	60 to 88/1,524 to 2,235
BRAKES				
Rear	Hydraulic wet multi-disc	Hydraulic wet multi-disc	Hydraulic wet multi-disc	Hydraulic wet multi-disc
Front	Wet brakes on cardan shaft	Wet brakes on cardan shaft	Wet brakes on cardan shaft	Wet brakes on cardan shaft
HYDRAULIC SYSTEM				
Type	Pressure flow/compensated	Pressure flow/compensated	Pressure flow/compensated	Pressure flow/compensated
# of remotes std./opt.	4 up to 6	4 up to 6	4 up to 6	4 up to 6
Max. Pressure (PSI/Bar)	2,900/200	2,900/200	2,900/200	2,900/200
Max. Flow (gpm/lpm)	39/147	39/147	39/147	39/147
3-POINT HITCH				
Lift Capacity @ 24" (lb/kg)	Electronic 15,600 (7,078)	Electronic 15,600 (7,078)	Electronic 15,600 (7,078)	Electronic 15,600 (7,078)
DIMENSIONS				
Wheel base (in/mm)	121/3,075	121/3,075	121/3,075	121/3,075
Minimum Width (in/mm)	118/3,000	118/3,000	118/3,000	118/3,000
Height Top of Cab (in/mm)	123.6/3,140	123.6/3,140	123.6/3,140	123.6/3,140
Overall Length (in/mm)	206/5,240	206/5,240	206/5,240	206/5,240
Shipping Weight (lbs/kg)	18,308/8,304	18,308/8,304	19,550/8,868	19,550/8,868

Challenger

MT700B SERIES

The Challenger® MT700B Series tractors deliver the future of tracked tractor performance. Powered by Caterpillar ACERT Technology Engines, these machines deliver smooth, effortless power with the latest in tractor technology for outstanding performance and productivity.

MODEL	MT755B	MT765B
ENGINE PTO HP @ rated 2,100 RPM Gross Engine HP (KW) Displacement (CID/L)	Caterpillar®C9 ACERT 245 301 537/8.8	Caterpillar®C9 ACERT 265 320 537/8.8
CAPACITIES Fuel - Standard (60" to 88 gauge) Optional fuel capacity Hydraulic System - Max Flow	118 US GAL (446.7 L) 208 US GAL (787.4 L) 43.5 GPM (164.7 L/MIN)	118 US GAL (446.7 L) 208 US GAL (787.4 L) 43.5 GPM (164.7 L/MIN)
TRANSMISSION Maximum Speed Range (mph/km/h) Creeper, 4 to 1 reduction	CAT®Powershift 16F/4R 24.6/39.6 Optional	CAT®Powershift 16F/4R 24.6/39.6 Optional
ELECTRICAL SYSTEM Alternator Batteries	185 amp (2) 1,000 cca, 12-V	185 amp (2) 1,000 cca, 12-V
DIMENSIONS Wheelbase (in/mm) Overall Width - Wide Gauge (in/mm) Height Top of Cab (in/mm) Overall Length (in/mm) Shipping Weight (lbs/kg)	96" (2,438 mm) 133" (3,376 mm) 135.5" (3,444 mm) 233" (5,917 mm) 31,075 lb (14,095 kg)	96" (2,438 mm) 133" (3,376 mm) 135.5" (3,444 mm) 233" (5,917 mm) 31,075 lb (14,095 kg)



Challenger

MT800B SERIES

Bigger, faster, stronger and smarter. That pretty much describes the Challenger® MT800B Series — whether you're comparing them to their predecessors or to the competition. With new engines and a broader range of models, the new MT800B Series has once again raised the limit on productivity and performance in the high-horsepower tractor category. All five models in the series, including a new MT875B model rated at 570 gross engine horsepower, feature upgraded engines, higher horsepower and advanced technology, compared to the MT800B Series they replace. The new MT875B, in fact, not only expands the line-up, but takes gross engine horsepower to a new level among modern-day production tractors — wheel or track.

MODEL	MT835B	MT845B	MT855B	MT865B	MT875B
ENGINE PTO HP @ rated at 2,100 RPM Gross Engine HP Displacement (cu. in./L)	Caterpillar®C15 ACERT 290 (216 kW) 350 (261 kW) 928/15.2	Caterpillar®C15 ACERT 335 (249 kW) 400 (299 kW) 928/15.2	Caterpillar®C15 ACERT 385 (287 kW) 460 (343 kW) 928/15.2	Caterpillar®C18 ACERT 425 (316 kW) 510 (343 kW) 1,105/18.1	Caterpillar®C18 ACERT 425 (316 kW) 570 (425 kW) 1,105/18.1
CAPACITIES Fuel -Standard Optional fuel capacity	305 US gal (1,159 L) 330 US gal (1,254 L)	305 US gal (1,159 L) 330 US gal (1,254 L)	305 US gal (1,159 L) 330 US gal (1,254 L)	330 US gal (1,254 L) NA	330 US gal (1,254 L) NA
TRANSMISSION Type Maximum Speed (mph/km/h)	CAT® Powershift 16F/4R 24.6/39.6	CAT® Powershift 16F/4R 24.6/39.6	CAT® Powershift 16F/4R 24.6/39.6	CAT® Powershift 16F/4R 24.6/39.6	CAT® Powershift 16F/4R 24.6/39.6
ELECTRICAL SYSTEM Alternator Batteries	185 amp (4) 1,000 cca, 12-V	185 amp (4) 1,000 cca, 12-V	185 amp (4) 1,000 cca, 12-V	185 amp (4) 1,000 cca, 12-V	185 amp (4) 1,000 cca, 12-V
HYDRAULIC SYSTEM Type Standard Flow Optional High Flow Max. System Pressure	Load-independent Flow (close-center) 43.5 GPM (164.7 L/min) 59 GPM (224.2L/min) 2,900 PSI (200 bar)	Load-independent Flow (close-center) 43.5 GPM (164.7 L/min) 59 GPM (224.2L/min) 2,900 PSI (200 bar)	Load-independent Flow (close-center) 43.5 GPM (164.7 L/min) 59 GPM (224.2L/min) 2,900 PSI (200 bar)	Load-independent Flow (close-center) 43.5 GPM (164.7 L/min) 59 GPM (224.2L/min) 2,900 PSI (200 bar)	Load-independent Flow (close-center) 43.5 GPM (164.7 L/min) 59 GPM (224.2L/min) 2,900 PSI (200 bar)
DIMENSIONS Wheelbase (in/mm) Min.Width -Wide Gauge (in/mm) Height to Top of Cab (in/mm) Overall Length (in/mm) Approx. Shipping Weight (lbs/kg)	118" (2,997 mm) 140.9" (3,579 mm) 138.1" (3,509 mm) 270" (6,863 mm) 41,000 lbs (18,597 kg)	118" (2,997 mm) 140.9" (3,579 mm) 138.1" (3,509 mm) 270" (6,863 mm) 41,000 lbs (18,597 kg)	118" (2,997 mm) 140.9" (3,579 mm) 138.1" (3,509 mm) 270" (6,863 mm) 41,000 lbs (18,597 kg)	118" (2,997 mm) 140.9" (3,579 mm) 138.1" (3,509 mm) 270" (6,863 mm) 41,000 lbs (18,597 kg)	118" (2,997 mm) 140.9" (3,579 mm) 138.1" (3,509 mm) 270" (6,863 mm) 41,000 lbs (18,597 kg)



Challenger

MT900B SERIES

The Challenger® brand is shaking up the tractor market with the introduction of the all-new MT900B series articulated 4-wheel drive tractor. Ideal for heavy pulling such as deep rippers, large harrows, air seeders, or towed scrapers, the MT900B series tractors provide farmers and custom operators with another reliable high horsepower option from their Caterpillar® dealer.

Model	MT945B	MT955B	MT965B	MT975B
ENGINE	Caterpillar® C15 ACERT	Caterpillar® C15 ACERT	Caterpillar® C18 ACERT	Caterpillar® C18 ACERT
# of cylinders/Valves	6/24	6/24	6/24	6/24
Gross Engine HP - hp (kW)	430 (320)	460 (343)	510 (381)	570 (425)
Engine Torque Rise @ rpm	42% @ 1,400	42% @ 1,400	42% @ 1,400	42% @ 1,400
Displacement (cu. in./L)	923 (15.2L)	923 (15.2L)	1,106 (18.1L)	1,106 (18.1L)
CAPACITIES				
Fuel Tank Capacity - US Gal (L)	390 (1,476)	390 (1,476)	390 (1,476)	390 (1,476)
Transmission				
Type	CAT® Powershift 16F/4R	CAT® Powershift 16F/4R	CAT® Powershift 16F/4R	CAT® Powershift 16F/4R
Maximum Speed (mph/km/h)	24.6/39.6	24.6/39.6	24.6/39.6	24.6/39.6
ELECTRICAL SYSTEM				
Alternator	185 amp	185 amp	185 amp	185 amp
Batteries	(4) 1,000 cca, 12-V	(4) 1,000 cca, 12-V	(4) 1,000 cca, 12-V	(4) 1,000 cca, 12-V
HYDRAULIC SYSTEM				
Type	Load-independent Flow	Load-independent Flow	Load-independent Flow	Load-independent Flow
Standard Flow - gpm (L/min)	44 (166.5)	44 (166.5)	44 (166.5)	44 (166.5)
Optional Flow - gpm (L/min)	59 (223.3)	59 (223.3)	59 (223.3)	59 (223.3)
Max. System Pressure	2,900 PSI (200 bar)	2,900 PSI (200 bar)	2,900 PSI (200 bar)	2,900 PSI (200 bar)
DIMENSIONS				
Wheel base (in/mm)	155.5 (3,949.7)	155.5 (3,949.7)	155.5 (3,949.7)	155.5 (3,949.7)
Overall Width (in/mm)	192 (4,871)	192 (4,871)	192 (4,871)	192 (4,871)
Height to Top of Cab (in/mm)	151 (3,835.4)	151 (3,835.4)	151 (3,835.4)	151 (3,835.4)
Overall Length (in/mm)	298 (7,569.2)	298 (7,569.2)	298 (7,569.2)	298 (7,569.2)
Operating Weight (lbs)	50,000	60,000	60,000	60,000



Challenger

CHALLENGER 1 SERIES

Clean up debris efficiently with a Challenger® Tractor Mounted Sweeper. Built tough for the professional operator, the Challenger rotary broom sweeper adjusts easily to perform a variety of jobs.

Manufacturer	Smith Equipment & Supply Company
Model	Challenger 1 Tractor Mounted Sweeper
Horsepower	40 to 60 HP ideally
Brush Drive	Hydraulic
Sweeping Angle	40° Right 0-40° Left
Weight	1400 lbs
Oil Capacity	24 Gallons
Brush Lift	Approximately 36"
Brush	35" x 7 Ft 100% Poly or 50% Poly - 50% Wire Quick change
Special Features	2 Minute Brush Change Requiring No Tools Grease Fittings and Replaceable Bushings Self Cooling Oil Reservoir Extra H/D Construction Large Diameter Brush



CHALLENGER DIESEL "GRADE" TRACTOR

Model	MT325B
PTO	55 PTO h/p / 68 gross h/p
Engine	3 cylinder turbo charged Diesel
Transmission	12x12 power shuttle
Tires	16.9x24 R-4 rear - F12.5/80-18 Front R4 Dual rear remotes, Beacon, grill guard Power links "Top & Tilt" and 78" H/D Box Blade
Factory warranty	24m/2000hrs

