


Fantuzzi CS 45 KS

Dimensions — Fantuzzi CS 45 KS



TECHNICAL SPECIFICATIONS CS 45 KL - KS

1	Manufacturer		FANTUZZI			
2	Model		TYPE		CS 42 KL	CS 45 KS
3	Weight empty			Kg.	71000	75000
4	Propulsion		Electrical, Diesel, Petrol, Gas		Diesel	
5	Tyres		V=Solid tyre - L=Tyres	F/R	L/L	L/L
6	Wheels (x=drive)		Number	F/R	4/2	
7	Materials		Arm	Weldox 700 Fe 510 D (Fe 52) Weldox 700 / Fe 510 D		
			Chassis			
			Spreader			
8	Noise		Outside / In cab	dB (A)	85 / 74	
9	Performance		Speed empty / loaded	km/h	25 / 23	
10	Spreader		Telescopic type 20' - 40'		SRP2 - 45	
			Rotation	degrees	-95° / +185°	
			Side shift	mm.	-800 / +800	
			Lateral oscilation	degrees	+ / - 3°	
11	Steering		Hydraulic - Servo-assisted			
	Drive axle				With epicyclic reduction gears	
12	Tyres		Number front /rear		4/2	4/2
			Size on front		18.00 - 25	18.00 - 25
			Size on rear		18.00 - 25	18.00 - 25
13	Service brakes	Front			Disc oil bath	
		Rear	Optional		Disc dry	
	Parking brake		Mechanical release		Dry disc on transmission	
14	Battery		Voltage / capacity	V/Ah	24 / 200	24 / 200
15	Motor				See Motor Table	
16	Transmission				Hydrodynamic with torque converter	
17	Clutch				Power-Shift	Power-Shift
18	Gear selector		Forward / Reverse	No.	4 / 4	4 / 4
19	Hydraulic cooling system				Yes	Yes
20	Controls				servo-assisted	
21	Tank capacity		Hydraulic fluid	litres	1000	
			Fuel		550	