

Solis

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

16



**SMART
ERGONOMICS DESIGN**

**EASY OPERATE
METAL BONNET**

**TWIN PROJECTOR
HEADLAMPS**

**AGRI/IND./TURF
TYRE OPTION**

**REINFORCED SAFETY
FEATURES**



**XTRA EFFICIENT *STAGE*
3 CYLINDER
S-TECH ENGINE**



**COST
EFFICIENT**

MECHANICAL TRACTORS

MADE OF

**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH**

YANMAR



Solis



FEATURES	16
ENGINE	
Engine Type	ITL 3 Cylinder 16 Hp
HP Category	16
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	979
Rated RPM (+/-25mm)	2700
Air Cleaner	Dry with clogging sensor
Cold Start	Standard
Max Torque (Nm)	48
Exhaust	Silencer in the engine compartment, downward discharge
TRANSMISSION	
Drive	4 WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Front Axle	4WD
Transmission	SLIDING MESH
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	15.1@2900
Minimum Speed (Km/Hr)	1.36@rated
BRAKES	
Brakes	Dry drum brake
Type of Actuation	Mechanical
Parking Brake	Independent
Differential Lock	
Differential Lock	Yes, Foot Operated
PTO	
PTO (rpm)	540, 1000
PTO (actuation)	Mechanical
STEERING	
Steering	Mechanical
ELECTRICAL	
Battery	12V, 60 Ah
Alternator	12V, 42 A
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Additional hydraulic circuit	1DA (Optional Feature)
Hydraulic Lifting Capacity	500 Kg
Lift Rods	Standard
Litre per Minute(LPM)	12

FEATURES		516	
SAFETY SWITCH 			
PTO Safety		Standard	
Neutral Safety Switch		Standard	
Clutch Safety Switch		Standard	
CAPACITY (LTRS)(+/-5%) 			
Fuel Tank (Lit)		26	
TURNING RADIUS 			
Without brakes (m) as per standard tyres		3.2 (RHS), 3.3 (LHS)	
TYRE 			
Front		5.00-12	
Rear		8.00-18	
DIMENSION & WEIGHT(+/-5%) 			
Weight (Kg)		970	
Wheel Base (mm)		1420	
Total Length (mm)		2735	
Total Width (mm)		945(max)-940(min)	
Height (mm) Up to ROPS		1945	
Min Ground Clearance (mm)		200	
Front Track (mm)		805	
Rear Track (mm)		715	
OTHERS 			
Fuel Indicator Gauge		Standard	
Front Tow Hook		Standard	
Trailer Hitch		Drawbar / Optional Towbar	
ROPS		Yes	
OPTIONAL FEATURES 			
Cabin Option		No	
Front & Rear Weights with std. Ballast		Front weights 30 Kg - 2 x 15 Kg (Optional Feature)	
Beacon Light		Optional	
Tyres			
			
Radial Agri: Front Rear	Turf: Front Rear	Ind: Front Rear	GALAXY PRO
Front 6.5/80-12 REAR 280/70 R18	23x8.50-12 33x15.5-16.5	23x8.50-12 33x15.5-16.5	FRONT 220/55R12 REAR 280/70R16
Front loader		YES optional	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solis.com | URL: www.solistractors.com/www.solisworld.com